

SEP 20 2000

ENGINEERING DATA TRANSMITTAL

Page 1 of 1

1. EDT

630024

2. To: (Receiving Organization) Distribution		3. From: (Originating Organization) TFR&SO		4. Related EDT No.:							
5. Proj./Prog./Dept./Div.: Project W-314/RPP		6. Design Authority/Design Agent/Cog. Engr.: D.E. Bowers		7. Purchase Order No.:							
8. Originator Remarks: This modification will not change collective dose since it has no impact on radiological sources, contamination control, or shielding. USQ not required per HNF-IP-0842, Vol. IV, Section 5.4, Rev. 12				9. Equip./Component No.:							
				10. System/Bldg./Facility:							
				12. Major Assm. Dwg. No.:							
				13. Permit/Permit Application No.:							
11. Receiver Remarks:		11A. Design Baseline Document? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		14. Required Response Date:							
15. DATA TRANSMITTED											
(A) Item No.	(B) Document/Drawing No.	(C) Sheet No.	(D) Rev. No.	(E) Title or Description of Data Transmitted	(F) Approval Designator	(G) Reason for Transmittal	(H) Originator Disposition	(I) Receiver Disposition			
1	RPP-6764		0	Master Pump Shutdown	Q						
				Software Quality							
				Assurance Plan (SQAP)							
16. KEY											
Approval Designator (F)		Reason for Transmittal (G)			Disposition (H) & (I)						
E, S, Q, D OR N/A (See WHC-CM-3-5, Sec. 12.7)		1. Approval 2. Release 3. Information 4. Review 5. Post-Review 6. Dist. (Receipt Acknow. Required)			1. Approved 2. Approved w/comment 3. Disapproved w/comment 4. Reviewed no/comment 5. Reviewed w/comment 6. Receipt acknowledged						
17. SIGNATURE/DISTRIBUTION (See Approval Designator for required signatures)											
(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN	(G) Reason	(H) Disp.	(J) Name	(K) Signature	(L) Date	(M) MSIN
1	1	Design Authority DE Bowers	D.E. Bowers	9/11/00	S5-13	1	1	DST Cog. Eng.	WD Winkelman	9/11/00	S5-05
		Design Agent				1	1	Ops	RP Raven	9/13/00	S0-09
1	1	Cog. Eng. RR Bevins	RR Bevins	9/11/00	R3-25						
1	1	Cog. Mgr. KN Jordan	KN Jordan	9/18/00	R3-25						
1	1	QA TL Bennington	TL Bennington	9-18-00	R2-89						
		Safety									
		Env.									
18. Signature of EDT Originator RR Bevins 9/11/00		19. Authorized Representative for Receiving Organization Date		20. Design Authority/Cognizant Manager KN Jordan 9/18/00		21. DOE APPROVAL (if required) Ctrl No. _____ <input type="checkbox"/> Approved <input type="checkbox"/> Approved w/comments <input type="checkbox"/> Disapproved w/comments					

Master Pump Shutdown MPS Software Quality Assurance Plan (SQAP)

Robert R. Bevins

CH2M Hill Hanford Group Inc., Richland, WA 99352

Richland, WA 99352

U.S. Department of Energy Contract DE-AC06-96RL13260

99RL14047

EDT/ECN: 630024

UC: 2000

Org Code: 7C900

Charge Code: 109749

B&R Code:

Total Pages: **37**

Key Words: Master Pump Shutdown System, Software Quality Assurance Plan (SQAP) MPSS, Tank Farm Restoration and Safe Operations


Abstract: The MPSS Software Quality Assurance (SQAP) describes the tools and strategy used in the development of the MPSS software. The document also describes the methodology for controlling and managing changes to the software.

*Windows NT is a registered trademark of Microsoft Corporation

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.


Release Approval Date



Approved For Public Release

PROJECT W-314

SOFTWARE QUALITY ASSURANCE PLAN

FOR







MASTER PUMP SHUTDOWN SYSTEM

(MPSS)

Prepared for

CH2M HILL Hanford Group, Inc.

September 2000

Approval:	 J. L. Dowell, FFS/TFSRO, Control Systems Lead Engineer	<u>9-13-00</u> Date
Approval:	 P.J. Bedell, FFS/TFSRO, Principal Lead Engineer	<u>9-13-00</u> Date
Approval:	 R.M. Tanner, FFS/TFSRO, Project Manager	<u>9-13-00</u> Date
Approval:	 K. N. Jordan, CHG, Project Manager	<u>9-18-00</u> Date
Approval:	 D. E. Bowers, RPP, Design Authority	<u>9-14-00</u> Date
Approval:	 R. P. Raven, CHG, Retrieval Operations	<u>9-13-00</u> Date

Software Quality Assurance Plan for MPSS

RPP-6764
Revision 0
Page 2

REVISION HISTORY			
Rev.	Date of Issue	Description	Remarks
0	8/01/00	For CHG Review and Release into RPP documentation control system.	Comments Incorporated. Ready for Release.

TABLE OF CONTENTS

Section	Page
1.0 INTRODUCTION.....	4
1.1 Quality Assurance Overview	4
1.2 Scope.....	5
1.3 Acronyms and Definitions.....	6
2.0 SQAP PROCESS	7
2.1 Precision Integration Products Checklist	7
2.2 MPSS Development Staff Personnel Requirements	8
2.3 Configuration Management.....	8
3.0 REFERENCES.....	8
APPENDIX A PRECISION INTEGRATION PRODUCTS CHECKLIST	9
APPENDIX B DEVELOPMENT PERSONNEL POSITION REQUIREMENTS	12
APPENDIX C MPSS DEVELOPMENT STAFF PERSONNEL PROFILE FORM	13
APPENDIX D CONFIGURATION MANAGEMENT PLAN INCLUDING SCR PROCESS	14
APPENDIX E CONFIGURATION CONTROL—SOFTWARE RELEASE PROCESS ...	29

1.0 INTRODUCTION

1.1 Quality Assurance Overview

This Software Quality Assurance Plan (SQAP) provides the basis for MPSS software quality assurance. The plan itself is based on activities within a Precision Integration life-cycle model (i.e., software development and maintenance model) developed by Fluor Federal Services (FFS). The basis for this plan is information contained within the FDH procedure, HNF-PRO-309, Revision 0, "Computer Software Quality Assurance Requirements".

Precision Integration (Figure 1) depends on several iterations (or cycles) of the following segments:

- Define (Requirements)
- Design
- Implement
- Test (Informal and Formal)




Figure 1 Precision Integration Cycles

The first cycle is referred to as the top cycle. The majority of development effort takes place in this iteration to avoid costly rework in future iterations. Each additional cycle refines the software system, but allows for changes to all aspects (e.g., a requirement change). As cycles are performed, the time duration of each cycle becomes increasingly shorter, as does the number of problems related to testing exceptions. This ~~is~~, in essence, meets an approved type of overall IEEE software lifecycle model, referred to as a “waterfall” type model.

The key to this SQAP is that it creates a balance between oversight and staff productivity. The W-314 project has many Phases. Phase I of MPSS is construction of an MPSS Operator Trainer, with migration of this MPSS system’s Human Machine Interface (HMI) and logic to several other tank farms, and a full mock-up test of the migrated MPSS in FY01. Phase II sees continued expansion and equipment configuration updates to the system. Therefore, this plan shall deal with activities, through Phase II, which are entirely within the Precision Integration model shown in Figure 1, and that allows for maintenance in future phases.

The process shall include products for Define, Design/Implement, and Test segments. In addition, where ever informal maintenance is no longer adequate, a formal configuration management plan shall be instituted for all changes to the system software.

The configuration management shall include a method for releasing baseline versions of the MPSS, and reporting, fixing, and closing issues, enhancements and/or problems. Note that the MPSS Operator Trainer Modicon logic diagrams are currently configuration controlled within AutoCAD. A conversion to the RTP product line will occur to address safety class and general service designations through the MPSS. At that point, the converted drawings shall be controlled within RTP Net Arrays software, with version control provided by this plan.

1.2 Scope

This Software Quality Assurance Plan (SQAP) provides the plan strategy and description of the tools used in performance of the Master Pump Shutdown System (MPSS) software development and maintenance.

This document does not provide a description of the MPSS requirements. For more information related to the MPSS requirements refer to HNF-SD-W314-PDS-004.

1.3 Acronyms and Definitions

CATS: Computer Automated Testing System. A database application, or test engine, that takes specific test data tables and converts them into automatic and human interaction-based tests. The CATS gathers all test responses, comments, and compares results to generate sets of passing and exception reports.

ECN: Engineering Change Notice

EDT: Engineering Data Transmittal

FDH: Fluor Daniel Hanford

FFS: Fluor Federal Services

HMI Software: A Human-Machine Interface software package developed by Ci Technologies, Citect, is used to create the human-machine interface portion of the DAS. The PC-based package works within the Microsoft Windows NT environment to provide graphic displays with user-friendly controls.

IP: In Progress

MPSS: Master Pump Shutdown System. Operator HMI for setting up and verifying waste transfer routes from tank to tank (up to six simultaneous). Also has interlocks connected to leak detection devices to ensure orderly shutdown of affected transfer lines.

PC: Personal computer used with HMI software to provide the human-machine interface.

PDS: Project Development Specification

PE: Professional Engineer certification from the State of Washington.

PLC: The Programmable Logic Controller is the microprocessor-based industrial controller capable of real-time control. It provides all of the discrete and process control logic required for controlling and/or monitoring the process. Once the program has been loaded into the controller module, it will execute all control/monitoring functions even if connection to the HMI computer is severed or interrupted.

PM: Project Manager

QTP: Qualification Test Procedure

RCR: Review Comment Record

Real-time: Indicates that monitoring and control signals are being processed and implemented in an acceptable time frame which is usually after an imperceptible time delay after the actual process events.

RPP: River Protection Project

SIMCart: Simulator Cart. When used with CATS, SIMCart provides a method for emulating all applicable field I/O virtually so as to fully test a finished system's HMI and PLC.

SQAP: Software Quality Assurance Plan. A method utilized to assure quality performance of software development.

V&V: Verification and validation. Process of ensuring that software products and/or systems are reviewed and checked/tested thoroughly at the different stages of implementation in the lifecycle model.

2.0 SQAP PROCESS

This section describes the tools available, and how and when to apply these tools. The process is primarily document and form based. The following are the tools that shall be described.

- ◆ **Appendix A Precision Integration Products Checklist**
- ◆ **Appendix B Development Personnel Requirements**
- ◆ **Appendix C MPSS Development Staff Personnel Profile Form**
- ◆ **Appendix D Configuration Management Plan Including SCR & Testing Evaluation Process**
- ◆ **Appendix E Configuration Control—Software Release Process**

2.1 Precision Integration Products Checklist

In Appendix A is the primary tool--a checklist that shows the different Precision Integration Iteration Segment products generated for the MPSS. The Appendix A checklist is used to assure that when an iteration segment (i.e., define, design, implement, test) is entered, the effect of the system change or implementation is fully evaluated, and the products are generated or modified with appropriate V&V. This will ensure that 1) the effect of a change to the system is evaluated before the change is made, and 2) the system documentation reflects the current state of the system after a change is implemented. This checklist is to be reviewed 1) during implementation of the initial system and 2) for SCR/PR(s) implementation during system upgrades and maintenance.

2.2 MPSS Development Staff Personnel Requirements

This list in Appendix B provides staffing requirements for the MPSS Software Development Personnel. The form in Appendix C shall be filled out for each person and kept in a desk reference by the MPSS PM.

2.3 Configuration Management

There are two procedures, in Appendix D and E, that account for MPSS developed software configuration management and releases respectively.

3.0 REFERENCES

1) HNF INFORMATION RESOURCE MANAGEMENT PROCEDURES

HNF-PRO-309, Computer Software Quality Assurance Requirements, Revision 1

HNF-PRO-2778, IRM Application Software System Life Cycle Standards, Revision 0

2) HNF ENGINEERING PROGRAM

HNF-PRO-244, Engineering Data Transmittal Requirements

HNF-PRO-440, Engineering Document Change Control Requirements

APPENDIX A PRECISION INTEGRATION PRODUCTS CHECKLIST

Review Process Products (To be Updated by MPSS PM as Products are Released—Check when Done and Fill in Tracking ID)						
Project Iteration Segment	Review Product Identifier	Title	Expected Tool Used	Responsible	Description	
DEFINE <input type="checkbox"/>	1) HNF-SD-W314-TI-004	PDS	EDT/ECN	Client	Describes specific requirements that may be utilized as acceptance criteria.	
	2) HNF-SD-W314-TI-008	PDC	Process		Describes enhancements to the system authorized outside of and complementary to the PDC/PDS.	
	3) Enhancements per modifications to 1) or 2) or per SCR/PR form.	SCR/PR(s)	SCMP Process	Change Control Board (CCB)		
DESIGN <input type="checkbox"/>	1) Validation Report (V&V) of design per PDC/PDS	RVR	EDT/ECN Process	MPSS PE	Describes how the implemented System design meets the PDS Requirements.	
	2) V&V of SCR/PR(s) enhancements	SCR/PR(s)	SCMP Process	MPSS PE	Ensures that the SCR/PR(s) effects and enhancements are documented in Programmer's /Design Document	
	3) Programmer's/Design Document	PROG/DES	EDT/ECN	MPSS PE	Describes the system design for HMI screens, taglists, functions, buttons, general operations, and generic functional logic of the PLC.	

Project Iteration Segment	Product Identifier	Title	Expected Tool Used	Responsible	Description
IMPLEMENT <input type="checkbox"/>	1) V&V design implementation	PDC, PDS Check	Yellow-Line Check Process	HMI and PLC Engineers /MPSS PE	Check of HMI, PLC and database implementation per design document.
		SCR/PR(s) Check	SCMP Process	HMI and PLC Engineers /MPSS PE	Check of HMI, PLC and database implementation per design document.
TEST <input type="checkbox"/>	1) All releases of software code for test to a physically separate storage device per SCMP Appendix D numbering Scheme. 2) V&V system implementation per test cases	TEST REL	O/S Network Drive AP012/FDNNWPROJ/PRO JECTS\W- 314\RELEASESE0.X<release date>	HMI and PLC Engineers /MPSS PE	All MPSS Project configured electronic files, libraries, etc. including compiled code, source code, etc., for test
		QTP and/or ATP and/or OTP and/or SCR/PR(s) test(s)	Test Cases (e.g., CATS and/or paper-based). Test Evaluation Forms, SCMP	HMI and PLC Engineers /MPSS PE	Check of HMI, PLC and database Implementation per PDC, and/or, PDS, and/or SCR/PR(s) enhancements.
SYSTEM RELEASE <input type="checkbox"/>	1) Releases of V&V'd code to a physically separate storage device per SCMP Appendix D numbering scheme.	SYSTEM REL	O/S Network Drive AP012/FDNNWPROJ/PRO JECTS\W- 314\RELEASESE0.X<release date>	HMI and PLC Engineers /MPSS PE	All MPSS Project configured electronic files, libraries, etc. including compiled code, source code, etc.

Concurrent Activities	Description	Title	Tool Used	Responsible	Description
CONFIGURATION MANAGEMENT <input type="checkbox"/>	Internal Work Control 1) SCR Logbook	CFMG/SCR	SCR/PR (Appendix D)	MPSS PE	Tracks all system problem reports or change requests (e.g., enhancement).
	2) Test Evaluation Form Logbook	CFMG/TEF	Test Evaluation Form (TEF) (Appendix D)	MPSS PE	Tracks all SCR/PR testing Evaluations and Results.
	3) Release Log and Logbook	CFMG/REL	Network Drive AP012/FDNNWPROJ/PRO JECTS/W- 314/RELEASE0.X<release date> (Appendix E)	Lead HMI/ MPSS PE	Tracks releases of MPSS baselines
TRAINING RECORDS <input type="checkbox"/>	Internal Work Control 1) Development Personnel Position Requirements	TR	Form (Appendix B)	MPSS PM	Position certification and training requirements
	2) Personnel Profiles of all MPSS Development Staff	PROF	Form (Appendix C)	MPSS PM	Personal profiles to document meeting MPSS Development Personnel Requirements.

APPENDIX B DEVELOPMENT PERSONNEL POSITION REQUIREMENTS

All persons filling the below positions on the Project W-314 MPSS development must be certified by the MPSS Project Engineer or Manager to meet the listed qualifications for the position. The certification is to be documented on the form in Appendix C. If the position required is not listed below, please contact the MPSS PM.

PROJECT MANAGER/ENGINEER/LEADS:

- 1) A degree in engineering or a Washington State Professional Engineering License.
- 2) 2 years project management experience.
- 3) Current with FFS procedure training per the EMPORTS reading list.

PLC PROGRAMMERS:

- 1) 2 years of engineering training/experience related to control systems.
- 2) Knowledge of ladder and function block logic (Note: a junior programmer with less than two years experience can work under the guidance of a qualified programmer).
- 3) Current with FFS procedure training per the EMPORTS reading list.

HMI PROGRAMMERS:

- 1) 2 years experience developing human machine interface screens with Citect or equivalent HMI development tool (Note: a junior programmer with less than two years experience can work under the guidance of a qualified programmer).
- 2) Current with FFS procedure training per the EMPORTS reading list.

DATABASE PROGRAMMERS:

- 1) 2 years experience developing relational databases using Microsoft Access or equivalent database software (Note: a junior programmer with less than two years experience can work under the guidance of a qualified programmer).
- 2) Current with FFS procedure training per the EMPORTS reading list.

LOGIC REVIEWERS:

- 1) Washington State Professional Engineering License in either Control Systems or Electrical engineering.
- 2) Current with FFS procedure training per the EMPORTS reading list.

INTEGRATION TESTERS:

- 1) A degree in engineering or background in a technical field.
- 2) Current with FFS procedure training per the EMPORTS reading list.

HMI TESTERS:

- 1) A degree in engineering or background in a technical field.
- 2) The ability to effectively operate a PC using Microsoft Windows and Office Programs

APPENDIX C MPSS DEVELOPMENT STAFF PERSONNEL PROFILE FORM

<i>Project W-314 MPSS Personnel Profile Form</i>
Name (First MI Last):
Position Title (See Appendix B of MPSS SQAP—more than one title may be submitted for multi-tasking personnel):
Note: If a reviewer, ensure that the person is independent of the work being inspected, unless informal.
Position-Related Qualifying Education, Certification, and Experience:
If deficient for position requirements, mark here <input type="checkbox"/>
If marked, but personnel is to be used on a task—state action plan, completion date, and mentoring position engineer below:
Reviewed by: (Print and Sign Name and Date)

APPENDIX D CONFIGURATION MANAGEMENT PLAN INCLUDING SCR PROCESS

Configuration Management Plan For Master Pump Shutdown System (MPSS)

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 MANAGEMENT**
- 3.0 SOFTWARE CONFIGURATION MANAGEMENT ACTIVITIES**
 - 3.1 CONFIGURATION IDENTIFICATION**
 - 3.2 CONFIGURATION CONTROL**
 - 3.3 CONFIGURATION STATUS ACCOUNTING**
 - 3.4 AUDITS AND REVIEWS**
 - 3.5 ACCESS CONTROL**
 - 3.6 BACKUP AND RECOVERY**
- 4.0 TOOLS, TECHNIQUES AND METHODOLOGIES**
- 5.0 SUPPLIER CONTROL**
- 6.0 RECORDS COLLECTION AND RETENTION**
- 7.0 REFERENCES**
- 8.0 SOFTWARE CHANGE REQUEST AND PROBLEM REPORT FORM**
- 9.0 MPSS SCR/PR TESTING EVALUATION FORM**

1.0 INTRODUCTION

1.1 PURPOSE

This Configuration Management Plan (CMP) provides the instructions for change & version control of the Master Pump Shutdown System (MPSS) software.

1.2 SCOPE

This plan applies to the MPS system software to be used by CH2MHILL (CHG) and includes the computer software source and executable code. This also applies to special configurations of vendor software (e.g., Windows NT 4.0, etc.). Control of information produced by the software once it has been exported is the responsibility of the receiving organization. This plan is required for formal 1) development and 2) production release and system maintenance. Changes to design basis documentation, via ECN, will require following this CMP to evaluate MPSS impacts.

1.3 OVERVIEW

The primary purpose of the MPSS is to provide an automated approach (via PLC & an HMI) to the safe and orderly shutdown of waste transfers in case of leak detection.

1.4 DEFINITIONS

Production: Pertaining to the status of a given system following acceptance by the customer.

Software Change Request and Problem Report (SCR/PR): A document that identifies a proposed change to or suspected problem with the WCS hardware and/or software. An SCR/PR may identify a new function, modify an existing function or report suspected problems of the software.

System and Software Configuration Management (SCM): A set of management disciplines within the context of the software engineering process that applies technical and administrative direction and surveillance. It identifies and documents the functional and physical characteristics of a product, controls changes to those characteristics, and it records and reports the change processing and implementation.

SCR/PR Testing Evaluation Form: A document that allows an SCR/PR(s) to have testing analysis performed to identify appropriate test cases to be planned. The test cases are then attached to this form, approved by the change control board, and the tests performed to close out the SCR/PR process.

2.0 MANAGEMENT

2.1 ORGANIZATION

CH2MHILL Hanford (CHG)--shall be designated as MPSS system owner, operator and maintenance authority.

Fluor Federal Services (FFS)--shall be designated MPSS developer, maintainer and custodian in conjunction with CH2MHILL Hanford.

2.2 RESPONSIBILITIES

Function	Organization	Individual	Responsibilities relative to this plan.
Design Authority	CHG	Dave Bowers	<ul style="list-style-type: none"> o Design Authority (Cognizant Engineer) o Approves SQAP o Approves OT (Operator Trainer) o Communicates Impacts (due to PDS, equipment, etc.) via SCR/PR o Approves SCR/PR that differ from PDS-based OT o Approves QTP and Oversees QTP, and Reviews QTR o Reviews All SQAP Products Generated o Reviews and Approves All SCR/PR Testing Evaluation Forms Generated, and Approves Test Results
Lead Engineer (LE)	FFS	Dwight Brayton	<ul style="list-style-type: none"> o Overall Responsibility For SCM and Design Agent of record. o Evaluate and implement changes resulting from SCR/PR. o Evaluate SCR/PR for impact on cost, schedule, & deliverables. o Maintain SCR/PR and SCR/PR log (log is paper-based and contained in a binder) at 1200 Jadwin, floor 3/cubicle 3. o Maintain a library of all associated correspondence, personnel assignments, documentation, deliverables, reports, logs, software, etc., in their most up-to-date version. Location is at 1200 Jadwin, floor 3. o Provide CCB liaison for testing evaluation forms.
Change Control Board (CCB) Chair	CHG	Bob Bevins	<ul style="list-style-type: none"> o Accept/prioritize work proposed by SCR/PR. o Approve or disapprove test plan/completed testing results from SCR/PR implementation o CCB members include CCB Chair, Design Authority, and others as appointed by the CCB Chair on a permanent or a case by case basis, with assistance and input from the Lead Engineer.
System and Software Developer & Maintainer	FFS	Dwight Brayton	<ul style="list-style-type: none"> o Provides development and maintenance
System and Software Custodian	FFS	Dennis Lauhala	<ul style="list-style-type: none"> o Ensure backup and recovery of application and software. o Ensure proper labeling and storage of backup media, as applicable. o Ensure correct software is installed for production use. o Ensures problem reports are distributed to development team/users.
Software Engineer(s)	FFS	Various	<ul style="list-style-type: none"> o Do the work identified in SCR/PR and conduct tests. o Ensure adequate tests are performed—fill out test evaluation form. o Document test results and include with change request, or indicate supporting document number if applicable. o Obtain independent review of SCR/PR, as required.
Report problems and submit change requests	Any Org. Involved w/ MPSS	Anyone In MPSS Organization	<ul style="list-style-type: none"> o Identify and report problems on a SCR/PR form. o Submit changes on a SCR/PR form.

(1) The appointed individual may be changed via internal memorandum or e-mail, signed by the organizational manager. Memorandum to be maintained in the MPSS PM desk files. Modification to this SCMP not required.

2.3 IMPLEMENTATION

This CMP becomes effective whenever a problem or change request is identified, either internally (prior to release to CH2MHILL Hanford for Production) or externally. Overall responsibility for the SCM activity rests with the Lead Engineer described in Section 2.2. Version change control of source code and executables becomes effective when released for correction of SCR groups, testing for major revisions, and/or released for production on minor revisions.

2.4 POLICIES AND PROCEDURES

Configuration management of the MPSS software items will be in guidance from HNF-PRO-309, particularly with regards to Software Control, Change Request & Problem Reports, and Document Approvals.

3.0 SOFTWARE CONFIGURATION MANAGEMENT ACTIVITIES

Configuration Management will be applied to the MPSS software items per the requirements established and steps provided herein.

3.1 CONFIGURATION IDENTIFICATION

3.1.1 Application Software

Design basis documentation which sets the foundation for the configuration of the MPSS software is found in the PDS associated references.

The local HMI which displays messages, alarms, and information to the operator are via Personal Computers with Windows NT O/S and using Citect as the Human Machine Interface (HMI). The HMI is used for all monitoring and initiation of control.

Each production for HMI software releases shall be a grouping of the code and executable software products, and any modifications to vendor software (e.g., configurations, etc.). The release is assigned a unique release number by the MPSS System and Software Custodian.

The software release number is of the form R.r as described in HNF-PRO-464, Software Control. Please refer to the sample form in the "Release Cover Sheet and Revision Record", Appendix E.

If the R is absent, the MPSS software is still in the Development phase.

3.1.2 Software Products

Each software product (e.g., the application software development packages, the operating system software, the network communications software, etc.) is assigned a unique product name

and release version number by the appropriate vendor and will be used as identification as much as practical on the software release documentation.

3.1.3 Computer Hardware

Computer hardware, such as installed field PLCs is controlled by normal Hanford administrative procedures (e.g., H-2 drawing system via Engineering Data Transmittals (EDT) and Engineering Change Notices (ECN)), Ref. 2. Configuration control is required by the MPSS, only for the cases of 1) identification of the minimum equipment necessary for operation and 2) evaluation of MPSS local and remote HMI and/or PLC impact, caused by field hardware changes that are part of the design basis documentation set--via an SCR/PR.

3.1.4 Documentation

Each MPSS document is assigned a unique name, number, and revision in accordance with the HNF/RPP documentation procedures and is documented.

MPSS SCR/PR forms shall be kept in local project files in log form by the Lead Engineer. When a Release of the MPSS system occurs, the Lead Engineer will ensure that the Release information is completed and associated SCR/PRs are updated.

MPSS SCR/PR testing evaluation forms shall be kept in local project files in log form by the Lead Engineer. When a Release of the MPSS system occurs, the Lead Engineer will ensure that the Release information is completed and associated testing evaluation forms are updated.

3.1.5 Application Reports

Control of application reports generated by the MPSS is not provided under this CMP, and is the responsibility of the software user organizations.

3.1.6 Removable Media Labels

Removable media shall be labeled consistent with the following information on the label:

- Media identifier (i.e., disc number)
- Software identification
- Software revision identification ("R.r", "R" = major and "r" = minor software changes, e.g. 1.0)
- Software or data name or description
- Responsible organization and software custodian's name
- Recording date and time.


3.1.7 Directory Nomenclature

Original or backup source and executable software placed on media containing multiple versions/revisions shall be segregated using the available directory/ subdirectory structure.

A major directory shall be provided for the software product, labeled with the product mnemonic. Subdirectories shall be provided for each major revision. Each minor revision shall be contained in a separate sub-subdirectory, uniquely identified with the appropriate revision number. The subdirectory name shall contain the major and minor revision number, separated by a period. For example:

AP012/FDNWPROJ/PROJECTS/W-314/RELEASE0.X<release date>

A sample directory listing is shown:



3.2 CONFIGURATION CONTROL

SCR/PR approvals are recorded and submitted using the SCR/PR form.

E-mail approvals for processing SCR/PRs may be substituted for handwritten approvals. When e-mail approvals are used a copy of the e-mail approval must be attached to the SCR/PR.

Telephone approvals for processing SCR/PRs may be used, but subsequently, must be documented on the SCR/PR form or with an e-mail approval.

SCR/PR testing evaluation form approvals are recorded and submitted using the testing evaluation form, or electronic equivalent (e-mail approval okay).

3.3 CONFIGURATION STATUS ACCOUNTING

The configuration status of all controlled items is documented in Release information per Appendix E of the MPSS SQAP. In addition, the status of all SCR/PRs, testing evaluation forms, and associated releases will be maintained and is available from the Lead Engineer.

3.4 AUDITS AND REVIEWS

The MPSS and associated documentation, including software change control, will be available for audit during normal working hours. The MPSS System and Software Administrator should periodically audit the project file and change control documentation to ensure compliance. Other surveillance and audits are the responsibility of other outside organizations and are outside the scope of this plan.

All changes and tests shall be reviewed (verified) by an independent technical person. For minor changes and releases, test results may be attached to the SCR/PR. For major changes and releases, refer to Testing Evaluation Form log.

Should changes require major modifications or enhancements, the Lead Engineer, Software Engineer, and Design Authority will determine if a formal plan will be prepared. The formal plan will identify appropriate technical, V&V and QA reviews consistent with HNF procedures and commensurate with the complexity of the change.

3.5 ACCESS CONTROL

Access control for operation of the MPSS software is administrative. However, to make changes to the MPSS code requires software other than what is available to the user through the local or remote HMI.

3.6 BACKUP AND RECOVERY

Backup shall be from the most recent set of release files per Section 3.1.7.

Backup of the source code and executable files that constitute each product release is done by the software custodian onto the fileserver backup partition selected and documented by the Software Custodian--for example "\\DCH\PROJECTS\WCS\SCMP\" (see section 3.2.1) at the time of release. The Software Custodian is responsible for verifying that the backup is in place and the appropriate files exist.

Recovery shall be accomplished by rewriting the appropriate files from the master media onto the production fileserver or its replacement. This shall be accomplished by the System and Software Custodian or Lead Engineer/Software Engineer as needed. Should the master media be simultaneously corrupt, recovery shall be from the backup fileserver partition.

4.0 TOOLS, TECHNIQUES AND METHODOLOGIES

Tools and instructions for software administration and usage are contained in Ref. 1.

All MPSS software release modifications will be completed and certified in a test environment where possible. Tests are informal up to the point of the QTP. At this point, rigorous testing methods shall be utilized to test the MPSS. This includes a testing evaluation for each SCR/PR

All MPSS software modifications/enhancements will be completed and certified in a test environment where possible. These changes will be implemented into the production environment only after the Design Authority has reviewed and approved the test results and the Change Control Board has approved the implementation. Modifications and enhancements will be grouped logically into production releases.

5.0 SUPPLIER CONTROL

The System and Software Developer & Maintainer will ensure that new releases and installation of the vendor application and software product are tested prior to its being placed in production. Changes in vendor application and/or software product will be processed as a change request or problem report with the same approval requirements as a locally generated change.

The System and Software Developer & Maintainer will maintain a software project file or binder of all system and software-related project documentation, correspondence, and project produced documents. This may be in the form of reference to released (e.g., HNF) documentation. Vendor provided materials and manuals will be maintained by the System and Software Custodian. This software project file or binder will maintain the most current version of all documents for the life

of MPSS.

6.0 RECORDS COLLECTION AND RETENTION

The MPSS System and Software Developer and Maintainer will process software development and maintenance records in accordance with HNF-PRO-309. These records, include at a minimum the SCR/PR log book and SCR/PR form entries, the Testing Evaluation log book and Testing Evaluation form entries, and will be kept by the Lead Engineer in local project files and/or logbooks.

7.0 REFERENCES

1) HNF INFORMATION RESOURCE MANAGEMENT PROCEDURES

HNF-PRO-433, Small Job Development,
HNF-PRO-555, System Configuration Management Plan,
HNF-PRO-464, Software Control
HNF-PRO-564, Records Retention and Disposal.

2) HNF ENGINEERING PROGRAM

HNF-PRO-244, Engineering Data Transmittal Requirements
HNF-PRO-440, Engineering Document Change Control Requirements

8.0 MPSS SYSTEM AND SOFTWARE CHANGE REQUEST AND PROBLEM REPORT FORM

MPSS SYSTEM AND SOFTWARE CHANGE REQUEST OR PROBLEM REPORT (SCR/PR)		
NOTE: Submitter Fills In Parts 1-8 (NON-GRAY)		FOR FFS USE ONLY
1. SCR/PR Type: <input type="checkbox"/> Problem <input type="checkbox"/> Enhancement		SCR Number:
2. Submitted By:		Date:
3. Project Name:		W/O:
4. Areas Affected (check): <input type="checkbox"/> PLC <input type="checkbox"/> HMI <input type="checkbox"/> Database <input type="checkbox"/> Operating System		Current Ver/Rev: Appendix A Evaluation <input type="checkbox"/> <input type="checkbox"/> (check when complete)
5. Submitter's Priority <input type="checkbox"/> (1= Critical 2= Very Important 3= Important 4= Inconvenient 5= Interesting)		6. Requested Completion Date:
7. Task/Change/Problem Title (One Sentence Description):		
8. Detailed Description/Justification (Attach Additional Sheet If Necessary):		

Decision By:	<input type="checkbox"/> Accept <input type="checkbox"/> Modify <input type="checkbox"/> Reject <input type="checkbox"/> Defer
Assigned To:	Target Release Date:
Resolution:	
System and Software Programs, Modules or Files Affected:	
Task Completed By:	Date:
Verified By:	Date:
Actual Release Version:	Date:
Closed By:	Date:

These instructions are for preparing the Change Request or Problem Report. If more space is needed, use blank pages and attach to the SCR/PR form. This will be the record of the change request or problem report.

Submitter (Anyone In MPSS Organization may submit) :

1. Fill out Sections 1-8 of the form—DO NOT fill in gray areas.
2. Suggestions for SCR resolution may be put into the Detailed Description section.
3. Provide a description of the changes requested or the problems being reported.
4. Attach additional sheets if necessary.
5. An E-mail to start the process is acceptable as long as an SCR form is filled out and logged.

Lead Engineer:

1. On receipt, enter into the MPSS SCR/PR Log. Enter the next SCR number on the form.
2. Track information by entering into the SCR database.
3. Enter the date received.
4. Enter current Version/Revision of the product.
5. Evaluate SCR/PR or group of SCR/PRs against Appendix A of this SQAP. Check when complete, and ensure activities are completed.
6. Review change request or problem with development personnel.
7. Note that SCR/PR may require attached cost estimate and planning by the Lead Engineer if extensive change or testing are anticipated.

Log ID # :	Summary Information Table						
SCR/PR Number(s) to be tested:							
1.	Submitted By:						
2.	Date:						
3.	Current Release:						
4.	Describe Overall Impact to MPSS System from SCR Changes (document for each SCR):						
5.	Check the Box Indicating Analysis to be performed for each SCR(s)— List SCR(s)/or ALL: <input type="checkbox"/> Perform Design Analysis and Impacts Review (attach review) SCR/PR(s): <input type="checkbox"/> Perform Automated Cicode and/or Object Cross-Reference (attach results) SCR/PR(s): <input type="checkbox"/> Perform Automated Syntax/Spelling Check (attach results) SCR/PR(s): <input type="checkbox"/> Perform Other (specify and attach results) SCR/PR(s): Areas Affected (check): <input type="checkbox"/> PLC <input type="checkbox"/> HMI <input type="checkbox"/> Database <input type="checkbox"/> Operating System					6. Testing <input type="checkbox"/> SCR/PR(s) test cases (attach w/ results) <input type="checkbox"/> QTP test <input type="checkbox"/> ATP test <input type="checkbox"/> OTP test Reference Number: (Provide Review Copy)	
7.	Overall Test Approach Justification Summary for items in 6:						
FOR MPSS CCB USE ONLY:							
				SCR Resolution Information			
Decision By Change Control Board Chair/Designee:				[] Accept [] Modify [] Reject [] Defer			
Assigned To: FFS				Target Release Date:			
Reasons (If Modify, Reject or Defer—attach additional sheets as required) :							
Task Completed By: FFS				Date:			
Verified By Chair/Designee:				Date:			
Actual Release Version:				Date:			
Closed By Chair/Designee:				Date:			

These instructions are for preparing the SCR/PR Testing Evaluation Form. If more space is needed, use blank

pages. This will be the record of the testing evaluation for the SCR/PR.

Submitter (Software Engineer) :

1. Fill out Sections 1-7 of the form—DO NOT fill in gray areas.
2. Suggestions for SCR resolution may be put into the Detailed Description section.
3. Provide a description of the testing, including analysis and SCR/PRs affected.
4. Attach additional sheets if necessary.

Lead Engineer:

1. On receipt, enter into the MPSS SCR/PR Testing Evaluation Form Log. Enter the next SCR/PR Testing Evaluation Log ID # onto the form.
2. Forward, when appropriate, for review by the Change Control Board (CCB) Chair for action.
3. Receive, when completed by CCB, and assign for testing per form.
4. Forward, when testing is complete, to CCB for verification and closure.


Change Control Board Chairman:

1. Receive form for review and accept, modify, reject or defer on form. Give reason. Return to Lead Engineer for action.
2. Receive, when completed by Lead Engineer, test results for accepted forms.
3. Verify and take actions to close Testing Evaluation Form and send to Lead Engineer.

APPENDIX E CONFIGURATION CONTROL—SOFTWARE RELEASE PROCESS**Process for Internal Software Release(s)**

For an Internal release of Software within a FFS Project, Teams should follow the described process where applicable. This process needs to be an iterative function, as an example - leaving testing (other than the standard review of ones own work) to the end invites unnecessary risk and delays to timetables.

The Project Team shall maintain two versions of the current release. One version will be a developmental version that will be in a continued state of flux as developers add enhancements and correct defects to the application, the other will be a testing platform that will remain stable allowing testers a static plane from which to work.

**ORIGINATE**

Generate Software Change Request (SCR/PR) per SCMP (e-mail as temporary SCR okay).

REVIEW/ASSIGN

LE Determine(s) whether SCR/PR is a defect or an enhancement

- A. Prioritize accordingly (typically a bug fix will have a higher priority & an enhancement will be accompanied with a charge code)
- B. SCR/PR meetings shall be held as required to document priority of SCR/PR open list.

TEST

Focus on achieving the following before closing an SCR/PR.

Reliability: fix operates without crashing, hanging, causing exceptions, or

leaking resources

Functionality: fix addresses the problem & meets established PDS requirements

Application Performance: The application responds in a timely manner

System Performance: The application continues to perform as designed when it is subjected to production load. For every instance where the application does not meet expectations an SCR/PR is generated or the current SCR/PR is updated.

RELEASE

The Project Team will maintain two versions of the current release

Development Version (dynamic)

Testing Version (static)

Approval

Based on SCR/PR(s) successful testing completion. The development team issues a new release. This release, once reviewed by Project Management, will replace the existing release.

Use the Release form to document the release.

New Release

Replaces current Development/Testing versions of existing release

Old Release

Saved within the project directory

Current MPSS Release Procedure (Development—FY00 and FY01)

Purpose: Describe the Release Process used to release a version from MICRON2 (Devel Server) to MICRON3 as a test server and MICRON4 as a test client.

Note:

The structure of the project is:

Main Project = MPSS

Sub Projects = CBS, TR, WTA

The version number x will be used for all projects.

Right now, the "designated backup media" is an empty Jaz disk - all W314 workstations have a Jaz drive.

Applications used for Release:

Windows NT Explorer

Citect Explorer

Citect Project Editor

1. Devel Server(MICRON2): Backup the development version and move to the designated backup media, using the next release number in the filename (<project name>_r0x.CTZ).

Make sure to choose "compression" and "save subdirectories".

a. Citect Explorer -> Tools -> Backup

b. Backup each of the 4 projects: MPSS, CBS, TR, WTA

c. Backup Project MPSS

check: Compression

check: Save Subdirectories

File name: MPSS_r0x.CTZ

d. Backup Project CBS

check: Compression

check: Save Subdirectories

File name: CBS_r0x.CTZ

e. Backup Project TR

check: Compression

check: Save Subdirectories

File name: TR_r0x.CTZ

e. Backup Project WTA

check: Compression

check: Save Subdirectories

File name: WTA_r0x.CTZ

f. Move the backup files to Jaz drive.

2. Test Server(MICRON3): Restore the backups to a new project on the test server computer (MICRON3)

a. Citect Explorer -> Tools -> Restore

b. Restore the subprojects before restoring the main project.

c. Restore Project WTA

Restore from: Jaz drive

To: New Project

Name: WTA_r0x.ctz

Location: C:\citect\user

d. Restore Project Trainer

Restore from: Jaz drive

To: New Project

Name: TR_r0x.ctz

Location: C:\citect\user

- e. Restore Project CBS
 - Restore from: Jaz drive
 - To: New Project
 - Name: CBS_r0x.ctz
 - Location: C:\citect\user

- f. Restore Project MPSS
 - Restore from: Jaz drive
 - To: New Project
 - Name: mpss_r0x.ctz
 - Location: C:\citect\user

3. Server(MICRON3): Copy files from 'c:\citect\user\mpss_r0x\files\test comms' into 'c:\citect\user\mpss_r0x'. Replace all existing files.

4. Pack the files.

- a. Citect Project Editor -> File -> Pack

5. Server(MICRON3): Compile the project

- a. Citect Project Editor
- b. Select Project MPSS
- c. File -> Compile

6. Server(MICRON3): Windows NT Explorer

On the test server computer, go to the "Files" subdirectory of the project directory created in Step

2. Copy the file MPSS.MDB to C:\Citect\Data.

7. Server(MICRON3): On Test Server Computer, change the computer set up in Citect Explorer.

- a. Citect Explorer -> Tools -> Computer Setup
- b. Citect Computer Setup Wizard
 - Express setup
- c. Computer Role Setup
 - Server and Display Client
- d. Project Setup
 - Project Name: mpss_r0x
- e. I/O Server Setup
 - check: This computer is an I/O Server
 - I/O Server Name: <default>
- f. Internet Server Setup
 - unchecked: This computer is an Internet Server
- g. Alarms Setup
 - check: This computer is an Alarm Server
 - option: Primary Alarm Server

- h. Reports Setup
 - check: This computer is a Reports Server
 - option: Primary Reports Server
 - i. Trends Setup
 - check: This computer is a Trends Server
 - uncheck: Trends Server supports redundancy
 - j. Alarms, Reports and Trends Server Setup
 - This Server Name: MICRON3
 - Other Server Name: (blank)
 - k. Network Setup
 - Citect computer name: MICRON3
8. Server(MICRON3): Verify ODBC DSN.
- a. Control Panel -> ODBC DataSources -> User DSN tab
 - Select w314
 - Click Configure button
 - b. ODBC Microsoft Access Setup
 - Data Source Name: w314
 - Database: C:\citect\data\mpss.mdb
 - If not, then change using Select button.
9. Client(MICRON4):
- a. Citect Explorer -> File -> Add Project Link
- Add project links to the directory created in Step 2 for each project.
- \\micron3\croot\citect\user\mpss_r0x).
 - \\micron3\croot\citect\user\CBS_r0x).
 - \\micron3\croot\citect\user\TR_r0x).
 - \\micron3\croot\citect\user\WTA_r0x).
10. Client(MICRON4): Change the computer set up in Citect Explorer.
- a. Citect Explorer -> Tools -> Computer Setup
 - b. Citect Computer Setup Wizard
 - Express setup
 - c. Computer Role Setup
 - Display Client
 - d. Project Setup
 - Project Name: mpss_r0x
 - e. Alarms, Reports and Trends Server Setup
 - Primary Server Name: MICRON3
 - Standby Server Name: (blank)
 - f. Network Setup
 - Citect computer name: MICRON4

11. Client(MICRON4): Verify ODBC DSN.
 - a. Control Panel -> ODBC DataSources -> User DSN tab
Select w314
Click Configure button
 - b. Verify that
Database: I:\citect\data\mpss.mdb
If not, then change using Select button.

CURRENT RELEASE DOCUMENTATION

At a minimum, the release documentation shall include the release title, the release date, comments about the release including why the release is being made, and the files contained in the release directory. Refer to the form at the end of this Appendix (E) that shall be filled out for each release.

This documentation shall also be put electronically in the MPSS.CTZ file of the release directory. To retrieve the information, restore the project and access the file within "Citect\User\MPSS\[Release Number]\Files\Release Notes.txt. The following is an example shows typical release notes:

Project W-314, MPSS Release Notes:

Release 0.7 - March 9, 2000

Added SFV Functionality, preliminary fix of communication losses to PLC, added association to CBS, cleared several SCRs since Rev 0.4 of MPSS. Revisions 0.5 and 0.6 fixed SCRs, though no real additions were part of each release.
All released subprojects as Rev 07.

Contained files:

mpss_r07.ctz
cbs_r07.ctz
tr_r07.ctz
wta_r07.ctz

Release 0.4

SCRs still open: 101, 108, 114, & 115
Added floor drains, solid red on objects for acknowledged alarms, compressed libraries, began removing references to QueryArg table in mpss.mdb.
All released subprojects as Rev 04.

Contained files:

mpss_r04.ctz
cbs_r04.ctz
tr_r04.ctz
wta_r04.ctz

Release 0.3

SCRs still open: 89, 101, 108, 113, 114, 115, & 125

Included project tree with Trainer, Create by Segment and Waste Transfer Annunciator subprojects.

All released subprojects as Rev 03.

Contained files:

mpss_r03.ctz
cbs_r03.ctz
tr_r03.ctz
wta_r03.ctz

Release 0.2

Included project tree with Trainer, Create by Segment and Waste Transfer Annunciator subprojects.

All released subprojects as Rev 01.

Contained files:

mpss_r02.ctz
cbs_r02.ctz
tr_r02.ctz
wta_r02.ctz

Release 0.1

Original release of project W-314, Master Pump Shutdown System

Contained files: mpss_r01.ctz

MPSS RELEASE FORM

At a minimum, the release documentation shall include the release title, the release date, comments about the release including why the release is being made, and the files contained in the release directory.

Log ID # :	MPSS Release Form
Testing Evaluation Form Log ID# (attach sheet):	
1.	Release Title:
2.	Release Date:
3.	Release Version (Ensure Back-Up of Previous Release):
4.	Release Comments:
5. Check Categories Included and List Files Contained in Release:	
<input type="checkbox"/> PLC Logic:	
<input type="checkbox"/> HMI:	
<input type="checkbox"/> Database:	
<input type="checkbox"/> Operating System:	
FOR MPSS CCB USE ONLY:	
Release Information	
Closed By CHG CCB:	Date:
Closed By FFS:	Date: