

Keywords: Sludge,
Waste Characterization,
F Tank Farm

**CHARACTERIZATION OF RADIONUCLIDES
IN PUREX WASTE SLUDGES
FROM F-AREA HIGH LEVEL WASTE TANKS (U)**

Retention: Permanent

Revised By

R. F. O'Bryant and J. K. W. Dunaway

Classification: U
Does not Contain UCNI

Paul D. O'Bryant
ADC/RO

Issued: January 2003

APPROVALS

R. F. O'Bryant
R. F. O'Bryant, CBU Engineering, Co-Author

J. K. W. Dunaway
J. K. W. Dunaway, DFM for CBU Engineering, Co-Author

W. R. Weiss
W. R. Weiss, DFM for CBU Engineering, Technical Reviewer

M. C. Chandler
M. C. Chandler, CBU Engineering

Date: 1/30/03

Date: 1/30/03

Date: 1/30/03

Date: 2/04/03

This document was prepared in conjunction with work accomplished under Contract No. DE-AC09-96SR18500 with the U. S. Department of Energy.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

**Available for sale to the public, in paper, from: U.S. Department of Commerce, National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161,
phone: (800) 553-6847,
fax: (703) 605-6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/help/index.asp>**

**Available electronically at <http://www.osti.gov/bridge>
Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from: U.S. Department of Energy, Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831-0062,
phone: (865)576-8401,
fax: (865)576-5728
email: reports@adonis.osti.gov**

TABLE OF CONTENTS

Revision Description.....	iii
1.0 Background.....	1
2.0 Introduction	1
3.0 Development of a Radionuclide Distribution for Sludge Fraction of Sludge-Contaminated Waste	2
3.1 Determining the Initial List of Radionuclides	
3.2 Consolidating Sludge from F-Area Tanks	
3.3 Excluding Radionuclides from Consideration	
3.4 Development of a Distribution	
3.5 Other WAC Criteria	
3.5.1 Comparison to Package Guidelines	
3.5.2 Sum of Fractions Calculation	
3.5.3 Nuclear Criticality Safety Criteria	
3.6 Documentation of the Distribution	
4.0 Supernate Fraction of Sludge-Contaminated Waste	12
4.1 Radionuclide Distribution	
4.2 Other WAC Criteria	
4.3 Documentation of the Supernate Fraction Distribution	
5.0 Quantification	13
5.1 Quantification of Sludge and Supernate Fractions	
5.2 Quantification of Job Control Waste and other Compactable Sludge-Contaminated Waste	
5.3 Quantification of Non-Compactable Sludge-Contaminated Waste	
6.0 Periodic Validation.....	15
7.0 References.....	15

ATTACHMENTS

- Attachment 1 Calculation of Scaling Factors from WCS Concentration Data
- Attachment 2 Comparison of F-Area Tank Farm Scaling Factors for Consolidation
- Attachment 3 F-Area Tank Farm Sludge Waste Streams Exclusion Criteria
- Attachment 4 Waste Characterization Forms for Sludge Fraction, FTK-00002-1 and FTK-00002-19
- Attachment 5 Waste Characterization Form for Supernate Fraction, FHW-00001
- Attachment 6 F-Area Tank Farm Sludge Waste Streams, Sludge and Supernate Fractions Activity Distributions

LIST OF TABLES

- Table 3.1 Radionuclides Important to Characterization of the Sludge Fraction of Sludge-Contaminated Waste
- Table 3.2 F-Area Tank Farm Sludge Tanks Historical Data
- Table 3.3 F-Area HLW Tank Farm Waste Streams
- Table 3.4 Radionuclides Excluded from Consideration, Sludge Fraction
- Table 3.5 Radionuclide Scaling Factors and Distribution for F-Area Tank Farm Sludge
- Table 3.6 Comparison of Sludge Fraction of Sludge-Contaminated Waste to LAWV Limits
- Table 3.7 Comparison of Maximum Amount of Sludge Present to Meet LAWV limits to TRU Criteria
- Table 3.8 Sum-of-Fractions for Sludge Fraction of Sludge-Contaminated Waste
- Table 3.9 Comparison of Maximum Amount of Sludge Present to Meet LAWV Sum-of Fraction Limits to TRU Criteria
- Table 3.10 Calculation of FGE Equivalent for Sludge Fraction of Sludge-Contaminated Waste
- Table 4.1 Validated Radionuclide Distribution and Scaling Factors for HLW Supernate

Revision Description

This revision to this document includes the following substantive changes to the Revision 0 document:

- Revalidate F-Area high level waste streams.
- Revise the consolidation of the waste from F-Area high level waste tanks from three waste streams (FTK-00002-1, -17, and -19) in Revision 0 to two waste streams (FTK-00002-1 and -19) in Revision 1.
- Update the distribution of radionuclides in each waste stream based on current high level waste tank contents and revised SRS Waste Acceptance Criteria (WAC) 2.02 and 3.17 requirements.

1.0 Background

Characterization of High Level Waste Sludge by the Concentration Storage and Transfer (CST) Department is outlined in WSRC-TR-94-0579, *High Level Waste Sludge Characterization in Support of Low Level Waste Certification* (Reference 1). The sludge characterization is based on a series of scaling factors for 31 of 34 known sludge-containing waste tanks. Scaling Factors were previously compiled and compared with available sample data in WSRC-TR-94-0562, *Characterization of Radionuclides in HLW Sludge Based on Isotopic Distribution in Irradiated Assemblies* (Reference 2). Quantification of sludge-contaminated waste and application of the scaling factors has been performed on a case-by-case basis since approval of the methodology by the Waste Characterization Board in 1994.

The Waste Characterization System (WCS) was established in 1996 to consolidate waste characterization information. Inventories and compositions of major sludge constituents are based on tank fill histories. Minor constituent inventories are based on compositions developed during DWPF design. Fill histories for each tank are also contained in the WCS (Reference 3). Subsequent analytical data is incorporated into this database as deemed appropriate. Pu-238 and Am-241 inventories for tanks containing Purex Low Activity Waste (LAW) were adjusted in 1999 (Reference 4).

Further examination of historical tank use data contained in Reference 3, tank contents (i.e. high heat or low heat fractions of either Purex or H-Modified waste) and waste age (both in Reference 2) allowed consolidation of sludge in waste tanks to be considered.

WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, *Low Level, Hazardous, Mixed and PCB Waste Characterization Requirements*, Revision 7 (Reference 5), allows for consolidation of waste streams when the following two criteria are met:

1. Performance Assessment (PA) radionuclide scaling factors do not vary from the proposed data set scaling factor by more than a factor of 10, and
2. The fractional activity of the predominant radionuclides (predominant radionuclides being those that make up 10% or greater of the activity) in each data set does not vary by more than a factor of 2 from the fractional activity of the same radionuclide in the proposed data set.

This document contains the characterization methodology for sludge-contaminated waste generated from the F-Area Tank Farm, based on process knowledge and available analytical data. In addition, this document contains an evaluation for consolidation of sludge-contaminated waste from multiple HLW tanks in the F-Area Tank Farm. The scaling factors developed in this document supercede those presented in References 1 and 2, and any other previously-developed radionuclide characterizations for F-Area Tank Farm sludge-contaminated waste.

2.0 Introduction

Sludge-contaminated waste consists of waste contaminated with both insoluble species (the sludge fraction) and entrained supernate. The WCS is based on the assumption that approximately 70% of the weight of what is commonly referred to as sludge is interstitial supernate; the remaining approximately 30% consists of the insoluble species (Reference 1).

Development of a method for characterization of sludge-contaminated waste must consider both fractions. Separate waste cuts may contain sludge and supernate fractions in varying proportions due to the nature of the job generating the waste and the variability in waste handling techniques. Development of a distribution representative of all sludge-contaminated waste cuts must allow for varying fractions of sludge and supernate contamination.

This document will develop a radionuclide distribution for the sludge fraction of sludge-contaminated waste stored in the F-Area Tank Farm in accordance with the methodology outlined in WSRC 1S SRS Waste

Acceptance Criteria Manual, Procedure 2.02, Revision 7. This distribution was based on the assumption that sludge-contaminated waste from F-Area High Level Waste Tanks could be co-mingled, and the actual contamination present on waste in a series of containers from these tanks will be representative of the mean radionuclide distribution. The original characterization was based primarily on process knowledge and fill histories. A single, comprehensive characterization for supernate has been developed previously (Reference 6).

This document also describes the methodology for application of radionuclide distributions representative of the sludge and supernate fractions of sludge-contaminated waste to individual waste packages.

Most of the waste contaminated with sludge from the F-Area Tank Farm will be categorized as Low Level Waste (LLW) and disposed of in the E-area Vaults (EAV). The waste does, however, have the potential to be categorized as TRU and/or mixed waste. Quantification of hazardous constituents and determination of whether the waste is classified as mixed is dependent on the amount of sludge present on the waste matrix and the nature of the waste matrix, and will be performed on a case-by-case basis. Quantification of radionuclides present in each waste package will be performed as described in Section 5.0.

The radionuclide distribution developed for LLW contaminated with sludge from the F-Area Tank Farm can also be applied to waste classified as transuranic. [Neither WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 3.06, *E-Area TRU Pads Transuranic Waste Acceptance Criteria*, Revision 5, nor Appendix A:34, *TRU Waste Container Characterization Form (OSR 29-90) Instruction* specifies a methodology for determination of the isotopic distribution in TRU Waste; simply that the methodology be documented.]

3.0 Development of a Radionuclide Distribution for Sludge Fraction of Sludge-Contaminated Waste

The development of the radionuclide distribution in this section is performed per guidance outlined in WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, Revision 7 (Reference 5).

3.1 Determining the Initial List of Radionuclides

WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, Revision 7, stipulates that the characterization of each package of waste having a total activity greater than 2 nanocuries/gram must consider the potential presence of any radionuclide that meets any one of three criteria:

1. The radionuclide is identified in WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 3.17, *Low Level Waste Acceptance Criteria*, Revision 7 (Reference 7), as being a Performance Assessment (PA) or Safety Authorization (SA) Basis radionuclide for a specific Treatment, Storage or Disposal (TSD) facility. For purposes of this distribution, we will use those PA and SA radionuclides for the EAV.
2. The radionuclide could be present in the waste with a relative activity greater than 1.0% of the total waste stream activity at the time of the characterization.
3. The radionuclide is a detectable transuranic or a fissile radionuclide.

The above criteria are hereafter referred to as "inclusion criteria."

Based on the three inclusion criteria and available process knowledge, the following list of 36 radionuclides (Table 3.1) will be considered when developing the radionuclide distribution of waste packages contaminated with sludge from the F-Area Tank Farm.

**Table 3.1. Radionuclides Important to Characterization of the Sludge Fraction
of Sludge-Contaminated Waste**

Radionuclide	Inclusion Criteria			
	PA Limiting	SA Limiting	Potentially Present At >1% Total Activity	Detectable Fissile or TRU Radionuclide
H-3		SA		
C-14	PA			
Ni-59			X	
Co-60			X	
Se-79			X	
Sr-90			X	
Y-90			Daughter of Sr-90	
Tc-99	PA			
Ru-106			X	
Rh-106			Daughter of Ru-106	
Sb-125			X	
Sn-126			X	
I-129	PA			
Cs-134			X	
Cs-135			X	
Cs-137			X	
Ba-137m			Daughter of Cs-137	
Ce-144			X	
Pr-144			Daughter of Ce-144	
Pr-144m			Daughter of Ce-144	
Pm-147			X	
Eu-154			X	
U-233				Detectable Fissile
U-234	PA			
U-235				Detectable Fissile
U-238	PA			
Np-237				Detectable TRU
Pu-238				Detectable TRU
Pu-239				Detectable Fissile, TRU
Pu-240				Detectable TRU
Pu-241				Detectable Fissile
Pu-242				Detectable TRU
Am-241				Detectable TRU
Am-242m				Detectable Fissile, TRU
Cm-244			X	
Cm-245				Detectable Fissile, TRU

Scaling factors for radionuclides known to be present in HLW tanks in the F-Area Tank Farms were calculated from decay-corrected concentration data tables in the WCS (Attachments 1, 2, and 3; Reference 8). Consolidated waste stream averages for radionuclide concentration data and resultant scaling factors are conservatively calculated to include only those tanks in the consolidation that contained the particular radionuclide; i.e., zero concentrations were not included in the averages.

3.2 Consolidating Sludge from F-Area Tank Farm

WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, Revision 7, allows for consolidation of waste streams when the following two criteria are met:

1. Performance Assessment radionuclide scaling factors do not vary from the proposed data set scaling factor by more than a factor of 10, and
2. The fractional activity of the predominant radionuclides (predominant radionuclides being those that make up 10% or greater of the activity) in each data set does not vary by more than a factor of 2 from the fractional activity of the same radionuclide in the proposed data set.

Historical data for tanks under consideration for consolidation are summarized in Table 3.2.

Table 3.2. F-Area Tank Farm Sludge Tanks Historical Data					
Tank No.	% Purex HHW	% Purex LHW	Avg. Age, PHHW	Avg. Age, PLHW	Tank Use/Notes
1	61	39	41	39	Waste Removal
2	50	50	46	46	Waste Removal
3	50	50	43	43	Waste Removal
4	97	3	31	31	Waste Removal
5	66	34	39	39	Waste Removal
6	100		33		Waste Removal
7		100		37	Waste Removal
8	22	78	35	25	Waste Removal
18		100		30	Waste Removal
19		100		27	Heel; contains zeolite
26		100		15	Evaporator Feed
33	100		16		F Waste Receipt
34	100		17		Storage
47		100		18	Waste Removal

The tanks contain exclusively Purex Waste with varying proportions of Purex High Heat Waste (PHHW) and Purex Low Heat Waste (PLHW) of varying age (15-47 years), and are all utilized for either waste removal, concentrate receipt, or evaporator feed.

Waste Tanks 17 and 20 were formerly used for waste removal and, accordingly, were included in characterization documentation for F-Area Tank Farm sludge-contaminated waste. Tanks 17 and 20 have subsequently been closed and grouted and will, therefore, no longer be used for management of wastes.

The scaling factors for PA radionuclides for each waste stream were then compared to determine what tanks could be consolidated based on whether they were within an order of magnitude from the mean set of scaling factors for those tanks. This comparison results in the following proposed waste streams for the F-Area Tank Farms:

Table 3.3. F-Area HLW Tank Farm Waste Streams	
HLW Tanks	Waste Stream Number
All active FTF Tanks except 19 (1-8, 18, 26, 33, 34, 47)	FTK-00002-1
19	FTK-00002-19

The grouping of waste tanks per table 3.3 was made based on the following factors:

- All but one F-Area waste tank were grouped together in waste stream FTK-00002-1. The exception to this grouping includes Tank 19. Tank 19 contains spent zeolite resin, which, by virtue of its high concentration of Cs-137, skews the radionuclide distribution for the sludge/zeolite layer. Tank 19 sludge is therefore characterized separately as waste stream FTK-00002-19. Zeolite resin in Tank 19 contains significantly higher Cs-137:Sr-90 ratios than sludge solids.
- Fractional activities were within consolidation criteria set forth in WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, Revision 7. Two exceptions to this exist in waste stream FTK-00002-1, however. C-14 and U-234, PA radionuclides, are present in some tanks in this grouping, while not in others. In addition, some tanks contain up to 3 orders of magnitude less C-14 than the fractional activity in the average stream. The WAC 2.02, Revision 7, indicates that "these [consolidation] factors can be exceeded if it can be shown that the distribution used will be conservative, i.e., the reported activity will be greater than if the factors were within the guidelines." In the case of C-14 and U-234 in this waste stream, the scaling factors will be based upon an average of scaling factors for the tanks containing the radionuclides, and applied to waste generated from all the tanks in this grouping.

Specific issues related to quantification of sludge-contaminated waste generated from these tanks are contained in Section 5. Analysis of combined waste streams FTK-00002-1 and FTK-00002-19 are documented in Attachment 2. The presence of each PA radionuclide, expressed as a fraction of the mean scaling factor for each tank was calculated. In order to meet the first consolidation criteria, the PA radionuclides must be present within an order of magnitude from the mean, or within a range of 0.1 to 10 times the mean scaling factor. All PA radionuclides in combined waste stream FTK-00002-1 meet this criteria with the exception of C-14 in Tanks 1, 2, 3, 4, 5, 7, and 8, and U-238 in Tank 2, which are each below this range. Since WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure 2.02, Revision 7, allows for exception to the consolidation criteria where it can be shown "that the....reported activity will be greater...," as outlined in the first bullet above, the affected tanks can be grouped into this waste stream. By virtue of being made up of waste from only one waste tank, all PA radionuclides in waste stream FTK-00002-19 meet the first consolidation criterion.

The second consolidation criterion applies to predominant radionuclides only. There are two predominant radionuclides in these waste stream distributions, Sr-90 and its daughter Y-90. For waste stream FTK-00002-1, the fractional activities of Sr-90 and Y-90 vary only slightly within the distribution of sludge; the maximum variation from the proposed data set (the mean distribution) is well within a factor of 2, the second criteria for consolidation. Again, by virtue of being made up of waste from only one waste tank, the predominant radionuclides in waste stream FTK-00002-19 meet the second consolidation criterion.

The mean set of scaling factors and comparison of both scaling factors and predominant radionuclides is presented in Attachment 4. Based on the results of this comparison, both consolidation criteria are met for these two combined waste streams, and the sludge fraction of sludge-contaminated waste from tanks in Table 3.3 may be consolidated into two waste streams, FTK-00002-1 and -19; the mean values will include all tanks that contain the specific radionuclide.

3.3 Excluding Radionuclides from Consideration

Under WAC 2.02, Revision 7, radionuclides that meet one of the inclusion criteria outlined in section 3.1 may be excluded from further consideration for a waste stream if one or more of the following conditions exist:

1. There is no reason to expect the radionuclide to be present in the waste stream.
2. For non-SA or -PA radionuclides, or non-detectable fissile or TRU radionuclides, the individual activity contribution is less than 1% of the total radionuclide activity.

The above criteria are hereafter referred to as "exclusion criteria;" exclusion results are presented in Table 3.4.

(Note: WSRC 1S SRS Waste Acceptance Criteria Manual, Procedure WAC 2.02, Revision 7, also allows for exclusion from the waste stream distribution of radionuclides whose activities are below specific analytical laboratory Maximum Allowable Lower Limits of Detection [MALLDs]. This exclusion criterion will not be used for this process-knowledge-based characterization of sludge waste streams FTK-00002-1 and -19).

Of the 36 radionuclides listed in Table 3.1, one SA radionuclide (H-3) is excluded because it is not expected to be present in either waste stream; also, one PA radionuclide (U-234), one fissile radionuclide (U-233), one TRU radionuclide (Np-237), and one fissile/TRU radionuclide (Am-242m) are excluded from FTK-00002-19 because they are not expected to be present (Table 3.4). Of the radionuclides included because they were expected to be present at more than 1% of total activity, an additional 14 are determined to be present at less than 1% of the total activity in both waste streams. Three additional radionuclides (Sr-90, Y-90, and Pm-147) are present at <1% in waste stream FTK-00002-19. Four of these radionuclides, however, are retained in one or the other of the distributions (Co-60, Sb-125, and Eu-154 in FTK-00002-1 and Sr-90 and Y-90 in FTK-00002-19) since they are near 1% of total activity. Calculations supporting this determination are summarized in Attachment 5.

Table 3.4. Radionuclides Excluded from Consideration, Sludge Fraction				
Radionuclide	Exclusion Criteria			
	Not Expected		Present at <1% (a)	
	FTK-00002-		FTK-00002-	
	1	19	1	19
H-3	X	X		
C-14				
Ni-59			X	X
Co-60			X(b)	X
Se-79			X	X
Sr-90				X(b)
Y-90				X(b)
Tc-99				
Ru-106			X	X
Rh-106			X	X
Sb-125			X(b)	X
Sn-126			X	X
I-129				
Cs-134			X	X
Cs-135			X	X
Cs-137				
Ba-137m				
Ce-144			X	X
Pr-144			X	X
Pr-144m			X	X
Pm-147				X
Eu-154			X(b)	X
U-233		X		
U-234		X		
U-235				
U-238				
Np-237		X		
Pu-238				
Pu-239				
Pu-240				
Pu-241				
Pu-242				
Am-241				
Am-242m		X		
Cm-244			X	X
Cm-245				

(a) For those radionuclides included only because they were expected to be present at >1%

(b) Retained in distribution since they are close to 1% total activity

NOTE: Bold = PA/SA radionuclides

3.4 Development of the Sludge Fraction Distribution

Thirty-six radionuclides were determined to be important to characterization of the sludge in F-Tank Farm. A number of these have been excluded per discussion in Section 3.3, leaving 24 and 16 radionuclides to be quantified for waste streams FTK-00002-1 and -19, respectively. Current tank contents were used to update the scaling factors to create an isotopic distribution for the two consolidated waste streams.

The radionuclides, their concentrations per gallon of sludge, corresponding mean scaling factors (to Sr-90), and mean activity distribution in the waste streams are summarized in Table 3.5.

Table 3.5. Radionuclide Scaling Factors and Distribution for F-Area Tank Farm Sludge

Radio-nuclide	Mean Activity (Ci/gal)		Mean Scaling Factors (Ci/Ci Sr-90)		Mean Distribution, Normalized (%)	
	FTK-00002-		FTK-00002-		FTK-00002-	
	1	19	1	19	1	19
C-14	1.54E-06	2.74E-07	1.10E-06	3.98E-06	4.88E-05	1.03E-06
Co-60	2.46E-01	1.29E-04	2.50E-03		1.11E-01	
Sr-90	6.84E+01	6.88E-02	1.00E+00	1.00E+00	4.44E+01	2.59E-01
Y-90	6.84E+01	6.88E-02	1.00E+00	1.00E+00	4.44E+01	2.59E-01
Tc-99	2.32E-02	2.31E-05	3.81E-04	3.36E-04	1.69E-02	8.71E-05
Sb-125	3.17E-01	4.27E-05	2.88E-03		1.28E-01	
I-129	1.11E-07	1.10E-10	1.82E-09	1.59E-09	8.06E-08	4.13E-10
Cs-137	4.73E+00	1.35E+01	6.97E-02	1.97E+02	3.09E+00	5.10E+01
Ba-137m	4.48E+00	1.28E+01	6.59E-02	1.86E+02	2.93E+00	4.83E+01
Pm-147	5.71E+00	6.81E-04	5.17E-02		2.30E+00	
Eu-154	3.36E-01	2.72E-04	3.91E-03		1.73E-01	
U-233	9.60E-12		6.91E-14		3.07E-12	
U-234	8.01E-08		5.76E-10		2.56E-08	
U-235	1.69E-06	2.67E-08	7.94E-08	3.88E-07	3.53E-06	1.01E-07
U-238	1.04E-04	2.44E-06	4.68E-06	3.55E-05	2.08E-04	9.20E-06
Np-237	9.98E-05		1.76E-06		7.82E-05	
Pu-238	5.36E-02	1.00E-02	2.95E-02	1.46E-01	1.31E+00	3.78E-02
Pu-239	2.62E-02	1.43E-03	3.71E-03	2.08E-02	1.65E-01	5.40E-03
Pu-240	5.44E-03	3.20E-04	8.67E-04	4.65E-03	3.85E-02	1.21E-03
Pu-241	1.21E-01	4.15E-02	1.80E-02	6.03E-01	7.98E-01	1.57E-01
Pu-242	1.56E-06	6.58E-07	5.23E-07	9.56E-06	2.32E-05	2.48E-06
Am-241	2.34E-01	4.02E-03	4.23E-03	5.83E-02	1.88E-01	1.51E-02
Am-242m	3.01E-04		3.91E-06		1.74E-04	
Cm-245	3.81E-11	3.82E-14	6.27E-13	5.55E-13	2.78E-11	1.44E-13
Total	1.53E+02	2.65E+01	2.25E+00	3.85E+02	1.00E+02	1.00E+02
Total TRU	3.20E-01	1.58E-02				

3.5 Other WAC Criteria

3.5.1 Comparison to Package Guidelines

Most sludge-contaminated waste will be disposed of in the E-Area Vaults (EAV). Administrative Waste Package Radiological Concentration Guidelines apply to waste disposed of in the EAV. The guidelines applicable to the Low Activity Waste Vault (LAWV), that portion of the EAV reserved for low activity waste, will be used for comparison since they are the most restrictive of the EAV facilities. Low activity waste is defined as waste that will produce less than or equal to 200 mR/hr at 5 cm from an unshielded final disposal container. The average concentration of each PA radionuclide in the F-Area Tank Farm Sludge Waste Streams (Attachment 3) and their corresponding LAWV limits (Reference 5) are summarized in Table 3.6. Calculations supporting this comparison are in Attachment 6. LAWV limits are expressed in Ci/ft³ waste and Ci/90 ft³ B-25 container.

Table 3.6. Comparison of Sludge Fraction of Sludge-Contaminated Waste to LAWV Limits

Radio-nuclide	Sludge (Ci/gal)		LAWV Limit		Gallons of sludge in B-25 to reach LAWV limit	
	Stream FTK-00002-01	Stream FTK-00002-19	Ci/ft ³	Ci/B-25	Stream FTK-00002-01	Stream FTK-00002-19
	A ₁	A ₂	B	C=B*90ft ³	D ₁ =C/A ₁	D ₂ =C/A ₂
C-14	1.54E-06	2.74E-07	2.50E-05	2.25E-03	1.46E+03	8.21E+03
Tc-99	2.32E-02	2.31E-05	5.60E-05	5.04E-03	2.17E-01	2.18E+02
I-129	1.11E-07	1.10E-10	1.10E-08	9.90E-07	8.92E+00	9.00E+03
U-234	8.01E-08		1.10E-03	9.90E-02	1.24E+06	
U-238	1.04E-04	2.44E-06	1.20E-03	1.08E-01	1.04E+03	4.43E+04

From the container limits, the maximum volume of sludge that could be present in a B-25 container while still meeting the LAWV limits can be calculated. The most limiting isotope in waste stream FTK-00002-1 is Tc-99, for which more than 0.2 gallons of sludge in a B-25 would cause the waste to exceed the LAWV limit. The most limiting isotope in waste stream FTK-00002-19 is also Tc-99, for which more than 218 gallons of sludge in a B-25 would cause the waste to exceed the LAWV limit. Sludge in the F-Area Tank Farm contains exclusively Purex sludge with an average total radionuclide and total TRU activity, respectively, for waste stream FTK-00002-1 of 153 and 0.3 Ci/gallon and for FTK-00002-19 of 26.5 and 0.02 Ci/gal (Table 3.7; Attachment 6). Accordingly, 0.2 gallons of FTK-00002-1 sludge to meet the LAWV for Tc-99 would be equivalent to 33 total Ci in a B-25, 0.07 Ci of which are transuranics; similarly, 218 gallons of FTK-00002-19 sludge would be equivalent to 33,400 total Ci in a B-25, 70 Ci of which are transuranics. Per Table 3.7, for waste stream FTK-00002-1, a box with less than 1,531 lb. of waste and 0.2 gallons or more of sludge will fail TRU limits. For waste stream FTK-00002-19, the limiting amount of sludge would be equivalent to an amount that would exceed the TRU limit and would not be disposed of in the LAWV. In practice, very few waste boxes fail TRU limits. Any such box will, upon entry into WITS, be flagged as TRU and not be sent to the LAWV.

Table 3.7. Comparison of Maximum Amount of Sludge Present to Meet LAWV limits to TRU Criteria

	Max gals sludge / B-25 to meet LAWV criteria	Average total Ci / gallon sludge	Average total Ci / B-25 at LAWV limit	Average total TRU Ci / gallon sludge	Average total TRU Ci / B-25 at LAWV limit
FTK-00002-	A	B	C=A*B	D	E=(D/B)*C
1	2.17E-01	1.53E+02	3.32E+01	3.20E-01	6.95E-02
19	2.18E+02	2.65E+01	3.34E+04	1.58E-02	6.98E+01

	TRU nCi/g at maximum waste weight (5000 lb) in a B-25 at LAWV limit	Minimum waste weight in a B-25 at LAWV limit to not be TRU waste (lb)
FTK-00002-	=(E*1E+09nCi/Ci) / (5000 lb*454 g/lb)	=(E*1E+09nCi/Ci) / (454 g/lb*100 nCi/g)
1	3.06E+01	1.53E+03
19	3.08E+04	1.54E+06

3.5.2 Sum of Fractions Calculation.

For acceptance of waste packages sent to the LAWW, the radiological content of the waste package must be compared to the administrative guidelines and shown to satisfy the sum-of-fractions criteria where:

$$\begin{aligned} & \text{activity concentration of isotope A/limit of isotope A} \\ & + \text{activity concentration of isotope B/limit of isotope B} \\ & + \text{activity concentration of isotope N/limit of isotope N} \\ & \leq 1 \end{aligned}$$

Table 3.8 calculates the maximum concentration of sludge on sludge-contaminated waste in order for the sum-of-the-fractions criteria to be met. Calculations supporting this comparison are in Attachment 6.

Table 3.8. Sum-of-Fractions for Sludge Fraction of Sludge-Contaminated Waste

Radio-nuclide	Ci/gal sludge		Ci/ft ³ sludge		ft ³ sludge / ft ³ waste		Ci/ft ³ waste		LAWV Limit (Ci/ft ³)	Fraction			
	A		B=A*7.48		C		D=B*C			E	=D/E		
	FTK-00002-1	FTK-00002-19	FTK-00002-1	FTK-00002-19	FTK-00002-1	FTK-00002-19	FTK-00002-1	FTK-00002-19		FTK-00002-1	FTK-00002-19		
H-3									1.10E+01				
C-14	1.54E-06	2.74E-07	1.15E-05	2.05E-06	3.15E-04	3.07E-01	3.63E-09	6.29E-07	2.50E-05	1.45E-04	2.52E-02		
Tc-99	2.32E-02	2.31E-05	1.74E-01	1.73E-04	3.15E-04	3.07E-01	5.46E-05	5.30E-05	5.60E-05	9.75E-01	9.47E-01		
I-129	1.11E-07	1.10E-10	8.30E-07	8.23E-10	3.15E-04	3.07E-01	2.61E-10	2.52E-10	1.10E-08	2.38E-02	2.30E-02		
U-234	8.01E-08		5.99E-07		3.15E-04	3.07E-01	1.89E-10		1.10E-03	1.71E-07			
U-238	1.04E-04	2.44E-06	7.78E-04	1.83E-05	3.15E-04	3.07E-01	2.45E-07	5.60E-06	1.20E-03	2.04E-04	4.67E-03		
									Sum-of-Fractions		9.99E-01		

Tc-99 dominates the sum-of-the-fractions criteria for both waste streams FTK-00002-1 and -19. Primarily based on this dominance, the criteria are met for waste streams FTK-00002-1 and FTK-00002-19, respectively, for a maximum of 3.15E-04 ft³ and 3.07E-01 ft³ of sludge for each 1ft³ of waste, which equate to 0.2 gallon of sludge (2.83E-02 ft³) for FTK-00002-1 and 207 gallon of sludge (2.76E+01 ft³) for FTK-00002-19 per each 90 ft³ volume B-25 container (Attachment 6 and Table 3.9). This is equivalent to 3.24E+01 total Ci and 6.78E-02 Ci of transuranic isotopes of sludge in a B-25 for waste stream FTK-00002-1 and 5.47E+03 total Ci of sludge and 3.26E+00 Ci of transuramics of sludge in a B-25 for FTK-00002-19 (Table 3.9).

For waste stream FTK-00002-1, any B-25 waste container containing 6.78E-02 Ci (or 6.78E+07 nCi) of transuramics must contain 6.78E+05 g (or 1,493 lbs) or more of waste (compared to the 5000 lb maximum waste weight per B-25 container) in order to be within the TRU limit of 100 nCi/g total transuramics (Table 3.9; Attachment 6). For waste stream FTK-00002-19, the limiting amount of sludge would be equivalent to an amount that would exceed the TRU limit and would not be disposed of in the LAWW. In practice, very few waste boxes fail TRU limits. Any such box will, upon entry into WITS, be flagged as TRU and not be sent to the LAWW.

Table 3.9. Comparison of Maximum Amount of Sludge Present to Meet LAWW Sum-of-Fractions Limits to TRU Criteria

Waste Stream FTK-	Maximum ft ³ sludge per ft ³ waste to meet sum-of-fractions criteria	Maximum gallons of sludge in a single B-25 to meet sum of fractions criteria	Average total TRU Ci / gallon sludge	Maximum total TRU Ci of a single B-25 to meet sum-of-fractions criteria	Minimum lb waste weight of a single B-25 to meet TRU limit of 100 nCi/g	TRU nCi/g in B-25 to meet sum-of-fractions criteria at 5000 lb maximum waste weight of a B-25
	A	B=A*90ft ³ /B-25*7.48 gal/ft ³	C	D=B*C	= (D*1E+09 nCi/Ci) / (100 nCi/g *454 g/lb)	= (D*1E+09 nCi/Ci) / (5000lb*454 g/lb)
0002-1	3.15E-04	2.12E-01	3.20E-01	6.78E-02	1.49E+03	2.99E+01
0002-19	3.07E-01	2.07E+02	1.58E-02	3.26E+00	7.18E+04	1.44E+03

3.5.3 Nuclear Criticality Safety Criteria

Sludge-contaminated LLW from F-Area Tank Farm Waste Streams contains an insignificant quantity of fissionable material to impact nuclear criticality criteria. Calculations supporting this comparison are in Attachment 6. Table 3.10 shows the maximum quantity of sludge that could be placed in a B-25 prior to exceeding the 50 g FGE U-235. This is equivalent to 33.9 and 978 gallons of sludge in a B-25 for waste streams FTK-00002-1 and -19, respectively, significantly exceeding TRU criteria for a waste box. Any such box will not be sent to the LAWW for disposal, therefore protecting this requirement.

Table 3.10. Calculation of FGE Equivalent for Sludge Fraction of Sludge-Contaminated Waste

Radio-nuclide	Activity in blended sludgee (Ci/gal)	Maximum gallons of sludge in a B-25 to meet FGE equivalent	Maximum Curies sludge in a B-25	Specific activity (Ci/g)	Maximum mass (grams) in a B-25	Equivalence factor	FGE U-235 (g)
	A	B	C=A*B	D	E=C/D	F	G=E*F
Waste Stream FTK-00001							
U-233	9.60E-12	33.9	3.25E-10	9.648E-03	3.37E-08	1.4	4.72E-08
U-235	1.69E-06	33.9	5.73E-05	2.16E-06	2.65E+01	1.0	2.65E+01
Pu-239	2.62E-02	33.9	8.88E-01	6.132E-02	1.45E+01	1.6	2.32E+01
Pu-241	1.21E-01	33.9	4.10E+00	1.034E+02	3.97E-02	3.5	1.39E-01
Am-242m	3.01E-04	33.9	1.02E-02	9.717E+00	1.05E-03	54.0	5.67E-02
Cm-245	3.81E-11	33.9	1.29E-09	1.716E-01	7.53E-09	24.0	1.81E-07
Waste Stream FTK-000019							
U-235	2.67E-08	978	2.61E-05	2.16E-06	1.21E+01	1.0	1.21E+01
Pu-239	1.43E-03	978	1.40E+00	6.20E-02	2.28E+01	1.6	3.65E+01
Pu-241	4.15E-02	978	4.06E+01	1.034E+02	3.92E-01	3.5	1.37E+00
Cm-245	3.82E-14	978	3.74E-11	1.716E-01	2.18E-10	24.0	5.22E-09

3.6 Documentation of the Sludge Fraction Distribution

Low level waste stream forms for F-Area Tank Farm Waste Streams, FTK-00002-1 and FTK-00002-19, included as Attachment 7, document the distribution from F-Area Tank Farms Waste Streams. For those packages determined to contain sufficient sludge to be determined mixed and/or transuranic, appropriate waste stream forms will be provided for each package.

4.0 Supernate Fraction of Sludge-Contaminated Waste

4.1 Radionuclide Distribution

The radionuclide distribution for the supernate fraction of sludge-contaminated waste has been previously determined and documented. "HLW Supernate Radionuclide Characterization," WSRC-TR-94-0290, Revision 3, April 19, 1999 (Reference 9), identifies 14 radionuclides present in supernate waste. This waste stream represents a single, comprehensive and conservative characterization/certification for all supernate in both F- and H-Areas. The waste stream consists primarily of Cs-137 and its daughter Ba-137m, which together comprise 97% of the total activity in supernate. The fourteen isotopes determined to be present in supernate waste, their relative activity and scaling factors (to Cs-137) for this waste stream are reproduced in Table 4.1.

Table 4.1. Validated Radionuclide Distribution and Scaling Factors for HLW Supernate

Radionuclide	Normalized Distribution (%)	Scaling Factors (Ci/Ci Cs-137)
H-3	2.01E-01	4.00E-03
Co-60	1.71E+00	3.40E-02
Sr-90	4.73E-02	9.30E-04
Tc-99	9.15E-03	1.80E-04
I-129	1.11E-05	2.10E-07
Cs-137	5.03E+01	1.00E+00
Ba-137m	4.73E+01	9.40E-01
U-233	2.62E-04	5.20E-06
U-234	7.14E-05	1.40E-06
Pu-238	2.51E-01	5.00E-03
Pu-239	2.92E-03	5.90E-05
Pu-240	1.31E-03	2.60E-05
Pu-241	1.91E-01	3.80E-03
Am-241	1.81E-02	3.50E-04
Total	1.00E+02	

4.2 Other WAC Criteria

Comparison of supernate waste to other WAC requirements has been performed previously (Reference 9). The following determinations were made for supernate waste:

- A B-25 container 90% full (81 ft^3 waste) can contain up to 0.36 gallons of supernate (1.8 Ci Cs-137), approximately 50-200 times the estimate of supernate expected in a typical B-25 before it is expected to exceed the LAWV Administrative Waste Package Radiological Concentration Guidelines
- Supernate waste passes the sum of fractions calculation

- Supernate waste contains an insignificant quantity of fissionable material to impact nuclear criticality criteria

4.3 Documentation of Supernate Fraction Distribution

Low Level waste stream form FHW-00001, previously submitted for approval to the Solid Waste Division, and included in Attachment 8 for information, will be used to document the supernate fraction distribution of sludge waste.

5.0 Quantification

5.1 Quantification of Sludge and Supernate Fractions

Quantification of radionuclides in sludge-contaminated waste requires quantification of both the supernate and sludge fractions in each waste cut. Independent quantification of Sr-90, indicative of the sludge fraction, and Cs-137, indicative of the supernate fraction, is key to accurate characterization of sludge-contaminated waste. Both the sludge and supernate fractions and their scaling ratios to Sr-90 and Cs-137, respectively, are reproduced in Attachment 9.

Scaling factors for the sludge fraction are tied to Sr-90. Although Sr-90 is present in the supernate fraction, it comprises less than 1% of total activity in the supernate fraction. For this reason, all Sr-90 identified in the sludge-contaminated waste will be attributed to the sludge fraction. Scaling ratios developed for the sludge fraction will be applied to the Sr-90 identified in sludge-contaminated waste.

Scaling factors for the supernate fraction are tied to Cs-137. Although Cs-137 is present in the sludge fraction, it typically comprises less than 5% of total activity in the sludge fraction (as is the case for waste stream FTK-00002-1). Waste stream FTK-00002-19 is a distinctly separate case, in that 99% of the activity in the sludge fraction is from Cs-137 and its daughter Ba-137m. Similarly, 98% of the activity in the supernate is from Cs-137 and its daughter Ba-137m. Application of the radionuclide distributions of waste streams FTK-00002-1 and -19 to quantification of waste from individual waste tanks will be performed on a case-by-case basis, based on available activity data and process knowledge.

The two fractions of sludge-contaminated waste will be manifested separately. The dose of Cs-137 and Sr-90 will be entered into two separate waste streams in WITS, representing the sludge and supernate fractions, respectively, which will calculate curies attributed to each radionuclide identified in the respective distributions. The two waste streams will be combined in WITS to create a single manifest.

5.2 Quantification of Job Control Waste and other Compactable Sludge-Contaminated Waste

The relative ease with which gamma radiation from Cs-137 is detected makes estimation of the curie content of the supernate fraction of waste straightforward. Dose-to-curie methodologies for quantification of Cs-137 on waste containers have been developed and are currently in use (References 9 and 10).

Sr-90, a low-energy beta emitter, is not easily measured. Although a Beta Screening Tool (BST) has been developed as an improved alternative method for providing a dose associated with Sr-90 (Reference 11), the BST methodology has not yet been implemented for waste quantification purposes. Until such time as the BST is field implemented, the actual quantity of Sr-90 present in the sludge fraction must be estimated by some other means.

The most conservative approach in quantification of a waste cut is to assume that all measured Cs-137 is attributed to both supernate and sludge fractions. For the sludge fraction, the known Sr-90 to Cs-137 ratio is utilized to estimate the maximum Sr-90 that could be present on the waste cut. This approach results in double-manifesting of the Cs-137, over-manifesting of virtually all of the remaining radionuclides, and significantly over-estimating the sludge fraction.

It is preferable, therefore, to determine an appropriate split of the measured Cs-137 that can be attributed to the supernate and sludge fractions. In determining the appropriate split between these fractions, one must consider the effects of overestimating one fraction or the other. Over-estimating the sludge fraction will result in

- under-manifesting of radionuclides attributed to supernate only (in this waste stream, the only radionuclide fitting this description is tritium, a PA radionuclide, present at 0.2% of total supernate activity), and
- over-manifesting of transuranics (a higher level of transuranics are present in sludge).

Over-estimating the supernate fraction will result in under-manifesting of radionuclides present in the sludge fraction only.

Determination of the split of Cs-137 contributed from the sludge and supernate fractions will be performed on a case-by-case basis for F-Area high level waste packages.

5.3 Quantification of Non-Compactable Sludge-Contaminated Waste

Estimation of the quantity of Cs-137 present on non-compactable waste, such as equipment or HEPA filters, is performed on a case-by-case basis. This is done by individual Dose-to-Curie runs, which take into account the specific geometry of the waste (Reference 12). Solid Waste Management Department personnel perform these runs.

Application of BST methodology to non-compactable waste to determine the amount of Sr-90 present is not appropriate since the waste itself shields beta radiation and would result in unrealistically low measured values. Estimation of Sr-90 present in cuts of non-compactable waste will be performed by estimation of the amount of Cs-137 attributed to the sludge fraction in combination with the known relationship between Sr-90 and Cs-137. This will be performed on a case-by-case basis.

6.0 Periodic Validation

Provisions of Procedure WAC 2.02, Revision 7 (Reference 5), require generators of routine wastes, including sludge-contaminated waste, to review and confirm the certification of each waste stream at least every two years. Since samples of supernate are routinely pulled and analyzed, validation of the supernate fraction is performed on this frequency.

Sludge sampling has been conducted on a very limited basis during development of DWPF design bases. Additional sludge samples have not been collected to date due to high cost and personnel exposure. For this reason, future validation performed of the sludge fraction will utilize process knowledge and analytical data as available.

7.0 References

- 1 D'Entremont, P. D. "HLW Sludge Characterization in Support of Low Level Waste Certification (U)," WSRC-TR-94-0579, Revision 1., December 15, 1994.
- 2 Georgeton, G. K. and J. R. Hester. "Characterization of Radionuclides in HLW Sludge Based on Isotopic Distribution in Irradiated Assemblies (U)," WSRC-TR-94-0562, Revision 1., January 27, 1995.
- 3 Hester, J. R., "High Level Waste Characterization System (WCS)," WSRC-TR-96-0264, Revision 0, December 1996.

- 4 Hester, J. R., "Correction of Am-241 Inventories and Adjustment of PUREX Low Heat Waste Pu-238 Inventories in the Waste Characterization System (WCS)," HLW-STE-99-0207, June 3, 1999.
- 5 Procedure WAC 2.02, Low Level Waste Characterization Requirements, WSRC 1S Savannah River Site Waste Acceptance Criteria Manual, Revision 7, Savannah River Site, November 1, 2002.
- 6 O'Bryant, R. F. and J. K. W. Dunaway, "Characterization of Radionuclides in Purex Waste Sludges from F-Area High Level Waste Tanks (U), WSRC-TR-2000-00215, June 2000.
- 7 Procedure WAC 3.17, Low Level Waste Acceptance Criteria, WSRC 1S Savannah River Site Waste Acceptance Manual, Revision 7, Savannah River Site, September 16, 2002.
- 8 M:\Waste\Hlcats\WCTables\TankData.xls, September 11, 2002.
M:\Waste\Hlcats\WCTables\SldgInv.xls, September 11, 2002.
- 9 Ketusky, E. T. and R. F. O'Bryant, "HLW Supernate Radionuclide Characterization," WSRC-TR-94-0290, Revision 3, April 19, 1999.
- 10 M. E. Jamison, "Characterization of Non-Routine Low-Level Waste from High Level Waste Activities (U)," WSRC-TR-95-0069, March 13, 1995.
- 11 P. D. Hunt, "Dose-to-Curie Calculations," ESH-HPT-99-0019, Revision 1, March 2, 1999.
- 12 Ross, R. H., Ketusky, E. T., and Petras, R. "HLW Characterization in Support of Low Level Waste Certification: HLW Sludge Beta Screening Tool," WSRC-TR-97-0555, Revision 1, October 8, 1998.
- 13 SRS-DTCTM 3.1, WMG Inc., 16 Bank Street, Peekskill, NY 10556.

Attachment 1

**WCS Tank Data
Reference Date: September 11, 2002**

Overall Project Summary	
Project ID	PJ-2023-Q1-A
Client Name	Global Solutions Inc.
Project Lead	Jane Doe
Start Date	2023-01-01
End Date	2023-06-30
Budget (USD)	1,200,000
Actual Spend (USD)	1,150,000
Remaining Budget (USD)	50,000
Scope Status	On Track
Risk Level	Low
Last Update	2023-03-15
Next Review	2023-04-15
Primary Contact	John Smith
Secondary Contact	Sarah Johnson
Emergency Contact	David Lee
Project Type	Industrial
Location	New York City, USA
Team Size	10
Team Composition	5 Engineers, 3 Technicians, 2 Support Staff
Key Milestones	System Design Completion (2023-02-15), Prototype Testing (2023-03-15), Final Assembly (2023-04-15), User Acceptance Testing (2023-05-15), Project Closeout (2023-06-15)
Resource Allocation	Hardware: 45%, Software: 30%, Personnel: 25%
Performance Metrics	Completion Rate: 95%, Defect Density: 0.5%, User Satisfaction: 4.8/5.0
Communication Plan	Daily stand-ups (M-F), Weekly status reports, Bi-monthly progress meetings, Emergency notifications via mobile app
Contingency Plan	Resource augmentation, Vendor substitution, Alternative supplier identification, Risk mitigation workshops
Final Status	On Track, Meets Scope, Within Budget, High Quality

Attachment 2

**WCS Sludge Inventory
Reference Date: September 11, 2002**

Attachment 2
WCS Sludge Inventory
Reformatted Date: 0/11/02

Release Date: 3/1/2024

cats\WCSsystem\WCSys

Bank	H-3 [C]	C-14 [C]	Sr-87 [C]	Se-75 [C]	Nb-94 [C]	Rb-106 [C]	Tl-132 [C]	Bi-173m [C]	P-144 [C]
1	1.2862E+02	2.3377E+01	2.961E+02	1.6283E+01	6.0396E+05	3.0349E+05	3.7914E+01	1.8517E+08	4.0318E+04
2	2.8622E+03	3.3717E+00	1.9227E+01	2.3074E+02	5.7598E+04	2.0191E+00	3.9817E+00	5.2625E+01	5.4625E+08
3	2.4795E+03	2.9189E+00	2.1873E+01	1.9877E+00	6.8749E+04	1.4244E+07	1.0376E+00	3.7156E+00	4.5149E+12
4	3.3530E+03	1.8405E+02	3.8557E+03	7.0575E+03	8.4768E+01	1.4857E+05	1.3919E+03	1.6102E+03	7.4889E+11
5	4.4477E+02	1.0101E+02	1.9755E+03	1.2226E+03	1.3739E+06	2.8420E+06	6.0577E+01	1.7873E+05	4.5606E+02
6	7.6183E+02	1.8723E+02	1.5935E+03	1.2893E+03	3.2898E+06	3.2898E+06	1.2630E+01	5.8778E+02	4.4636E+08
7	1.4588E+02	3.6226E+00	2.1066E+01	1.5057E+00	2.4888E+00	1.2106E+05	1.1715E+04	2.1977E+02	2.4458E+07
9	3.0874E+03	3.6388E+00	2.0573E+01	8.1715E+04	4.3054E+01	1.9588E+07	6.9819E+03	2.1977E+04	1.6094E+04
10	3.2383E+04	3.8810E+01	2.4575E+00	8.7264E+03	4.4894E+00	3.0806E+09	8.8168E+09	2.1204E+05	4.7466E+12
11	1.5858E+01	1.6377E+02	1.3262E+04	9.0493E+01	5.4228E+06	5.4228E+06	1.5533E+03	1.4767E+01	2.9773E+05
12	5.2340E+01	2.8025E+02	1.3207E+04	1.5782E+02	3.8655E+06	3.8655E+06	5.2301E+03	1.7226E+01	2.1852E+02
13	2.9212E+01	2.8077E+02	7.4822E+03	1.7171E+02	6.7860E+06	2.9847E+03	3.1705E+03	1.7179E+02	4.3849E+05
14	1.5057E+03	7.7175E+00	8.3051E+01	5.2884E+00	1.9612E+05	9.0606E+01	4.3236E+07	8.8803E+00	1.3888E+09
15	2.3383E+01	2.6013E+02	1.0127E+04	1.4383E+02	7.5049E+06	2.4374E+03	1.0111E+02	1.2203E+05	3.9278E+05
16	3.4177E+03	2.0161E+01	1.1679E+00	1.6363E+02	7.8504E+02	1.9507E+01	9.0081E+03	9.0081E+03	7.2038E+07
18	4.0698E+02	2.3587E+00	1.2562E+01	3.8484E+03	4.0928E+02	3.2817E+01	4.0928E+02	3.2817E+01	6.1966E+06
19	6.5567E+04	4.0928E+02	3.2817E+01	3.8484E+03	5.8725E+02	5.8531E+02	5.8531E+06	5.8531E+06	1.0240E+07
20	8.5571E+05	1.0360E+00	1.8948E+02	1.6554E+00	1.1354E+05	1.3129E+01	2.1256E+02	1.2256E+02	1.0240E+07
21	2.1332E+00	3.6368E+02	5.6851E+01	5.3129E+04	7.8169E+01	5.3129E+04	2.8006E+01	1.4770E+02	4.3047E+01
22	2.1332E+00	3.6368E+02	5.6851E+01	5.3129E+04	7.8169E+01	5.3129E+04	2.8006E+01	1.4770E+02	4.3047E+01
23	5.2644E+01	2.1332E+00	3.6368E+02	5.6851E+01	5.3129E+04	7.8169E+01	5.3129E+04	2.8006E+01	1.4770E+02
24	5.8770E+01	3.4531E+01	1.3717E+03	2.8553E+00	1.9675E+05	4.9543E+01	7.8283E+01	2.2221E+03	5.3062E+00
25						4.9543E+01	7.8283E+01	2.2221E+03	5.3062E+00
26						2.3509E+00	2.3509E+04	1.8591E+01	3.3076E+02
27						1.3422E+02	1.3422E+04	1.2637E+04	2.3872E+01
28						2.3872E+01			
29									
30	7.8049E+04	8.55587E+01	4.5207E+02	4.7092E+01	4.0631E+04	4.0631E+04	7.9796E+00	1.1542E+00	1.1542E+00
31									
32	2.4530E+01	2.7068E+02	4.9770E+04	1.4324E+02	1.0203E+07	1.0203E+07	2.5231E+03	7.3041E+01	7.3041E+01
33									
34	1.1108E+01	3.4983E+04	1.7147E+02	2.9081E+02	5.4188E+06	5.4188E+06	1.3757E+03	1.0730E+03	5.0184E+04
35									
36	2.0689E+01	2.2702E+02	5.8851E+04	1.2491E+02	3.1719E+05	3.1719E+05	2.1167E+03	1.1430E+03	1.2431E+02
37									
38	1.8066E+01	1.9815E+02	8.4562E+04	1.0803E+02	9.0081E+06	9.0081E+06	7.9001E+01	3.6680E+06	3.6680E+06
40	6.1413E+01	1.4524E+02	5.0513E+03	7.9001E+01	3.6680E+06	3.6680E+06	1.7146E+01	1.7235E+01	1.7235E+01
41									
42	2.5749E+02	1.1463E+01	4.8288E+02	5.9729E+01	3.1719E+05	3.1719E+05	1.0214E+02	6.3266E+03	6.3266E+03
43									
44									
45									
46									
47	4.3667E+01	2.5662E+01	7.7288E+02	2.1223E+00	1.3968E+05	1.3968E+05	3.6819E+01	7.0961E+00	9.0739E+02
48									
49									
50									
51									
Total	3.2273E+01	4.7769E+00	4.1821E+01	2.3715E+00	6.1939E+00	2.8567E+05	2.4761E+00	7.9618E+02	3.2597E+03
	4.5473E+02	2.3575E+03	3.5206E+05	2.3715E+00	1.7051E+05	1.7051E+05	2.3703E+05	7.7547E+03	7.7547E+03

Attachment 2
WCS Sludge Inventory

Reference Date: 9/1/02

WCS Sludge Inventory																							
M:\WASTE8\H\bas\WCSystam\WCSystem.xls\Sludge\inv																							
Tank	Prn-147 (C)	Ei-154 (C)	Th-232 (C)	U-232 (C)	U-233 (C)	U-234 (C)	U-235 (C)	U-236 (C)	U-238 (C)	Pu-238 (C)	Pu-239 (C)												
1	3.63048E+02	1.1819E+03	1.2709E-02	1.7297E-03	1.5265E-02	1.7650E-02	4.3927E-01	6.4083E-01	5.1637E-02	1.3239E-02	2.9723E-01												
2	8.6501E+02	1.0861E+02	1.5057E+04	1.0399E+01	1.5250E-03	2.0247E-02	2.1177E-01	1.9755E-01	4.4154E-01	2.1040E-01	9.0842E-04												
3	1.3672E+01	1.0399E+02	1.5250E-02	5.0578E-02	5.7801E-01	5.6645E-01	5.3778E-01	5.3142E-01	3.0483E-01	1.0933E-03	7.3042E+00												
4	5.2289E+04	1.4067E+04	7.1920E-02	3.3491E+00	2.9845E+00	6.0537E+02	5.9775E+02	1.3386E+02	1.2824E+03	2.7487E+02	1.7490E+02												
5	3.7756E+03	6.6374E+03	5.6892E-02	2.4861E+00	1.8895E+00	4.2020E+02	1.1517E+02	2.7522E+02	3.3972E+02	1.7158E+02	9.2283E+03												
6	8.8565E+03	9.2882E+03	6.1842E-02	2.4860E+00	6.6277E+01	8.6484E+01	1.1270E+03	1.7494E+01	9.8222E+01	1.2588E+01	2.5487E+00												
7	1.5164E+03	6.5936E+03	8.5669E-02	9.1577E+00	8.3866E+00	4.2485E+04	5.6561E+03	8.7562E+03	7.1718E+02	1.2948E+01	2.5044E+00												
8	8.6985E+02	3.8126E+02	2.3233E+03	2.9471E+01	1.1336E+01	4.5426E+01	7.1295E+01	1.6778E+01	1.8136E+02	2.1167E+02	9.5877E+02												
9	9.1832E+00	1.1682E+02	1.8655E+03	1.7901E+03	1.9227E+04	1.9227E+04	1.5204E+04	1.3939E+04	6.5776E+00	2.8677E+04	1.8824E+00												
10	1.2178E+00	1.3826E+01	3.2201E+00	2.2830E+04	2.5904E+01	2.2101E+05	1.5682E+01	7.0598E+01	3.3649E+00	3.1515E+01	4.2127E+02												
11	2.0550E+04	5.9837E+04	1.4313E+02	1.6631E+04	2.0418E+00	1.6759E+00	1.5239E+00	1.4892E+00	9.3937E+02	6.0761E+04	1.5898E+00												
12	1.1246E+04	7.1824E+04	8.3805E+00	1.4052E+02	3.8238E+01	3.5849E+00	1.1666E+00	1.4101E+00	2.3162E+03	2.1820E+03	1.3363E+04												
13	5.7940E+03	4.7114E+04	1.9815E+01	5.5634E+02	4.0600E+01	5.7287E+00	1.5664E+01	1.8131E+00	1.4731E+01	5.5575E+03	6.3307E+03												
14	4.2988E+01	5.3103E+02	1.0584E+02	3.2201E+03	4.1408E+03	5.1289E+02	4.3541E+03	2.2105E+01	6.0449E+01	1.1210E+02	2.6738E+02												
15	7.4062E+03	6.0844E+04	1.1534E+00	1.3870E+01	3.7925E+01	6.1173E+02	3.5532E+00	5.8175E+04	1.2175E+03	5.8978E+02	1.3898E+04												
16	17	5.6404E+00	2.6933E+00	4.8849E-05	3.2871E+04	2.0426E+02	8.3807E+01	1.1872E+01	3.1664E+00	4.4466E+01	4.7984E+00												
18	18	6.0637E+01	2.9362E+01	5.6563E-04	6.2980E+03	2.3153E+01	9.3516E+02	1.4071E+02	3.5955E+01	6.5756E+02	4.6073E+02												
19	19	7.2298E+00	6.9086E+01	1.0302E+05	6.7959E+05	6.2030E+03	2.5477E+01	3.6395E+00	8.1349E+01	1.0580E+02	1.7673E+03												
20	20	6.7348E+02	8.0391E+02	5.6685E+06	1.7520E+01	1.7108E+01	2.3576E+03	1.5973E+02	1.0844E+00	6.3401E+01	2.3605E+04												
21	21	1.1834E+03	1.6484E+03	1.0746E+00	3.8683E+01	5.9073E+03	6.5592E+02	2.3473E+01	1.6251E+03	3.3971E+00	2.9395E+02												
22	22	1.5406E+04	1.4982E+03	9.7325E+03	2.2130E+02	2.0218E+00	1.6755E+04	2.3939E+03	5.3497E+02	1.3235E+04	1.1006E+01												
23	23	24	24	25	4.0334E+04	1.4982E+03	9.7325E+03	2.2130E+02	2.0218E+00	1.6755E+04	2.3939E+03	5.3497E+02	1.3235E+04										
26	26	27	27	28	28	29	30	31	32	33	34												
30	30	31	32	33	34	35	36	37	38	39	40												
37	38	39	40	41	42	43	44	45	46	47	48												
49	49	50	51	Total	3.5033E+06	9.4225E+05	2.7911E+00	3.1847E+00	2.1192E+00	2.0525E+02	5.5903E+02	4.7166E+01	9.4226E+01	7.0850E+03	1.2897E+02	1.7712E+03	1.0784E+06	3.5791E+01	2.1070E+02	2.6536E+02	1.6481E+05	1.2128E+05	1.7537E+01

Attachment 3

Calculation of Scaling Factors from WCS Concentration Data

Attachment 3, F-Area Tank Farms

Calculation of Sludge Scaling Factors from WCS Concentration Data

WCS Reference Date: 9/11/02

Tank	H-3	C-14	Nl-59	Co-60	Se-79	St-90	Y-90	Tc-99	Ru-106	Rh-106	Sb-125	Sn-126	I-129	Cs-134	Cs-135	Cs-137	Ba-137m	Ce-144	Pr-144	Pm-147
	Concentration (Ci/gal)																			
1	1.83E-06	3.33E-03	4.23E-02	2.32E-02	8.63E+01	8.63E+01	4.02E-02	4.34E-09	4.34E-09	3.61E-03	4.32E-03	1.91E-03	4.21E-06	2.69E-05	6.09E+00	5.76E+00	7.80E-12	7.80E-12	5.15E-02	
2	7.16E-07	8.43E-04	4.81E-03	5.77E-03	1.89E+01	1.89E+01	4.63E-12	4.63E-12	1.63E-04	1.07E-03	4.75E-08	9.61E-08	6.68E-06	1.36E+00	1.27E+00	1.13E-15	1.13E-15	2.14E-03		
3	6.20E-07	7.30E-04	5.47E-03	4.99E-03	1.72E+01	1.72E+01	8.64E-03	3.11E-11	1.51E-11	1.52E-04	9.29E-04	4.12E-08	1.89E-07	5.78E-06	1.22E+00	1.16E+00	1.87E-14	1.87E-14	3.40E-03	
4	2.63E-08	9.33E-04	5.40E-02	6.67E-02	3.11E+01	3.11E+01	1.55E-05	1.15E-05	2.49E-02	1.24E-03	5.50E-08	9.28E-05	7.72E-06	2.17E+00	2.05E+00	3.60E-07	3.60E-07	4.12E-01		
5	1.58E-06	3.59E-03	7.02E-02	2.51E-02	1.01E+02	1.01E+02	4.34E-02	4.69E-02	4.69E-02	9.06E-03	4.67E-03	4.67E-07	1.41E-05	2.91E-05	7.09E-06	6.71E+00	6.71E+00	1.59E-10	1.34E-01	
6	4.16E-06	1.30E-01	2.98E-03	1.32E+02	1.32E+02	1.32E+02	1.58E-02	3.79E-02	3.79E-02	2.33E-02	5.54E-03	2.46E-03	3.45E-05	3.45E-05	4.49E-05	8.70E+00	8.70E+00	2.38E-09	3.35E-01	
7	4.12E-06	8.96E-04	7.22E-03	4.88E-04	1.74E+01	1.74E+01	8.44E-03	6.04E-10	6.04E-10	6.04E-10	5.34E-04	9.07E-04	4.02E-04	5.92E-07	5.65E-06	1.123E+00	1.117E+00	1.117E-12	1.117E-12	7.57E-03
8	1.78E-06	6.70E-04	2.40E-02	4.14E-02	1.88E+01	1.88E+01	7.15E-03	8.46E-07	8.46E-07	6.58E-03	7.69E-04	3.41E-08	1.73E-05	4.79E-06	1.31E+00	1.24E+00	2.48E-08	2.48E-08	1.04E-01	
18	8.53E-07	5.02E-05	2.67E-04	4.15E-06	1.92E-01	1.92E-01	7.20E-05	9.77E-09	8.09E-06	7.71E-06	3.42E-10	2.26E-07	4.81E-08	1.34E-02	1.26E-02	1.74E-10	1.74E-10	1.29E-03		
26	2.09E-06	1.23E-04	4.88E-03	1.02E-05	7.00E-01	7.00E-01	1.76E-04	2.79E-04	2.79E-04	7.90E-03	1.88E-05	8.37E-10	6.62E-05	1.18E-07	4.78E-02	4.52E-02	8.50E-05	8.50E-05	1.45E-01	
33	2.85E-03	8.97E-01	2.04E-03	1.39E+02	1.39E+02	1.39E+02	2.75E-02	2.75E-02	2.75E-02	3.16E-03	1.68E-07	9.75E-03	2.36E-05	9.48E+00	8.91E+00	8.91E+00	7.35E-03	7.35E-03	2.32E+01	
34	6.88E-03	9.95E-01	4.91E-03	3.26E+02	8.49E-02	8.49E-02	6.49E-02	2.75E-02	2.75E-02	9.13E-03	4.05E-07	2.12E-02	5.69E-05	2.23E-01	2.11E+01	1.57E-02	4.97E+01	4.97E+01	6.50E-02	
47	1.76E-06	1.03E-04	3.12E-03	8.56E-06	5.63E-01	5.63E-01	1.48E-04	2.86E-05	2.86E-05	3.66E-03	1.58E-05	7.04E-10	2.32E-05	9.91E-08	3.85E-02	3.64E-02	3.50E-06	3.50E-06	6.50E-02	
Average	1.54E-06	1.93E-03	2.46E-01	1.34E-03	6.84E+01	6.84E+01	1.34E-03	3.17E-01	3.17E-01	2.49E-03	1.11E-07	2.40E-03	1.55E-05	4.73E+00	4.48E+00	1.78E-03	1.78E-03	5.71E+00		
19		2.74E-07	1.61E-05	1.29E-04	1.33E-06	6.88E-02	6.88E-02	2.31E-05	3.36E-09	4.27E-05	2.47E-05	2.47E-05	1.10E-10	1.17E-07	1.54E-03	1.35E+01	1.25E+01	4.03E+11	4.03E+11	6.81E-04
Average	2.74E-07	1.61E-05	1.29E-04	1.33E-06	6.88E-02	6.88E-02	2.31E-05	3.36E-09	3.36E-09	4.27E-05	2.47E-05	1.10E-10	1.17E-07	1.54E-03	1.35E+01	1.25E+01	4.03E+11	4.03E+11	6.81E-04	
	Scaling Factors (Ci/Ci Sr-90)																			
1	2.12E-08	3.87E-05	4.90E-04	2.69E-05	1.00E+00	1.00E+00	4.66E-04	5.03E-11	5.03E-11	4.18E-05	5.01E-05	2.22E-09	4.88E-08	3.12E-07	7.06E-02	6.68E-02	9.05E-14	9.05E-14	5.97E-04	
2	3.78E-08	4.45E-05	2.54E-04	3.04E-05	1.00E+00	1.00E+00	2.44E-13	2.44E-13	2.44E-13	5.66E-05	5.66E-05	2.51E-09	6.10E-09	5.32E-07	7.11E-02	6.72E-02	5.96E-17	5.96E-17	1.19E-04	
3	3.61E-08	4.25E-05	3.18E-04	2.91E-05	1.00E+00	1.00E+00	1.81E-12	1.81E-12	1.47E-12	2.39E-05	2.39E-05	1.10E-09	3.36E-07	7.09E-02	6.71E-02	1.09E-15	1.09E-15	1.98E-04		
4	8.44E-10	3.00E-05	1.73E-03	2.14E-05	1.00E+00	1.00E+00	3.70E-04	3.68E-07	3.68E-07	8.01E-04	3.98E-05	1.77E-09	2.98E-16	2.48E-07	6.96E-02	5.95E-02	1.15E-08	1.15E-08	1.32E-02	
5	1.56E-08	3.55E-05	6.95E-04	2.49E-05	1.00E+00	1.00E+00	4.30E-04	4.64E-10	4.64E-10	8.98E-05	4.63E-05	2.05E-09	1.40E-07	2.88E-07	7.03E-02	6.65E-02	1.58E-12	1.58E-12	1.33E-03	
6	3.16E-05	2.37E-07	5.14E-05	4.14E-04	2.27E-05	1.00E+00	1.00E+00	3.92E-04	2.87E-09	2.87E-09	4.21E-05	1.87E-09	3.39E-07	2.62E-07	6.99E-02	6.61E-02	1.81E-11	1.81E-11	2.69E-03	
7	9.50E-08	5.13E-05	1.28E-03	2.20E-05	1.00E+00	1.00E+00	2.80E-05	3.47E-11	3.47E-11	3.07E-05	5.20E-05	2.31E-09	3.40E-08	3.24E-07	7.07E-02	6.69E-02	6.71E-14	6.71E-14	4.34E-04	
8	4.45E-06	3.13E-05	1.39E-03	2.17E-03	1.00E+00	1.00E+00	3.78E-05	4.51E-08	4.51E-08	4.51E-05	4.10E-05	1.82E-09	1.98E-07	2.55E-07	6.98E-02	6.60E-02	1.32E-09	1.32E-09	5.53E-03	
18	4.62E-04	2.99E-06	6.97E-03	1.48E-05	1.00E+00	1.00E+00	5.10E-06	6.42E-04	6.42E-04	4.02E-05	4.78E-05	1.78E-07	2.51E-06	1.98E-06	9.10E-10	9.10E-10	9.10E-10	9.10E-10	6.73E-03	
26	2.05E-05	2.10E-05	5.99E-03	1.51E-05	1.00E+00	1.00E+00	2.52E-04	3.98E-04	3.98E-04	2.70E-05	1.13E-04	1.19E-09	9.44E-09	1.63E-07	6.82E-02	6.45E-02	1.21E-04	1.21E-04	2.07E-01	
33																				
34																				
47	3.13E-06	1.84E-04	5.53E-03	1.52E-05	1.00E+00	1.00E+00	2.64E-04	5.08E-05	5.08E-05	6.50E-03	2.32E-05	1.25E-09	4.25E-05	1.76E-07	6.84E-02	6.41E-02	6.21E-06	6.21E-06	1.15E-01	
Average	1.10E-06	7.48E-05	2.50E-03	2.20E-05	1.00E+00	1.00E+00	1.93E-05	3.36E-04	3.36E-04	4.89E-08	4.89E-08	6.20E-04	3.59E-05	1.58E-09	1.70E-06	2.24E-07	1.97E+02	1.97E+02	5.76E-05	
19	3.98E-06	2.34E-04	1.88E-03	1.93E-05	1.00E+00	1.00E+00	1.93E-05	1.93E-05	1.93E-05	1.93E-05	1.93E-05	1.59E-05	1.59E-05	1.70E-06	2.24E-07	1.97E+02	1.97E+02	5.85E-03		
Average	3.98E-06	2.34E-04	1.88E-03	1.93E-05	1.00E+00	1.00E+00	1.93E-05	1.93E-05	1.93E-05	1.93E-05	1.93E-05	1.59E-05	1.59E-05	1.70E-06	2.24E-07	1.97E+02	1.97E+02	5.85E-03		

Attachment 3. F-Area Tank Farms

Calculation of Sludge Scaling Factors from WCS Concentration Data

WCS Reference Date: 9/11/02

Concentration (Ci/gal)	Eu-154	U-233	U-234	U-235	U-238	Np-237	Pu-238	Pu-239	Pu-240	Pu-241	Pu-242	Ingrown Am-241	Am-241	Am-242m	Cm-244	Cm-245	Total	TRU	
1	1.69E-01			2.52E-06	6.28E-05	9.15E-05	7.42E-02	4.25E-03	2.65E-02	8.74E-07	5.80E-03	3.02E-01	3.80E-04	6.07E-05	6.60E-11	1.85E+02			
2	2.71E-02			2.03E-07	5.06E-06	5.29E-05	4.94E-03	1.10E-03	5.28E-03	2.27E-07	1.50E-03	7.41E-02	9.22E-05	1.24E-05	1.64E-11	4.07E+01			
3	2.75E-02			5.07E-07	1.26E-05	9.45E-05	4.16E-02	5.94E-03	1.33E-03	7.62E-03	2.73E-07	1.83E-03	6.44E-02	8.05E-05	1.15E-05	1.42E-11	3.69E+01		
4	1.11E-01			6.12E-07	2.63E-05	2.38E-05	4.77E-03	1.05E-03	1.05E-02	2.16E-07	1.38E-03	8.81E-02	1.14E-04	2.52E-05	1.89E-11	6.72E+01			
5	2.36E-01			3.72E-06	8.81E-05	1.49E-04	1.03E-01	1.71E-02	4.09E-02	3.11E-06	6.09E-03	3.28E-01	4.18E-04	7.43E-05	7.13E-11	2.17E+02			
6	3.72E-01			2.66E-06	9.94E-05	3.45E-05	1.02E-02	3.54E-03	4.51E-02	6.98E-02	6.98E-06	6.93E-01	5.06E-04	1.02E-04	8.46E-11	2.82E+02			
7	3.12E-02			1.82E-06	4.38E-05	4.02E-05	1.16E-01	1.75E-02	4.19E-03	3.41E-02	1.35E-06	6.17E-03	6.07E-02	7.62E-05	1.20E-05	1.39E-11	3.76E+01		
8	5.91E-02			8.42E-07	3.87E-05	1.76E-05	7.05E-02	1.11E-02	2.60E-03	2.81E-02	3.28E-06	2.66E-03	5.34E-02	6.90E-05	1.49E-05	1.17E-11	4.05E+01		
18	6.28E-04			9.14E-08	4.92E-06	2.10E-02	2.99E-03	7.65E-04	1.40E-02	9.80E-07	1.52E-03				1.52E-07	1.19E-13	4.52E+01		
26	5.34E-03			7.88E-08	7.19E-06	5.96E-02	8.52E-03	1.90E-03	4.71E-02	3.92E-07	1.85E-03				6.93E-07	2.92E-13	1.78E+00		
33	1.03E+00	9.60E-12	8.01E-08	6.31E-06	6.33E-04	2.48E-04	5.85E-04	1.77E-01	3.22E-02	1.65E-06	7.06E-03				3.24E+02				
34	2.30E+00			4.56E-06	3.22E-04	2.49E-04	5.20E-02	1.16E-02	2.73E-01	2.41E-06	1.15E-02	6.65E-01	9.00E-04	3.19E-10	7.53E+02				
47	3.84E-03			7.52E-08	5.95E-06	6.39E-02	9.13E-03	2.04E-03	4.50E-02	4.20E-07	2.11E-03				5.43E-07	2.46E-13	1.40E+00		
Average	3.36E-01	9.60E-12	8.01E-08	6.169E-06	1.04E-04	9.98E-05	5.36E-02	2.62E-02	5.44E-03	1.21E-01	1.56E-06	4.34E-03	2.30E-01	3.01E-04	5.93E-05	3.81E-11	1.53E+02	3.20E-01	
19	2.72E-04			2.67E-08	2.44E-06		1.00E-02	1.43E-03	3.20E-04	4.15E-02	6.58E-07	4.02E-03				5.77E-08	3.82E-14	2.65E+01	
Average	2.72E-04			2.67E-08	2.44E-06		1.00E-02	1.43E-03	3.20E-04	4.15E-02	6.58E-07	4.02E-03				5.77E-08	3.82E-14	2.65E+01	1.58E-02

Scaling Factors (Ci/Ci Sr-80)	Eu-154	U-233	U-234	U-235	U-238	Np-237	Pu-238	Pu-239	Pu-240	Pu-241	Pu-242	Ingrown Am-241	Am-241	Am-242m	Cm-244	Cm-245	Total	TRU	
1	1.96E-03			2.92E-08	7.27E-07	1.06E-06	8.60E-04	2.20E-04	4.92E-05	3.07E-04	1.01E-08	6.72E-05	3.50E-03	4.41E-06	7.03E-07	7.66E-13			
2	1.43E-03			2.67E-08	2.79E-06	1.82E-05	2.61E-03	5.83E-05	2.73E-04	1.20E-08	7.94E-05	3.91E-03	4.86E-06	6.52E-07	8.65E-13				
3	1.60E-03			2.95E-08	3.36E-07	5.50E-06	2.42E-03	3.46E-04	7.73E-05	4.35E-08	1.20E-04	5.75E-03	4.68E-06	6.77E-07	8.25E-13				
4	3.56E-03			1.96E-08	8.48E-07	7.55E-07	1.51E-04	1.51E-04	3.38E-05	3.24E-04	6.95E-09	4.42E-05	2.83E-03	3.67E-06	8.11E-07	6.08E-13			
5	2.34E-03			3.68E-08	6.73E-07	1.47E-06	1.02E-03	1.70E-04	4.05E-05	3.08E-04	1.20E-08	6.04E-05	3.25E-03	4.14E-06	7.36E-07	7.06E-13			
6	2.82E-03			2.02E-08	7.56E-07	2.62E-07	3.04E-03	3.43E-04	7.69E-05	3.43E-04	5.29E-08	5.26E-05	2.99E-03	3.67E-06	6.81E-07	6.43E-13			
7	1.79E-03			1.04E-07	2.51E-06	6.67E-06	1.01E-03	2.40E-04	1.95E-03	7.75E-08	3.54E-04	3.49E-03	4.37E-06	6.83E-07	6.75E-13				
8	3.15E-03			4.48E-08	2.06E-06	9.36E-07	3.75E-03	5.89E-04	1.50E-03	1.75E-07	1.42E-04	2.85E-03	3.68E-06	7.92E-07	6.26E-13				
18	3.28E-03			4.77E-07	2.57E-05	3.09E-07	1.56E-04	3.99E-03	7.30E-04	7.91E-02	6.12E-06	7.91E-03	7.93E-07	6.21E-13					
26	7.62E-03			1.12E-07	1.03E-05	8.52E-02	1.22E-02	2.72E-03	6.73E-02	5.59E-07	2.64E-03	9.90E-07	4.16E-13						
33	7.38E-03	6.91E-14		5.76E-10	4.55E-06	1.77E-06	4.21E-06	1.27E-03	2.32E-04	7.29E-03	1.19E-08	5.08E-05	1.99E-03	2.70E-06	9.92E-07	4.17E-13			
34	7.04E-03			1.40E-08	9.88E-07	7.63E-07	1.60E-04	3.57E-05	8.38E-04	7.40E-09	3.54E-06	2.04E-03	2.76E-06	9.79E-07	4.28E-13				
47	6.82E-03			1.33E-07	1.06E-05	1.13E-01	1.62E-02	3.62E-03	7.99E-02	7.45E-07	3.74E-03		9.63E-07	4.36E-13					
Average	3.91E-03	6.91E-14	5.76E-10	7.94E-08	4.68E-06	1.76E-06	2.95E-02	3.71E-03	8.67E-04	1.80E-02	5.23E-07	1.18E-03	3.06E-03	3.91E-06	8.11E-07	6.27E-13	2.25E+00	3.83E-02	
19	3.95E-03			3.88E-07	3.55E-05		1.46E-01	2.08E-02	4.65E-03	6.03E-01	9.56E-06	5.83E-02		8.33E-07	5.55E-13				
Average	3.95E-03			3.88E-07	3.55E-05		1.46E-01	2.08E-02	4.65E-03	6.03E-01	9.56E-06	5.83E-02		8.33E-07	5.55E-13				

Attachment 4

Comparison of F-Area Tank Farm Sludge Scaling Factors for Consolidation

Attachment 4

Comparison of F-Tank Farm Sludge Scaling Factors for Consolidation

Sludge scaling factors (C/Ci Sr-90)									
Isotope	Tank 1	Tank 2	Tank 3	Tank 4	Tank 5	Tank 6	Tank 7	Tank 8	Tank 18
H-3	3.78E-08	3.61E-08	8.44E-10	1.58E-08	2.37E-07	9.50E-08	4.45E-06	2.99E-06	3.13E-06
C-14	2.12E-08	5.27E-04	5.03E-04	1.30E-04	3.22E-04	4.84E-04	3.61E-04	2.32E-04	2.54E-04
Tr-99	4.66E-04	2.35E-09	1.77E-09	2.05E-09	1.87E-09	1.82E-09	1.78E-09	1.78E-09	1.78E-09
F-123	2.22E-09	2.51E-09	1.87E-09	2.31E-09	2.05E-09	1.82E-09	1.78E-09	1.78E-09	1.78E-09
U-234	7.27E-07	2.67E-07	7.38E-07	8.46E-07	8.73E-07	7.56E-07	2.51E-08	2.06E-06	2.57E-05
U-238	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06

PA radionuclides, fraction of mean scaling factor (allowable fraction = 0.1-10.0)									
Isotope	Tank 1	Tank 2	Tank 3	Tank 4	Tank 5	Tank 6	Tank 7	Tank 8	Tank 18
St-90	4.66E-01	4.66E-01	4.63E-01	4.66E-01	4.66E-01	4.64E-01	4.64E-01	4.62E-01	4.62E-01
Y-90	4.66E-01	4.66E-01	4.63E-01	4.66E-01	4.66E-01	4.64E-01	4.64E-01	4.62E-01	4.62E-01
H-3	3.58E-06	3.36E-04	1.59E-09	1.59E-09	1.59E-09	1.00	1.00	1.00	1.00
C-14	3.58E-06	3.36E-04	1.59E-09	1.59E-09	1.59E-09	1.00	1.00	1.00	1.00
Tc-99	3.58E-06	3.36E-04	1.59E-09	1.59E-09	1.59E-09	1.00	1.00	1.00	1.00
I-129	3.58E-06	3.36E-04	1.59E-09	1.59E-09	1.59E-09	1.00	1.00	1.00	1.00
U-234	3.55E-05	3.55E-05	3.55E-05	3.55E-05	3.55E-05	1.00	1.00	1.00	1.00
U-238	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06

Predominant radionuclides, variation from mean fractional activity (allowable variation = 10%)									
Isotope	Tank 1	Tank 2	Tank 3	Tank 4	Tank 5	Tank 6	Tank 7	Tank 8	Tank 18
St-90	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	5.0%	-11.7%
Y-90	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	3.9%	-11.7%
H-3	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	5.0%	-9.5%
C-14	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	3.9%	-9.5%
Tc-99	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	3.9%	-9.5%
I-129	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	3.9%	-9.5%
U-234	4.47%	4.4%	4.3%	3.8%	4.4%	4.0%	3.9%	3.9%	-9.5%
U-238	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06

Sludge scaling factors (C/Ci Sr-90)	PA rats, fraction of mean scaling factor (allowable fraction = 0.1-10.0)		
Isotope	Tank 19	Mean Ci Cs/Sr-90	Tank 19
H-3	3.58E-06	3.36E-04	1.00
C-14	3.58E-06	3.36E-04	1.00
Tc-99	3.58E-06	3.36E-04	1.00
I-129	3.58E-06	3.36E-04	1.00
U-234	3.55E-05	3.55E-05	1.00
U-238	0.06	0.06	1.00

Fractional Activity	Prod. rats, variation from mean fract. act. (allowable variation = 10%)		
Isotope	Tank 19	Mean	Tank 19
Sr-80	2.59E-03	2.59E-03	0.0%
Y-90	2.59E-03	2.59E-03	0.0%

Attachment 5

F-Area Tank Farm Sludge Waste Streams Exclusion Criteria

**Attachment 5. F-Area Tank Farm Sludge Waste Streams
Exclusion Criteria**

Isotope	Mean Ci/Ci Sr-90)	Mean Distribution (%)	<1% of dist?(a)	Not Expected	Distribution		
					RADs remaining after excl criteria	Mean distribution (percent)	Re-normalized distribution
Waste Stream FTK-00002-1							
H-3				x			
C-14	1.10E-06	4.88E-05			C-14	4.88E-05	4.88E-05
Ni-59	7.48E-05	3.32E-03	yes		Co-60	1.11E-01	1.11E-01
Co-60	2.50E-03	1.11E-01	yes(b)		Sr-90	4.44E+01	4.44E+01
Se-79	2.20E-05	9.78E-04	yes		Y-90	4.44E+01	4.44E+01
Sr-90	1.00E+00	4.44E+01	no		Tc-99	1.69E-02	1.69E-02
Y-90	1.00E+00	4.44E+01	no		Sb-125	1.28E-01	1.28E-01
Tc-99	3.81E-04	1.69E-02			I-129	8.06E-08	8.06E-08
Ru-106	6.51E-05	2.89E-03	yes		Cs-137	3.09E+00	3.09E+00
Rh-106	6.51E-05	2.89E-03	yes		Ba-137m	2.92E+00	2.93E+00
Sb-125	2.88E-03	1.28E-01	yes(b)		Pm-147	2.30E+00	2.30E+00
Sn-126	4.10E-05	1.82E-03	yes		Eu-154	1.73E-01	1.73E-01
I-129	1.82E-09	8.06E-08			U-233	3.07E-12	3.07E-12
Cs-134	2.14E-05	9.49E-04	yes		U-234	2.56E-08	2.56E-08
Cs-135	2.55E-07	1.13E-05	yes		U-235	3.53E-06	3.53E-06
Cs-137	6.97E-02	3.09E+00	no		U-238	2.08E-04	2.08E-04
Ba-137m	6.59E-02	2.92E+00	no		Np-237	7.82E-05	7.82E-05
Ce-144	1.76E-05	7.80E-04	yes		Pu-238	1.31E+00	1.31E+00
Pr-144	1.76E-05	7.80E-04	yes		Pu-239	1.65E-01	1.65E-01
Pr-144m	1.76E-05	7.80E-04	yes		Pu-240	3.84E-02	3.85E-02
Pm-147	5.17E-02	2.30E+00	no		Pu-241	7.98E-01	7.98E-01
Eu-154	3.91E-03	1.73E-01	yes(b)		Pu-242	2.32E-05	2.32E-05
U-233	6.91E-14	3.07E-12			Am-241	1.88E-01	1.88E-01
U-234	5.76E-10	2.56E-08			Am-242m	1.74E-04	1.74E-04
U-235	7.94E-08	3.53E-06			Cm-245	2.78E-11	2.78E-11
U-238	4.68E-06	2.08E-04			Total	1.00E+02	1.00E+02
Np-237	1.76E-06	7.82E-05			Total	1.00E+02	1.00E+02
Pu-238	2.95E-02	1.31E+00					
Pu-239	3.71E-03	1.65E-01					
Pu-240	8.67E-04	3.84E-02					
Pu-241	1.80E-02	7.98E-01					
Pu-242	5.23E-07	2.32E-05					
Am-241	4.23E-03	1.88E-01					
Am-242m	3.91E-06	1.74E-04					
Cm-244	8.11E-07	3.60E-05					
Cm-245	6.27E-13	2.78E-11	yes				
Total	2.25E+00	1.00E+02					
Waste Stream FTK-00002-19							
H-3				x			
C-14	3.98E-06	1.03E-06			C-14	1.03E-06	1.03E-06
Co-60	1.88E-03	4.87E-04	yes		Sr-90	2.59E-01	2.59E-01
Ni-59	2.34E-04	6.07E-05	yes		Y-90	2.59E-01	2.59E-01
Se-79	1.93E-05	5.02E-06	yes		Tc-99	8.71E-05	8.71E-05
Sr-90	1.00E+00	2.59E-01	yes(b)		I-129	4.13E-10	4.13E-10
Y-90	1.00E+00	2.59E-01	yes(b)		Cs-137	5.10E+01	5.10E+01
Tc-99	3.36E-04	8.71E-05			Ba-137m	4.83E+01	4.83E+01
Ru-106	4.89E-08	1.27E-08	yes				
Rh-106	4.89E-08	1.27E-08	yes				
Sb-125	6.20E-04	1.61E-04	yes				
Sn-126	3.59E-05	9.32E-06	yes				
I-129	1.59E-09	4.13E-10					
Cs-134	1.70E-06	4.41E-07	yes				
Cs-135	2.24E-07	5.81E-08	yes				
Cs-137	1.97E+02	5.10E+01	no				
Ba-137m	1.86E+02	4.83E+01	no				
Ce-144	5.85E-10	1.52E-10	yes				
Pr-144	5.85E-10	1.52E-10	yes				
Pr-144m	5.85E-10	1.52E-10	yes				
Pm-147	9.89E-03	2.56E-03	yes				
Eu-154	3.95E-03	1.02E-03	yes				
U-233				x			
U-234				x			
U-235	3.88E-07	1.01E-07			U-235	1.01E-07	1.01E-07
U-238	3.55E-05	9.20E-06			U-238	9.20E-06	9.20E-06
Np-237				x			
Pu-238	1.46E-01	3.78E-02			Pu-238	3.78E-02	3.78E-02
Pu-239	2.08E-02	5.40E-03			Pu-239	5.40E-03	5.40E-03
Pu-240	4.65E-03	1.21E-03			Pu-240	1.21E-03	1.21E-03
Pu-241	6.03E-01	1.57E-01			Pu-241	1.57E-01	1.57E-01
Pu-242	9.56E-06	2.48E-06			Pu-240	2.48E-06	2.48E-06
Am-241	5.83E-02	1.51E-02			Am-241	1.51E-02	1.51E-02
Am-242m				x			
Cm-244	8.38E-07	2.17E-07	yes		Cm-245	1.44E-13	1.44E-13
Cm-245	5.55E-13	1.44E-13			Total	1.00E+02	1.00E+02
Total	3.85E+02	1.00E+02			Total	1.00E+02	1.00E+02

Bold = PA radionuclides

(a) radionuclides included only because they were expected to be present >1%

(b) retained in distribution since they are close to 1% of total activity

Attachment 6

Comparison of F-Area Sludge Waste Against WAC 3.17, Rev. 7, Requirements

Attachment 6
Comparison of F-Area Sludge Waste Against WAC 3.17, Rev. 7, Requirements

Comparison Against WAC 3.17, Rev. 7, Requirements - Waste Stream FTK-00002-1								
Comparison to Package Guidelines (Section 3.5.1)								
Isotope	Isotope Average Ci/gal	LAWV limit Ci/ft3	LAWV limit Ci for B-25	Amt isotope in B-25 to reach LAWV Limit (gal) = LAWV limit in B-25/sludge activity	Total Curies in B-25 TRU Curies	for 5000 lb min waste nCi/g	wt to not be TRU	
H-3		1.10E+01	9.90E+02					
C-14	1.54E-06	2.50E-05	2.25E-03	1.46E+03				
Tc-99	2.32E-02	5.60E-05	5.04E-03	2.17E-01	3.32E+01	6.95E-02	30.62265	1531.132
I-129	1.11E-07	1.10E-08	9.90E-07	8.92E+00				
U-234	8.01E-08	1.10E-03	9.90E-02	1.24E+06				
U-238	1.04E-04	1.20E-03	1.08E-01	1.04E+03				
Sum of Fractions Calculation (Section 3.5.2)								
Isotope	Isotope Average Ci/gal	Ci/ft3 sludge	Ci/ft3 waste	LAWV limit Ci/ft3	Fraction	TRU Curies/Total Curies =	2.09E-03	
H-3				1.10E+01				
C-14	1.54E-06	1.15E-05	3.63E-09	2.50E-05	1.45E-04	Np-237	9.98E-05	
Tc-99	2.32E-02	1.74E-01	5.46E-05	5.60E-05	9.75E-01	Pu-238	5.36E-02	
I-129	1.11E-07	8.30E-07	2.61E-10	1.10E-08	2.38E-02	Pu-239	2.62E-02	
U-234	8.01E-08	5.89E-07	1.89E-10	1.10E-03	1.71E-07	Pu-240	5.44E-03	
U-238	1.04E-04	7.78E-04	2.45E-07	1.20E-03	2.04E-04	Pu-242	1.56E-06	
ft3 sludge/ft3 waste		3.15E-04		Total	9.99E-01	Am-241	2.34E-01	
ft3 sludge/B-25		2.83E-02				Am-242m	3.01E-04	
Gal sludge/B-25		2.12E-01				Cm-245	3.81E-11	
Equivalent Curies		3.24E+01						
max amount of sludge in a B-25 to meet Sum of Fractions Limit								
TRU curies				6.78E-02	min lb wt to be TRU			
nCi/g at max wt				2.99E+01	1493.176116			
Nuclear Criticality Safety Criteria (Section 3.5.3)								
Specific Activity Ci/g	Activity in Sludge Ci/gal sludge	Ci	Mass (g)	Equiv Factor	FGE			
U-233	9.648E-03	9.60E-12	3.25E-10	3.37E-08	4.72E-08			
U-235	2.160E-06	1.69E-06	5.73E-05	2.65E+01	1.0	2.65E+01		
Pu-239	6.132E-02	2.62E-02	8.88E-01	1.45E+01	1.6	2.32E+01		
Pu-241	1.034E+02	1.21E-01	4.10E+00	3.97E-02	3.5	1.39E-01		
Am-242m	9.717E+00	3.01E-04	1.02E-02	1.05E-03	54.0	5.67E-02		
Cm-245	1.716E-01	3.81E-11	1.29E-09	7.53E-09	24.0	1.81E-07		
Gal Sludge		33.9		Total	4.99E+01			
Equiv Curies		5.19E+03						

Comparison Against WAC 3.17, Rev. 7, Requirements - Waste Stream FTK-00002-19								
Comparison to Package Guidelines (Section 3.5.1)								
Isotope	Isotope Average Ci/gal	LAWV limit Ci/ft3	LAWV limit Ci for B-25	Amt isotope in B-25 to reach LAWV Limit (gal) = LAWV limit in B-25/sludge activity	Total Curies in B-25 TRU Curies	for 5000 lb min waste nCi/g	wt to not be TRU	
H-3		1.10E+01	9.90E+02					
C-14	2.74E-07	2.50E-05	2.25E-03	8.21E+03				
Tc-99	2.31E-05	5.60E-05	5.04E-03	2.18E+02	3.34E+04	6.98E+01	30755.21	1537761
I-129	1.10E-10	1.10E-08	9.90E-07	9.00E+03				
U-234		1.10E-03	9.90E-02					
U-238	2.44E-06	1.20E-03	1.08E-01	4.43E+04				
Sum of Fractions Calculation (Section 3.5.2)								
Isotope	Isotope Average Ci/gal	Ci/ft3 sludge	Ci/ft3 waste	LAWV limit Ci/ft3	Fraction	TRU Curies/Total Curies =	5.95E-04	
H-3				1.10E+01				
C-14	2.74E-07	2.05E-06	6.29E-07	2.50E-05	2.52E-02	Np-237		
Tc-99	2.31E-05	1.73E-04	5.30E-05	5.60E-05	9.47E-01	Pu-238	1.00E-02	
I-129	1.10E-10	8.23E-10	2.52E-10	1.10E-08	2.30E-02	Pu-239	1.43E-03	
U-234				1.10E-03		Pu-240	3.20E-04	
U-238	2.44E-06	1.83E-05	5.60E-06	1.20E-03	4.67E-03	Pu-242	6.58E-07	
ft3 sludge/ft3 waste		3.07E-01		Total	9.99E-01	Am-241	4.02E-03	
ft3 sludge/B-25		2.76E+01				Am-242m		
Gal sludge/B-25		2.07E+02				Cm-245	3.82E-14	
Equivalent Curies		5.47E+03						
max amount of sludge in a B-25 to meet Sum of Fractions Limit								
TRU curies				3.26E+00	min lb wt to be TRU			
nCi/g at max wt				1.44E+03	71752.310J6			
Nuclear Criticality Safety Criteria (Section 3.5.3)								
Specific Activity Ci/g	Activity in Sludge Ci/gal sludge	Ci	Mass (g)	Equiv Factor	FGE			
U-233	9.648E-03	2.67E-08	2.61E-05	1.21E+01	1.4			
U-235	2.160E-06	2.67E-08	2.61E-05	1.21E+01	1.0	1.21E+01		
Pu-239	6.132E-02	1.43E-03	1.40E+00	2.28E+01	1.6	3.65E+01		
Pu-241	1.034E+02	4.15E-02	4.06E+01	3.92E+01	3.5	1.37E+00		
Am-242m	9.717E+00				54.0			
Cm-245	1.716E-01	3.82E-14	3.74E-11	2.18E-10	24.0	5.22E-09		
Gal Sludge		977.9		Total	4.99E+01			
Equiv Curies		2.59E+04						

Attachment 7

**Waste Characterization Forms for Sludge Fraction,
FTK-00002-1 and FTK-00002-19**

EAV Low Level Waste Stream Characterization

1. Waste Stream ID FTK-00002-1	2. Generating Facility FTF	3. Waste Organization F-Area Tank Farm	4. Building Name 241-F	5. Effective Date 6/30/2002	
6. WITS Stream Description Sludge contaminated waste from HLW dks 1-8, 18, 26, 33, 34, and 47		7. Reason for Submittal Re-characterize Stream	8. WSCF No. 9. Rev 2		
10. Activity Generating Waste F Tank Farm Operations		11. Physical Form Combustible	12. TSD Facility/Location EAV - Law Vault - 1		
13. Valid Calculation Method for Waste <input type="checkbox"/> Char by Pack <input type="checkbox"/> Dose-to-Curie <input type="checkbox"/> Smear to Curie <input checked="" type="checkbox"/> Curies or RAD Weight		14. STC Constant N/A	15. STC Min Value N/A	16. DTC Waste Form N/A	
17. Assigned Container Types B-12 (14) B-25 (Yellow)-Light (6) B-25 (Yellow) 625# (733) 55-gal Drum (A,7A) (15) Riser Plug Box (945)	18. DTC Containers N/A	19. Waste Description Contaminated Equipment Job Control Waste		Vol % 50 50	
<i>Any approved container (WITS) 214103</i>					
20. WITS ID FTK000021-LLW	21. Tech Baseline WSRC-2000-00215, Rev.1	22. Container Document No. N/A	23. Deviation Document No. N/A	24. CERCLA <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
25. Waste < 2 nCi/g <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	26. Source(s) <input type="checkbox"/> PCB Category <input type="checkbox"/> PCB Leachable	27. PCB Category <input type="checkbox"/> PCB Bulk <input type="checkbox"/> PCB Remediation	<input checked="" type="checkbox"/> N/A <input type="checkbox"/> PCB Laboratory	28. Comments NA	
29. Meas Tech <input type="checkbox"/> Sample and Analysis <input checked="" type="checkbox"/> Process Knowledge		30. Waste Incidental to Reprocessing (WIR) — Evaluation Document No. _____			
31. Currently Assigned Isotopes					
Isotope	Ci %	Basis for Exclusion (PA isotopes only)	Isotope	Ci %	Basis for Exclusion*
C-14	4.88E-05		Am-242m	1.74E-04	
Co-60	1.11E-01		Cm-245	2.78E-11	
Sr-90	4.44E+01				
Y-90	4.44E+01		H-3		Not present
Tc-99	1.69E-02				
Sb-125	1.28E-01				
I-129	8.06E-08				
Cs-137	3.09E+00				
Ba-137m	2.93E+00				
Pm-147	2.30E+00				
Eu-154	1.73E-01				
U-233	3.07E-12				
U-234	2.56E-08				
U-235	3.53E-06				
U-238	2.08E-04				
Np-237	7.82E-05				
Pu-238	1.31E+00				
Pu-239	1.65E-01				
Pu-240	3.85E-02				
Pu-241	7.98E-01				
Pu-242	2.35E-05				
Am-241	1.88E-01				
			Total	100.00 <i>Page 214103</i> 70.550%	
32. GCO Name P. J. Riley		33. GCO Address 242-102F	34. GCO Phone 2-4425		
35. GCO Signature** <i>P. J. Riley</i>		Date 2/4/03	Environmental Compliance Authority Signature <i>Newt Bresler</i>		Date 2/4/03
Solid Waste Generator Service Approval		Date	WITS Data Input Signature		Date

**Generator Certification Statement: "I certify that to the best of my knowledge, the data submitted provides a true and accurate description of the waste."

EAV Low Level Waste Stream Characterization

****Generator Certification Statement:** "I certify that to the best of my knowledge, the data submitted provides a true and accurate description of the waste."

Attachment 8

Waste Characterization Form for Supernate Fraction, FHW-00001

EAV/CIF Low Level Waste Stream Characterization

• [View Details](#) • [Edit](#) • [Delete](#) • [Print](#) • [Email](#)

****Generator Certification Statement:** "I certify that to the best of my knowledge, the data submitted provides a true and accurate description of the waste."

EAV/CIF Low Level Waste Stream Characterization

Waste Stream ID
FHW00001

WCF No.

80

WITS □

FHW000011.W

CIF Section

36. Major Waste Components

37. Chemicals/Organics/Metals

Concentration, PPM

Description

Concentration Wt%

37. Chemicals/Organics/Metals

Concentration, PPM

Chemicals/Organics/Metals

Constitutive CRM

38. Properties

Heat Value (BTU/lb)	Ash Content (Weight %)	Total Halogens (Weight %)
No. of Liquid Layers in Waste	Water (Weight%)	

No. of Liquid Layers in Waste			Water (Weight%)			
Liquid Layer Description	Vol % Liquid Layer	pH	Spec Gravity	Est Viscosity(CP)	Total Susp Solids (Wt%)	Total Diss Solids (Wt%)

Attachment 9

F-Area Tank Farm Sludge Waste Streams, Sludge and Supernate Fractions Activity Distributions

Attachment 9. F-Area Tank Farm Sludge Waste Streams
Sludge and Supernate Fractions Activity Distributions

SLUDGE FRACTION			SUPERNATE FRACTION		
Radionuclide	Normalized Distribution (%)	Scaling Factors Ci/Ci Sr-90	Activity Fraction	Normalized Distribution (%)	Scaling Factors Ci/Ci Cs-137
FTK-00002-1			FHW-00001		
H-3			2.00E-01	2.01E-01	4.00E-03
C-14	4.88E-05	1.10E-06	1.70E+00	1.71E+00	3.40E-02
Co-60	1.11E-01	2.50E-03	4.70E-02	4.73E-02	9.30E-04
Sr-90	4.44E+01	1.00E+00	9.10E-03	9.15E-03	1.80E-04
Y-90	4.44E+01	1.00E+00	1.10E-05	1.11E-05	2.10E-07
Tc-99	1.69E-02	3.81E-04	5.00E+01	5.03E+01	1.00E+00
Sb-125	1.28E-01	2.88E-03	4.70E+01	4.73E+01	9.40E-01
I-129	8.06E-08	1.82E-09	2.60E-04	2.62E-04	5.20E-06
Cs-137	3.09E+00	6.97E-02	7.10E-05	7.14E-05	1.40E-06
Ba-137m	2.93E+00	6.59E-02			
Pm-147	2.30E+00	5.17E-02			
Eu-154	1.73E-01	3.91E-03			
U-233	3.07E-12	6.91E-14			
U-234	2.56E-08	5.76E-10			
U-235	3.53E-06	7.94E-08			
U-238	2.08E-04	4.68E-06			
Np-237	7.82E-05	1.76E-06			
Pu-238	1.31E+00	2.95E-02			
Pu-239	1.65E-01	3.71E-03			
Pu-240	3.85E-02	8.67E-04			
Pu-241	7.98E-01	1.80E-02			
Pu-242	2.32E-05	5.23E-07			
Am-241	1.88E-01	4.23E-03			
Am-242m	1.74E-04	3.91E-06			
Cm-245	2.78E-11	6.27E-13			
Total	1.00E+02		9.94E+01	1.00E+02	
FTK-00002-19					
H-3					
C-14	1.03E-06	3.98E-06			
Ni-59					
Co-60					
Sr-90	2.59E-01	1.00E+00			
Y-90	2.59E-01	1.00E+00			
Tc-99	8.71E-05	3.36E-04			
Sb-125					
I-129	4.13E-10	1.59E-09			
Cs-137	5.10E+01	1.97E+02			
Ba-137m	4.83E+01	1.86E+02			
Pm-147					
Eu-154					
U-233					
U-234					
U-235	1.01E-07	3.88E-07			
U-238	9.20E-06	3.55E-05			
Np-237					
Pu-238	3.78E-02	1.46E-01			
Pu-239	5.40E-03	2.08E-02			
Pu-240	1.21E-03	4.65E-03			
Pu-241	1.57E-01	6.03E-01			
Pu-242	2.48E-06	9.56E-06			
Am-241	1.51E-02	5.83E-02			
Am-242m					
Cm-245	1.44E-13	5.55E-13			
Total	1.00E+02				