

Annual Groundwater Detection Monitoring Report for the Idaho CERCLA Disposal Facility (2008)

July 2009

Annual Groundwater Detection Monitoring Report for the Idaho CERCLA Disposal Facility (2008)

July 2009

**Prepared for the
U.S. Department of Energy
DOE Idaho Operations Office**

ABSTRACT

This report presents the data collected for groundwater detection monitoring at the Idaho Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Disposal Facility (ICDF) during calendar year 2008.

The detection-monitoring program developed for the ICDF groundwater-monitoring wells is applicable to six wells completed in the uppermost portion of the Snake River Plain Aquifer – five wells downgradient of the ICDF and one well upgradient. The ICDF detection-monitoring program was established to meet the substantive requirements of Title 40 Code of Federal Regulations (CFR) Parts 264.97 and 264.98, which are applicable or relevant and appropriate requirements under CERCLA.

Semiannual groundwater samples were collected and analyzed for indicator parameters in March and September. The indicator parameters focus on constituents that are found in higher concentrations in ICDF leachate than in groundwater (bicarbonate alkalinity, sulfate, U-233, U-234, and U-238).

The only detection monitoring limits that were exceeded were for bicarbonate alkalinity. Bicarbonate alkalinity is naturally occurring in groundwater. Bicarbonate alkalinity found in ICDF detection monitoring wells is not a result of waste migration from the ICDF landfill or the evaporation pond. The U.S. Department of Energy will continue with detection monitoring for the ICDF, which is semiannual sampling for indicator parameters.

CONTENTS

ABSTRACT.....	iii
ACRONYMS.....	vii
1. INTRODUCTION.....	1
1.1 Regulatory Background.....	1
1.2 Site Background.....	1
2. SNAKE RIVER PLAIN AQUIFER DETECTION MONITORING PROGRAM.....	4
2.1 Well Modifications and Sampling History.....	5
2.2 Water-Level Measurements.....	5
2.3 Field Parameters.....	7
3. EVALUATION OF MONITORING DATA.....	7
3.1 Quality Assurance/Quality Control.....	7
3.2 Treatment of Duplicate Results.....	8
3.3 Uranium Isotopes.....	8
3.4 Bicarbonate and Alkalinity.....	8
4. CONCLUSIONS.....	11
5. REFERENCES.....	11
Appendix A—Hydrographs of ICDF Perched Water Wells for 2008.....	A-1
Appendix B—Field Parameter Measurements from 2008 Sampling of ICDF Aquifer Monitoring Wells.....	B-1
Appendix C—Analytical Results from 2008 Sampling of ICDF Aquifer Monitoring Wells.....	C-1

FIGURES

1.	Location of the ICDF Complex.....	2
2.	ICDF well locations and water levels, September 2008.....	3

TABLES

1.	List of analytes for indicator sampling events.....	4
2.	Groundwater levels measured in March and September 2008.....	5
3.	Perched water levels measured in 2008.....	6
4.	Detection monitoring limit and sample analysis results for U-233 and U-234 (pCi/L).....	9
5.	Detection monitoring limit and sample analysis results for U-238 (pCi/L).....	9
6.	Comparison of maximum sample results and detection monitoring limits for radionuclides.....	9
7.	Detection monitoring limits and sample analysis results for bicarbonate alkalinity (mg/L as CaCO ₃).....	10
8.	Detection monitoring limits and sample analysis results for sulfate (mg/L).....	10
9.	Comparison of maximum sample results and detection monitoring limits for bicarbonate alkalinity and sulfate.....	10

ACRONYMS

amsl	above mean sea level
bgs	below ground surface
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CFR	Code of Federal Regulations
DML	detection monitoring limit
DOE-ID	Department of Energy Idaho Operations Office
ICDF	Idaho CERCLA Disposal Facility
INL	Idaho National Laboratory
INTEC	Idaho Nuclear Technology and Engineering Center
MDA	minimum detectable activity
OU	operable unit
ROD	Record of Decision
SRPA	Snake River Plain Aquifer
WAG	Waste Area Group

Annual Groundwater Detection Monitoring Report for the Idaho CERCLA Disposal Facility (2008)

1. INTRODUCTION

This report summarizes the groundwater monitoring results for 2008 at the Idaho Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) Disposal Facility (ICDF) near the Idaho Nuclear Technology and Engineering Center (INTEC) located at the Idaho National Laboratory (INL) Site.


1.1 Regulatory Background

The U.S. Department of Energy Idaho Operations Office (DOE-ID) authorized a remedial action for the INTEC in accordance with the Waste Area Group (WAG) 3, Operable Unit (OU) 3-13 Record of Decision (ROD) (DOE-ID 1999). The OU 3-13 ROD requires the removal and on-Site disposal of some of the CERCLA remediation wastes generated within the boundaries of the INL Site.

1.2 Site Background

The ICDF is an on-Site, engineered facility, located outside the southwest boundary of INTEC (Figure 1). The major components of the ICDF Complex include the following: landfill (originally consisting of two disposal cells); evaporation pond (consisting of two cells); administration trailer; scale; decontamination building with treatment area (not in use); contaminated equipment pad (not in use); and staging and storage areas. The ICDF groundwater-monitoring network consists of five Snake River Plain Aquifer wells downgradient of the ICDF and one upgradient well, USGS-123 (Figure 2). These wells meet the substantive requirements of Title 40 Code of Federal Regulations (CFR) Parts 264.97 and 264.98 that were designated as applicable or relevant and appropriate requirements under CERCLA in the OU 3-13 ROD. The first waste was placed in the ICDF landfill on September 16, 2003.

The *ICDF Complex Groundwater Monitoring Plan* (DOE-ID 2007) details the groundwater monitoring requirements associated with the ICDF, including monitoring wells, sample frequency, required analytes, laboratory analysis, fieldwork, and quality control. The *INEEL CERCLA Disposal Facility Groundwater Detection Monitoring Program: Data Analysis Plan* (DOE-ID 2003) (referred to as the *Data Analysis Plan*) details the approach used to evaluate the groundwater data collected in support of the ICDF detection-monitoring program.



Date Drawn: 5/4/2009
 Path: x:/projects/cpp/icdf_maps
 File Name: INTEC_Location_Map-ap_v7.mxd

Figure 1. Location of the ICDF Complex.




Figure 2. ICDF well locations and water levels, September 2008.

2. SNAKE RIVER PLAIN AQUIFER DETECTION MONITORING PROGRAM

Detection monitoring is conducted at the ICDF to comply with the OU 3-13 ROD (DOE-ID 1999) requirements to meet the substantive portions that are applicable or relevant and appropriate in 40 CFR 264.98. Detection monitoring will continue unless there is statistically significant evidence of a release as defined in 40 CFR 264.98(f)(1). The detection-monitoring program developed for the ICDF groundwater monitoring wells is currently applicable to those six wells completed in the uppermost portion of the Snake River Plain Aquifer (SRPA). Detection monitoring does not include the investigation phase that will be conducted if statistically significant evidence is found that a release has occurred from the ICDF.

The ICDF detection-monitoring program has established the statistical methods that determine whether there is statistically significant evidence of contamination for any monitoring parameter at the ICDF SRPA wells. As stated above, these statistical methods are detailed in the *Data Analysis Plan*. Of the acceptable methods listed in 40 CFR 264.97(h), the ICDF detection-monitoring program will use either nonparametric prediction limits as allowed in 40 CFR 264.97(h)(3) or control charts as allowed in 40 CFR 264.97(h)(4) to evaluate the groundwater monitoring data for statistically significant evidence of contamination. Either method produces detection monitoring limits (DMLs); if a sample result exceeds the DML, there is statistically significant evidence of contamination.

As documented in the *ICDF Complex Groundwater Monitoring Plan* (DOE-ID 2007), the six SRPA wells are sampled semiannually for indicator parameters (Table 1).

Table 1. List of analytes for indicator sampling events.

<u>Analytes</u>
U-233, U-234, and U-238
Bicarbonate alkalinity and sulfate

As agreed in the *Data Analysis Plan* and as part of the ongoing detection monitoring, the DMLs and methods selected for a given parameter/well will be evaluated every 2 years as recommended by the American Society of Testing and Materials (ASTM) D6312 to incorporate additional data obtained after ICDF startup. This evaluation will be performed after validation of the 2009 sampling results from two rounds of indicator sampling.

The Site-wide false-positive rate is the probability, given there is an exceedance of a DML at any well for any of the four indicator analytes, that the exceedance does not represent true contamination above background levels. The current individual false-positive rate is approximately 17% for bicarbonate alkalinity and sulfate and around 1% for U-233, U-234, and U-238. The major reason why the Site-wide false positive rate is higher for bicarbonate alkalinity and sulfate is because the DMLs are well-specific; therefore, they are based on fewer data points. When DMLs are recalculated, if results can be pooled across wells, then this rate will dramatically decrease. The false-positive rates for U-233/U-234 and U-238 are lower because they have combined control chart DMLs. The rate should continue to decrease as more data are collected.

2.1 Well Modifications and Sampling History

There were no well modifications during 2008. Sampling and well history can be found in the *Analysis of Baseline Data from ICDF Detection Monitoring Wells* (INEEL 2006).

2.2 Water-Level Measurements

Water levels were measured in the six SRPA monitoring wells in March and September 2008 (Table 2). Water-level elevations ranged from 4,446 to 4,448 ft above mean sea level (amsl). The water levels are higher in March than in September.

Table 2. Groundwater levels measured in March and September 2008.

Well Name	March 2008 Water Level in ft amsl (Depth to water in ft bgs)	September 2008 Water Level in ft amsl (Depth to water in ft bgs)
ICPP-1782	4446.96 (475.83)	4445.71 (477.08)
ICPP-1783	4446.98 (474.53)	4445.72 (475.79)
ICPP-1800	4446.86 (473.80)	4445.67 (474.99)
ICPP-1829	4446.76 (473.13)	4445.54 (474.35)
ICPP-1831	4447.93 (475.74)	4446.13 (477.54)
USGS-123	4447.19 (471.99)	4445.80 (473.38)

Amsl above mean sea level
bgs below ground level

Perched water monitoring wells are installed around the ICDF as shown in Figure 2. Perched water wells were checked for the presence of perched water prior to each sampling event. Where perched water was present, water levels were measured, although it is difficult to get an accurate estimate of the height of the water column in the wells due to the small amount of water in the wells and the presence of mud. The results are shown in Table 3. The only well that consistently had water in it in 2008 was ICPP-1804M, which had between 0.09 and 0.3 ft of water in it (see hydrograph in Appendix A). There are transducers in the westernmost wells (ICPP-1802U, ICPP-1802L, ICPP-1781U, ICPP-1781M, and ICPP-1781L). The transducers recorded no water in the three completions in ICPP-1781 (U, M, or L) or in ICPP-1802U, although presence of water was occasionally detected manually (e.g., 0.04 ft of water in ICPP-1802U in February).

Appendix A contains a hydrograph for perched water well ICPP-1802L. The fluctuations in water levels in ICPP-1802L are attributed to barometric pressure. The apparent shift in water levels in August 2008 is due to the barometric pressure sensor. The battery was failing, and a new barometric pressure sensor began recording in August. As was shown in the biennial monitoring report (DOE-ID 2008a), the well exhibits close to 100% barometric efficiency with an approximate 1-day lag. The well was checked manually three times in 2008. In February, the well only contained mud. In June, approximately 1.65 ft of water was found in the well above the mud. In August, approximately 1.49 ft of water was found above the mud. ICPP-1781U and ICPP-1807L had just enough moisture to record on the electronic water-level indicator in February, but insufficient water to measure any height for a water column (i.e., electronic water-level indicator sounded on the bottom of the well).

Table 3. Perched water levels measured in 2008.

Well Name	Measurement Dates (Manual Water Levels)	Depth to Water in ft bgs (ft of water)
ICPP-1781 Lower	2/19/2008	Dry
	6/5/2008	Dry
	8/20/2008	Dry
ICPP-1781 Middle	2/19/2008	Dry
	6/5/2008	Dry
	8/20/2008	Dry
ICPP-1781 Upper	2/19/2008	175.26 (Dry by transducer)
	6/5/2008	Dry
	8/20/2008	Dry
ICPP-1801 Middle	2/19/2008	Dry
	8/20/2008	Dry
ICPP-1801 Upper	2/19/2008	Dry
	8/20/2008	Dry
ICPP-1802 Lower	2/19/2008	Dry
	6/5/2008	378.22 (1.65)
	8/20/2008	378.32 (1.49)
ICPP-1802 Upper	2/19/2008	206.45 (0.04)
	6/5/2008	Dry
	8/20/2008	Dry
ICPP-1803 Lower	2/19/2008	Dry
	8/20/2008	Dry
ICPP-1803 Middle	2/19/2008	Dry
	8/20/2008	Dry
ICPP-1803 Upper	2/19/2008	108.45 (0.12 ft)
	8/20/2008	Dry
ICPP-1804 Lower	2/19/2008	377.48 (0.40)
	6/5/2008	377.22
	8/20/2008	Dry

Table 3. (continued).

Well Name	Measurement Dates (Manual Water Levels)	Depth to Water in ft bgs (ft of water)
ICPP-1804 Middle	2/19/2008	265.73 (0.30)
	6/5/2008	265.78
	8/20/2008	265.78 (0.09)
ICPP-1807 Lower	2/19/2008	384.6 (trace)
	8/20/2008	Dry
ICPP-1807 Middle	2/19/2008	Dry
	8/20/2008	Dry
ICPP-1807 Upper	2/19/2008	Dry
	8/20/2008	Dry
PW-1	2/19/2008	Not measured due to ice obstruction
	8/20/2008	Dry
PW-6	2/19/2008	Dry
	8/20/2008	Dry

bgs below ground surface

2.3 Field Parameters

Field parameters (pH, specific conductivity, and temperature) are measured immediately prior to sampling each well. These parameters are measured by the field sampling team as required in the *ICDF Complex Groundwater Monitoring Plan* (DOE-ID 2007) and are recorded in the field-sampling logbook. Field parameters are measured before taking the water sample and are used to determine when a sample can be collected. The field parameters are included in Appendix B.

3. EVALUATION OF MONITORING DATA

Data from routine detection monitoring were compared to DMLs for each well and each of the required constituents (Table 1). As specified in the *Data Analysis Plan*, before using any monitoring data, they were evaluated with respect to any impacts from validation (i.e., rejected results), nondetected results, and duplicate sample results per sampling round. All sampling results are tabulated in Appendix C.

3.1 Quality Assurance/Quality Control

All rounds of sampling and analysis followed established procedures and analytical methodologies. Two rounds of samples for indicator parameters were collected in March and September 2008. The completeness goal for the project of 100% was met. All of the data are acceptable.

Laboratories on the CWI Qualified Suppliers List performed all analyses. The *ICDF Complex Groundwater Monitoring Plan* (DOE-ID 2007) required one duplicate and field blank for every 20 samples collected or, at a minimum, 5% of the total number of samples collected. The actual percentage of duplicates and blanks was higher, because the number of wells sampled during each round was much less than 20.

The radioanalytical results were U-flagged by the data validator for reported data less than minimum detectable activity (MDA) (i.e., no detectable activity) or J-flagged if radioactivity was detected, but due to analytical and/or laboratory quality control issues, the reported quantity was considered an estimate. As shown in Appendix C (Table C-1), one field blank was flagged U and the other was flagged J by the data validator. For U-238, both field blanks were flagged U by the data validator.

For bicarbonate alkalinity and sulfate analyses, a J flag from the laboratory means that the material was analyzed for, was detected at or above the applicable detection limit, and the associated value is an estimate that may be inaccurate or imprecise. A U flag from the laboratory means that the material was not detected. The two field blanks for sulfate were flagged U by the laboratory (not detected), and one of the field blanks for bicarbonate alkalinity was flagged J by the laboratory and flagged U by the data validator to denote the data are nondetect at the reported value due to a positive blank detection as shown in Appendix C (Table C-2).

3.2 Treatment of Duplicate Results

When duplicate results existed, the maximum detected result was used for comparison to DMLs. All duplicate results are presented in Appendix C.

3.3 Uranium Isotopes

For U-233 and U-234, none of the data from the monitoring wells was flagged, as shown in Table 4. Four of the monitoring well results for U-238 were flagged J during the September sampling round by the data validator, as shown in Table 5.

The maximum result and DMLs for the U isotopes are presented in Table 6 and all monitoring results are presented in Appendix C (Table C-1). All results for U isotopes were below the DMLs.

3.4 Bicarbonate and Alkalinity

For bicarbonate alkalinity and sulfate analyses, none of the sample results from the monitoring wells were flagged, as shown in Tables 7 and 8. All monitoring results are presented in Appendix C (Table C-2). The maximum results and DMLs are presented in Table 9. Bicarbonate exceeded the DML in three wells (ICPP-1783, ICPP-1800, and ICPP-1831 [duplicate exceeded DML, sample did not]). Bicarbonate alkalinity is not attributable to ICDF operations because the concentrations measured in the detection monitoring wells are within the range of naturally occurring bicarbonate alkalinity levels found in the SRPA upgradient of the ICDF. During the 2007 WAG 3 sampling, bicarbonate alkalinity ranged from 139 to 226 mg/L in INTEC wells located upgradient of the ICDF (DOE-ID 2008b). In addition, the leak detection systems at the ICDF do not indicate that the landfill or evaporation ponds have leaked.

Table 4. Detection monitoring limit and sample analysis results for U-233 and U-234 (pCi/L). (Field duplicate results in parentheses.)

Wells		ICPP-1782	ICPP-1783	ICPP-1800	ICPP-1829	ICPP-1831	USGS-123
Detection Monitoring Limit		2.66					
Sample Analysis Results	3/4/08	1.85 ± 0.26 (1.95 ± 0.27)	1.7 ± 0.2	1.32 ± 0.20	1.34 ± 0.20	1.89 ± 0.25	1.34 ± 0.21
	9/8/08 and 9/9/08	1.8 ± 0.4	1.77 ± 0.43	1.63 ± 0.39	1.72 ± 0.43	2.11 ± 0.46 (1.89 ± 0.43)	1.5 ± 0.4

Table 5. Detection monitoring limit and sample analysis results for U-238 (pCi/L). (Field duplicate results in parentheses.)

Wells		ICPP-1782	ICPP-1783	ICPP-1800	ICPP-1829	ICPP-1831	USGS-123
Detection Monitoring Limit		1.41					
Sample Analysis Results	3/4/08	0.534 ± 0.128 0.906 ± 0.172	0.846 ± 0.155	0.904 ± 0.158	0.705 ± 0.141	0.77 ± 0.15	0.873 ± 0.16
	9/8/08 and 9/9/08	0.812 ± 0.277 J	0.724 ± 0.263 J	0.897 ± 0.278	0.701 ± 0.264 J	0.918 ± 0.29 (0.915 ± 0.29)	0.629 ± 0.239 J

Table 6. Comparison of maximum sample results and detection monitoring limits for radionuclides.

Radionuclide	Number of Available Monitoring Results	Number of Nondetected/ Detected Results	Maximum Detected Result / DML Over All Wells (pCi/L)	Maximum Detected Result / Well-Specific DML ^a					
				ICPP-1782 (pCi/L)	ICPP-1783 (pCi/L)	ICPP-1800 (pCi/L)	ICPP-1829 (pCi/L)	ICPP-1831 (pCi/L)	USGS-123 (pCi/L)
U-233 and 234	12	0/12	2.11 / 2.66	—	—	—	—	—	—
U-238	12	0/12	0.918 / 1.410	—	—	—	—	—	—

a. No result or limit shown in a given column indicates that the detection monitoring limit for the parameter was not determined using that method (over all wells or well-specific).

Table 7. Detection monitoring limits and sample analysis results for bicarbonate alkalinity (mg/L as CaCO₃). (Field duplicate results in parentheses.)

Wells		ICPP-1782	ICPP-1783	ICPP-1800	ICPP-1829	ICPP-1831	USGS-123
Detection Monitoring Limits		152	146	138	139	153	145
Sample Analysis Results	3/4/08	152 (150)	148	141	132	154	130
	9/8/08 and 9/9/08	152	151	139	132	153 (155)	133

Table 8. Detection monitoring limits and sample analysis results for sulfate (mg/L). (Field duplicate results in parentheses.)

Wells		ICPP-1782	ICPP-1783	ICPP-1800	ICPP-1829	ICPP-1831	USGS-123
Detection Monitoring Limits		27.6	28.5	29.4	32.5	26	29.3
Sample Analysis Results	3/4/08	22.4 (22.5)	24.2	25.6	27.4	22.2	20
	9/8/08 and 9/9/08	24.4	26.3	27.7	29.2	24.5 (24.7)	22

Table 9. Comparison of maximum sample results and detection monitoring limits for bicarbonate alkalinity and sulfate. Bold entries indicate maximum 2008 result exceeds DML.

Radionuclide	Number of Available Monitoring Results	Number of Nondetected/ Detected Results	Maximum Detected Result / Well-Specific DML					USGS-123 (mg/L)
			ICPP-1782 (mg/L)	ICPP-1783 (mg/L)	ICPP-1800 (mg/L)	ICPP-1829 (mg/L)	ICPP-1831 (mg/L)	
Bicarbonate		0/12	152 / 152	151 / 146	141 / 138	132 / 139	155 / 153	133 / 145
Sulfate		0/12	24.4 / 27.6	26.3 / 28.5	27.7 / 29.4	29.2 / 32.5	24.7 / 26	22 / 29.3

4. CONCLUSIONS

Semiannual sampling of the ICDF detection monitoring network for indicator parameters during 2008 resulted in bicarbonate alkalinity exceeding the DMLs in three downgradient wells. The sampling results for all other indicator parameters were below the DMLs. Bicarbonate alkalinity is not attributable to ICDF operations because the concentrations measured in the detection monitoring wells are within the range of naturally occurring bicarbonate alkalinity levels found in the Snake River Plain Aquifer upgradient of the ICDF. In addition, the leak detection systems at the ICDF do not indicate that the landfill or evaporation ponds have leaked. This report meets the substantive requirements of 40 CFR 264.98(g) to demonstrate that the contamination is not due to waste migration from the ICDF landfill or evaporation pond. DOE will continue with the detection monitoring for the ICDF, which is semiannual sampling for indicator parameters.

5. REFERENCES

- 40 CFR 264.97, 2000, "General Ground-Water Monitoring Requirements," *Code of Federal Regulations*, Office of the Federal Register, July 2000.
- 40 CFR 264.98, 2000, "Detection Monitoring Program," *Code of Federal Regulations*, Office of the
- DOE-ID, 1999, *Final Record of Decision Idaho Nuclear Technology and Engineering Center, Operable Unit 3-13*, DOE/ID-10660, Rev. 0, U.S. Department of Energy Idaho Operations Office, October 1999.
- DOE-ID, 2003, *INEEL CERCLA Disposal Facility Groundwater Detection Monitoring Program: Data Analysis Plan*, DOE/ID-10998, Rev. 0, U.S. Department of Energy Idaho Operations Office, February 2003.
- DOE-ID, 2007, *ICDF Complex Groundwater Monitoring Plan*, DOE/ID-10955, Rev. 5, U.S. Department of Energy Idaho Operations Office, August 2007.
- DOE-ID, 2008a, *ICDF Detection Monitoring Biennial Report (2006-2007)*, DOE/ID-11373, Rev. 0, U.S. Department of Energy Idaho Operations Office, July 2008.
- DOE-ID, 2008b, *INTEC Groundwater Monitoring Report (2007)*, DOE/ID-11356, Rev. 1, U.S. Department of Energy Idaho Operations Office, June 2008.
- INEEL, 2006, *Analysis of Baseline Data from ICDF Detection Monitoring Wells*, INEEL/EXT-03-00251, Rev. 1, Idaho Cleanup Project, June 2006.


Appendix A

Hydrographs of ICDF Perched Water Wells for 2008

Appendix A

Hydrographs of ICDP Perched Water Monitoring Wells for 2008

ICPP-1802L



A-3

Figure A-1. Hydrograph for ICPP-1802L.

Water Levels in ICPP-1804M

A-4




Figure A-2. Hydrograph for ICPP-1804M.

Appendix B

Field Parameter Measurements from 2008 Sampling of ICDF Aquifer Monitoring Wells

Appendix B

Field Parameter Measurements from 2008 Sampling of ICDF Aquifer Monitoring Wells

Table B-1. Field parameter measurements.

Location	Parameter	Date Collected	Result	Units
ICPP-1782	pH	3/4/2008	7.68	
ICPP-1782	pH	9/8/2008	7.64	
ICPP-1783	pH	3/4/2008	7.71	
ICPP-1783	pH	9/8/2008	7.80	
ICPP-1800	pH	3/4/2008	7.62	
ICPP-1800	pH	9/8/2008	7.72	
ICPP-1829	pH	3/4/2008	7.63	
ICPP-1829	pH	9/8/2008	7.90	
ICPP-1831	pH	3/4/2008	7.65	
ICPP-1831	pH	9/9/2008	7.88	
USGS-123	pH	3/4/2008	7.97	
USGS-123	pH	9/8/2008	7.97	
ICPP-1782	Specific Conductivity	3/4/2008	0.441	mmhos/cm
ICPP-1782	Specific Conductivity	9/8/2008	0.425	mmhos/cm
ICPP-1783	Specific Conductivity	3/4/2008	0.508	mmhos/cm
ICPP-1783	Specific Conductivity	9/8/2008	0.484	mmhos/cm
ICPP-1800	Specific Conductivity	3/4/2008	0.554	mmhos/cm
ICPP-1800	Specific Conductivity	9/8/2008	0.537	mmhos/cm
ICPP-1829	Specific Conductivity	3/4/2008	0.678	mmhos/cm
ICPP-1829	Specific Conductivity	9/8/2008	0.627	mmhos/cm
ICPP-1831	Specific Conductivity	3/4/2008	0.439	mmhos/cm
ICPP-1831	Specific Conductivity	9/9/2008	0.436	mmhos/cm
USGS-123	Specific Conductivity	3/4/2008	0.375	mmhos/cm
USGS-123	Specific Conductivity	9/8/2008	0.357	mmhos/cm
ICPP-1782	Temperature	3/4/2008	12.46	°C
ICPP-1782	Temperature	9/8/2008	13.13	°C
ICPP-1783	Temperature	3/4/2008	12.72	°C
ICPP-1783	Temperature	9/8/2008	13.81	°C
ICPP-1800	Temperature	3/4/2008	12.25	°C
ICPP-1800	Temperature	9/8/2008	14.23	°C
ICPP-1829	Temperature	3/4/2008	9.02	°C
ICPP-1829	Temperature	9/8/2008	13.74	°C
ICPP-1831	Temperature	3/4/2008	12.07	°C
ICPP-1831	Temperature	9/9/2008	13.09	°C
USGS-123	Temperature	3/4/2008	12.32	°C
USGS-123	Temperature	9/8/2008	13.42	°C

Appendix C

Analytical Results from 2008 Sampling of ICDF Aquifer Monitoring Wells

Appendix C

Analytical Results from 2008 Sampling of ICDF Aquifer Monitoring Wells

Table C-1. Analytical results for radionuclides.

SDG Number	Sample Number	Date Collected	Location	Result Type	Standard Constituent	Concentration	Combined Standard Uncertainty	Lab Qualifier	Validation Qualifier	Units	Detection Limit	L&V Report Number
AWB12501R9	AWB13101R9	3/4/08	ICDF	Field Blank	Uranium-233/234	0.182	0.0701		J	PCI/L	0.0782	DNT-138-08
AWB12501R9	AWB12602R9	3/4/08	ICPP-1782	Field Duplicate	Uranium-233/234	1.95	0.273			PCI/L	0.085	DNT-138-08
AWB12501R9	AWB12601R9	3/4/08	ICPP-1782		Uranium-233/234	1.85	0.26			PCI/L	0.131	DNT-138-08
AWB12501R9	AWB12701R9	3/4/08	ICPP-1783		Uranium-233/234	1.7	0.233			PCI/L	0.115	DNT-138-08
AWB12501R9	AWB12801R9	3/4/08	ICPP-1800		Uranium-233/234	1.32	0.198			PCI/L	0.112	DNT-138-08
AWB12501R9	AWB12901R9	3/4/08	ICPP-1829		Uranium-233/234	1.34	0.204			PCI/L	0.118	DNT-138-08
AWB12501R9	AWB12501R9	3/4/08	ICPP-1831		Uranium-233/234	1.89	0.252			PCI/L	0.0745	DNT-138-08
AWB12501R9	AWB13001R9	3/4/08	USGS-123		Uranium-233/234	1.34	0.208			PCI/L	0.195	DNT-138-08
AWB14101R9	AWB14201R9	9/8/08	ICPP-1782		Uranium-233/234	1.8	0.428			PCI/L	0.128	BAM-034-08
AWB14101R9	AWB14301R9	9/8/08	ICPP-1783		Uranium-233/234	1.77	0.43			PCI/L	0.14	BAM-034-08
AWB14101R9	AWB14401R9	9/8/08	ICPP-1800		Uranium-233/234	1.63	0.387			PCI/L	0.108	BAM-034-08
AWB14101R9	AWB14501R9	9/8/08	ICPP-1829		Uranium-233/234	1.72	0.428			PCI/L	0.1	BAM-034-08

Table C-1. (continued).

SDG Number	Sample Number	Date Collected	Location	Result Type	Standard Constituent	Concentration	Combined Standard Uncertainty	Lab Qualifier	Validation Qualifier	Units	Detection Limit	L&V Report Number
AWB14101R9	AWB14701R9	9/8/08	INEEL	Field Blank	Uranium-233/234	0.0527	0.0912		U	PCI/L	0.158	BAM-034-08
AWB14101R9	AWB14601R9	9/8/08	USGS-123		Uranium-233/234	1.5	0.38			PCI/L	0.104	BAM-034-08
AWB14101R9	AWB14101R9	9/9/08	ICPP-1831		Uranium-233/234	2.11	0.461			PCI/L	0.115	BAM-034-08
AWB14101R9	AWB14102R9	9/9/08	ICPP-1831	Field Duplicate	Uranium-233/234	1.89	0.431			PCI/L	0.114	BAM-034-08
AWB12501R9	AWB13101R9	3/4/08	ICDF	Field Blank	Uranium-238	0.0198	0.0268		U	PCI/L	0.125	DNT-138-08
AWB12501R9	AWB12602R9	3/4/08	ICPP-1782	Field Duplicate	Uranium-238	0.906	0.172			PCI/L	0.085	DNT-138-08
AWB12501R9	AWB12601R9	3/4/08	ICPP-1782		Uranium-238	0.534	0.128			PCI/L	0.151	DNT-138-08
AWB12501R9	AWB12701R9	3/4/08	ICPP-1783		Uranium-238	0.846	0.155			PCI/L	0.147	DNT-138-08
AWB12501R9	AWB12801R9	3/4/08	ICPP-1800		Uranium-238	0.904	0.158			PCI/L	0.112	DNT-138-08
AWB12501R9	AWB12901R9	3/4/08	ICPP-1829		Uranium-238	0.705	0.141			PCI/L	0.118	DNT-138-08
AWB12501R9	AWB12501R9	3/4/08	ICPP-1831		Uranium-238	0.77	0.148			PCI/L	0.0745	DNT-138-08
AWB12501R9	AWB13001R9	3/4/08	USGS-123		Uranium-238	0.873	0.16			PCI/L	0.12	DNT-138-08
AWB14101R9	AWB14201R9	9/8/08	ICPP-1782		Uranium-238	0.812	0.277		J	PCI/L	0.0939	BAM-034-08
AWB14101R9	AWB14301R9	9/8/08	ICPP-1783		Uranium-238	0.724	0.263		J	PCI/L	0.0612	BAM-034-08
AWB14101R9	AWB14401R9	9/8/08	ICPP-1800		Uranium-238	0.897	0.278			PCI/L	0.0539	BAM-034-08
AWB14101R9	AWB14501R9	9/8/08	ICPP-1829		Uranium-238	0.701	0.264		J	PCI/L	0.1	BAM-034-08

Table C-1. (continued).

SDG Number	Sample Number	Date Collected	Location	Result Type	Standard Constituent	Concentration	Combined Standard Uncertainty	Lab Qualifier	Validation Qualifier	Units	Detection Limit	L&V Report Number
AWB14101R9	AWB14701R9	9/8/08	INEEL	Field Blank	Uranium-238	0.0622	0.09		U	PCI/L	0.138	BAM-034-08
AWB14101R9	AWB14601R9	9/8/08	USGS-123		Uranium-238	0.629	0.239		J	PCI/L	0.104	BAM-034-08
AWB14101R9	AWB14101R9	9/9/08	ICPP-1831		Uranium-238	0.918	0.29			PCI/L	0.0578	BAM-034-08
AWB14101R9	AWB14102R9	9/9/08	ICPP-1831	Field Duplicate	Uranium-238	0.915	0.29			PCI/L	0.114	BAM-034-08
J Flag by the validator means radioactivity was detected but due to analytical and/or laboratory quality control issues the reported quantity was considered an estimate. U Flag by the validator means reported data less than minimum detectable activity (MDA) (i.e., no detectable activity).												

Table C-2. Analytical results for bicarbonate alkalinity and sulfate.

SDG Number	Sample Number	Date Collected	Result Type	Location	Constituent	Concentration	Lab Qualifier	Validation Qualifier	Units	L&V Report Number
AWB12501B9	AWB12901B9	3/4/08		ICPP-1829	Bicarbonate	132			MG/L	DNT-146-08
AWB12501B9	AWB13101B9	3/4/08	Field Blank	ICDF	Bicarbonate	1.04	J	U	MG/L	DNT-146-08
AWB12501B9	AWB12801B9	3/4/08		ICPP-1800	Bicarbonate	141			MG/L	DNT-146-08
AWB12501B9	AWB12701B9	3/4/08		ICPP-1783	Bicarbonate	148			MG/L	DNT-146-08
AWB12501B9	AWB12602B9	3/4/08	Field Duplicate	ICPP-1782	Bicarbonate	150			MG/L	DNT-146-08
AWB12501B9	AWB12601B9	3/4/08		ICPP-1782	Bicarbonate	152			MG/L	DNT-146-08
AWB12501B9	AWB12501B9	3/4/08		ICPP-1831	Bicarbonate	154			MG/L	DNT-146-08
AWB12501B9	AWB13001B9	3/4/08		USGS-123	Bicarbonate	130			MG/L	DNT-146-08
AWB14101B9	AWB14601B9	9/8/08		USGS-123	Bicarbonate	133			MG/L	DNT-391-08
AWB14101B9	AWB14501B9	9/8/08		ICPP-1829	Bicarbonate	132			MG/L	DNT-391-08
AWB14101B9	AWB14401B9	9/8/08		ICPP-1800	Bicarbonate	139			MG/L	DNT-391-08
AWB14101B9	AWB14301B9	9/8/08		ICPP-1783	Bicarbonate	151			MG/L	DNT-391-08
AWB14101B9	AWB14201B9	9/8/08		ICPP-1782	Bicarbonate	152			MG/L	DNT-391-08
AWB14101B9	AWB14701B9	9/9/08	Field Blank	INEEL	Bicarbonate	20			MG/L	DNT-391-08
AWB14101B9	AWB14102B9	9/9/08	Field Duplicate	ICPP-1831	Bicarbonate	155			MG/L	DNT-391-08
AWB14101B9	AWB14101B9	9/9/08		ICPP-1831	Bicarbonate	153			MG/L	DNT-391-08
AWB12501B9	AWB13101S2	3/4/08	Field Blank	ICDF	Sulfate	0	U		MG/L	DNT-146-08
AWB12501B9	AWB12602S2	3/4/08	Field Duplicate	ICPP-1782	Sulfate	22.5			MG/L	DNT-146-08
AWB12501B9	AWB12501S2	3/4/08		ICPP-1782	Sulfate	22.2			MG/L	DNT-146-08
AWB12501B9	AWB12601S2	3/4/08		ICPP-1782	Sulfate	22.4			MG/L	DNT-146-08
AWB12501B9	AWB12701S2	3/4/08		ICPP-1783	Sulfate	24.2			MG/L	DNT-146-08
AWB12501B9	AWB12801S2	3/4/08		ICPP-1800	Sulfate	25.6			MG/L	DNT-146-08
AWB12501B9	AWB12901S2	3/4/08		ICPP-1829	Sulfate	27.4			MG/L	DNT-146-08

Table C-2. (continued).

SDG Number	Sample Number	Date Collected	Result Type	Location	Constituent	Concentration	Lab Qualifier	Validation Qualifier	Units	L&V Report Number
AWB12501B9	AWB13001S2	3/4/08		USGS-123	Sulfate	20			MG/L	DNT-146-08
AWB14101S2	AWB14601S2	9/8/08		USGS-123	Sulfate	22			MG/L	DNT-392-08
AWB14101S2	AWB14501S2	9/8/08		ICPP-1829	Sulfate	29.2			MG/L	DNT-392-08
AWB14101S2	AWB14401S2	9/8/08		ICPP-1800	Sulfate	27.7			MG/L	DNT-392-08
AWB14101S2	AWB14301S2	9/8/08		ICPP-1783	Sulfate	26.3			MG/L	DNT-392-08
AWB14101S2	AWB14201S2	9/8/08		ICPP-1782	Sulfate	24.4			MG/L	DNT-392-08
AWB14101S2	AWB14701S2	9/9/08	Field Blank	INEEL	Sulfate	0.5	U		MG/L	DNT-392-08
AWB14101S2	AWB14102S2	9/9/08	Field Duplicate	ICPP-1831	Sulfate	24.7			MG/L	DNT-392-08
AWB14101S2	AWB14101S2	9/9/08		ICPP-1831	Sulfate	24.5			MG/L	DNT-392-08
<p>J Flag from the laboratory means that the material was analyzed for, was detected at or above the applicable detection limit, and the associated value is an estimate that may be inaccurate or imprecise.</p> <p>U Flag from the laboratory means that the material was not detected.</p>										