

PAPER • OPEN ACCESS

## Syngas formation by dry and steam reforming of methane using microwave plasma technology

To cite this article: Nabil Majd Alawi *et al* 2019 *IOP Conf. Ser.: Mater. Sci. Eng.* **579** 012022

View the [article online](#) for updates and enhancements.



**IOP | ebooks™**

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the collection - download the first chapter of every title for free.

# Syngas formation by dry and steam reforming of methane using microwave plasma technology

Nabil Majd Alawi<sup>1,2</sup>, Gia Hung Pham<sup>1</sup>, Ahmed Barifcani<sup>1</sup>, Minh Hoang Nguyen<sup>1</sup> and Shaomin Liu<sup>1</sup>

<sup>1</sup>Department of Chemical Engineering, Curtin University, Perth, Western Australia 6845, Australia

<sup>2</sup>Petroleum Technology Department, University of Technology, Baghdad, Iraq  
Corresponding author's e-mail address: n.alawi@postgrad.curtin.edu.au

**Abstract.** The combined dry and steam reforming of methane at atmospheric pressure was experimentally studied by using microwave plasma technology. The effect of the process parameters such as total feed gas flow rate, steam concentration and input microwave power on the synthesis gas H<sub>2</sub>/CO ratio was investigated using a commercial microwave reactor system. In order to minimise the carbon formation and plasma instability, the concentration of methane and carbon dioxide in nitrogen plasma were kept at a low level in this study. The long-term test results show that at the flow rate of 0.2 L min<sup>-1</sup>, 0.4 L min<sup>-1</sup> and 1.5 L min<sup>-1</sup> for CH<sub>4</sub>, CO<sub>2</sub> and N<sub>2</sub> respectively, the carbon formation was not detectable at the input power of 700 W. This reaction condition offers an opportunity to study the effect of adding water to the feed on the syngas ratio H<sub>2</sub>/CO. The test results show that a higher CH<sub>4</sub> conversion (82.74%), H<sub>2</sub> selectivity (98.79%) and yield (81.73%) were achieved compared with those of the dry reforming at the same operating conditions. With the steam addition, the desired H<sub>2</sub>/CO ratio for the Fischer-Tropsch synthesis process can be reached.

## 1. Introduction

Nowadays, the increasing energy demand of the growing population has led to the rapid consumption of fossil fuels, inevitably releasing carbon dioxide (CO<sub>2</sub>) which is a prime contributor to global warming and climate change. For this reason, significant efforts have been devoted to developing innovative and cost-effective technologies to produce synthesis gas (syngas) from CO<sub>2</sub> [1]. Syngas, a mixture of hydrogen (H<sub>2</sub>) and carbon monoxide (CO), is a versatile intermediate to the synthesis of a variety of valuable chemical feedstock and liquid fuels such as ammonia, methanol, ethanol, acetic acid, methyl format, dimethyl ether, synthetic gasoline and diesel via Fischer-Tropsch process [2-9]. Syngas can be produced from a variety of primary feedstock such as coal, natural gas (NG) and biomass. Among them, NG is the cheapest and cleanest source [10]. Many reforming technologies can be used to produce syngas including steam reforming, dry reforming (CO<sub>2</sub> reforming) and partial oxidation [11-13]:

### Steam Reforming of Methane (SRM)



$$\Delta H = +206 \text{ k / m}$$

### Dry Reforming of Methane (DRM)





**Partial Oxidation of Methane (POM)**



SRM is the most important process for syngas production at large scale, because of its stability. The drawbacks of this highly endothermic reaction are the high energy consumption and syngas ratio  $\text{H}_2/\text{CO}$ , which is not suitable for the Fischer Tropsch synthesis process (F-T process). POM is an exothermic reaction (Reaction 3), which produces the synthesis gas at the desired syngas ratio of 2 for the F-T process. Unfortunately, during the reaction carbon is developed and covers the catalyst surface. This leads to the shortening of the catalyst life time. In recent years, DRM (Reaction 2) has become an important technique that produces synthesis gas from two main greenhouse gases: natural gas ( $\text{CH}_4$ ) and carbon dioxide ( $\text{CO}$ ) [7, 14]. The reason for this is that it has environmental, economical, technical and industrial advantages [15]. The drawback of DRM is the low syngas ratio  $\text{H}_2/\text{CO}$ , which can not be used to feed to the F-T process without  $\text{H}_2$  addition. From the above reasons, the combined SRM and DRM, abbreviated as CSDRM (Equation 4), also known as bi-reforming of methane, has recently appeared as a promising technique since it is capable of generating a suitable syngas for F-T process by using the greenhouse gases and water [16, 17].



The CSDRM can produce the synthesis gas with flexible  $\text{H}_2/\text{CO}$  ratios of 2.0 [18-20]. The  $\text{H}_2/\text{CO}$  ratio of the synthesis gas produced via the CSDRM can be controlled by changing the composition of the feed gas ( $\text{H}_2\text{O}$ ,  $\text{CO}_2$ , and  $\text{CH}_4$ ) [21, 22].

CSDRM is a complex process, because many side reactions can occur simultaneously as follows:

**Water gas shift (WGS):**




**Reverse water gas shift (RWGS):**



**Methane decomposition (Methane Cracking Reaction):**



**Disproportionation Reaction (Boudouard Reaction):**



**Carbon Gasification:**



Nowadays, plasma technology has been used widely in conversion of  $\text{CO}_2$  and  $\text{CH}_4$  to produce synthesis gas [23]. A plasma process is divided into two main methods; the first is non-thermal (or cold) plasma discharge including dielectric barrier discharge (DBD), corona discharge (CD),

atmospheric pressure glow discharge (APGD), gliding arc discharge (GAD), microwave discharge (MWD) and spark discharge [24].

The second is thermal plasma including direct current (DC), alternating current (AC) arc torch and radio frequency (RF) [25, 26].


The microwave plasma technology has a number of advantages that will make it useful in the industry at present. The main advantage of microwave technology is that the energy transfer is rapid and uniform heating by irradiation with microwave [27]. Additionally, the use of microwaves offers technical advantages such as smooth operation, electrodeless reactors and high plasma density [28, 29].

In recent days, some research results on methane reforming by carbon dioxide and water by using microwave plasma are reported in the literature [21, 22]. From these studies, it is found that the adding steam into the dry reforming of methane is effective and leads to increasing the conversion of CH<sub>4</sub>, selectivity and yield of H<sub>2</sub>. Unfortunately, some knowledge gaps about the combination effect of the steam concentration and microwave power on the process performance and product quality have been remained unknown. Therefore, the main aims of the present work will study the combination influence of the process parameters (total feed gas flow rate, steam concentration and input microwave power) on the H<sub>2</sub>/CO ratio under microwave irradiation at atmospheric pressure.

## 2. Experimental Set up

The schematic diagram of the experimental set-up is shown in Figure 1; microwave plasma system fundamentally consists of a gas cylinders, mass flow controllers, gas mixer, feed gas system, steam vapour unit, plasma reactor, microwave generator, and gas chromatographic (GC-MSD and GC-TCD) analysis system. The three feeding gases (CH<sub>4</sub>, CO<sub>2</sub>, and N<sub>2</sub>) were controlled by a mass flow controller (MFC Alicat Scientific, MCS-Series) and sent into the gas mixer. Deionised water was sent into a vaporiser, which works at the set temperature of 300°C, by using a HPLC pump (Shimadzu LC pump). These gases are joined with the steam in a final feed mixer before entering the plasma reactor. To avoid water recondensation before the reactor, the heated pipe line was used. The quartz reactor has a size of 1.68 mm wall thickness, 25.5 mm outer diameter and length of 126 mm, as shown in Fig. 2. However, the more experimental details were presented elsewhere [30].





**Figure 2.** Quartz tube reactor

### 3. Results and Discussions

#### 3.1 Microwave Plasma Dry Reforming of Methane


##### 3.1.1 Effect of $\text{CO}_2/\text{CH}_4$ molar ratio

The  $\text{CO}_2/\text{CH}_4$  molar ratio has a significant effect on the conversions of  $\text{CH}_4$  and  $\text{CO}_2$ , the selectivity's and yields of  $\text{H}_2$  and  $\text{CO}$  and the  $\text{H}_2$  to  $\text{CO}$  molar ratio, as shown in Figure 3(a-d). In our experiments, keeping the  $\text{CH}_4$  and  $\text{N}_2$  flow rates constant of 0.2 L/min and 1.5 L/min and microwave power of 700 W. The  $\text{CO}_2/\text{CH}_4$  molar ratio was changed from 2/1 to 5/1. Figure 3(a)-(d) depict the result of the influence of the  $\text{CO}_2/\text{CH}_4$  ratio on the conversions of  $\text{CH}_4$  and  $\text{CO}_2$ , the selectivity's and yields of  $\text{H}_2$  and  $\text{CO}$ , and  $\text{CO}$  and the  $\text{H}_2/\text{CO}$  ratio was investigated by varying the  $\text{CO}_2/\text{CH}_4$  ratio. As shown in Figure 3(a) and (b), the conversions of  $\text{CH}_4$  and the selectivity to  $\text{CO}$  escalated when increasing  $\text{CO}_2/\text{CH}_4$  ratio. Conversely, the increase of  $\text{CO}_2/\text{CH}_4$  ratio leads to decreasing the conversion of  $\text{CO}_2$ , the selectivity's and the yields of  $\text{H}_2$ ,  $\text{CO}$  and  $\text{H}_2/\text{CO}$  ratio, as shown in Figure 3(a)-(d), respectively. The decreased in  $\text{CO}_2$  conversion could be explained because the main reaction of  $\text{CH}_4$  and  $\text{CO}_2$  under microwave plasma at atmospheric pressure was the plasma reforming reaction (see Equation (2)). When  $\text{CO}_2$  amount exceeds the reaction stoichiometry of the main reaction, the conversion of  $\text{CO}_2$  decreased while the conversion of  $\text{CH}_4$  increased [31]. The conversion of  $\text{CH}_4$  is higher than that of  $\text{CO}_2$  under all testing conditions.

In addition, the induction of high amount of  $\text{CO}_2$  in the reactor resulted in larger amount of carbon atoms, which are cracked by electron collision. These radicals are reacted with oxygen atoms to form carbon mono oxide (see Equation 6) while the hydrogen is low because of the formation of water as a consequence of the reaction of hydrogen atoms with oxygen atoms (see Equation 6). So, the selectivity's and yields of  $\text{H}_2$ ,  $\text{CO}$  and the  $\text{H}_2/\text{CO}$  ratio significantly decreased when the  $\text{CO}_2$  content in the gas mixture increased, as shown in Figure 3(b)-(d), respectively [32].

The conversion of  $\text{CH}_4$  was always higher than those of  $\text{CO}_2$ . That can be attributed to the nature of the gas molecules, where these gases have a different molecular structure with different chemical bonds.

Methane has covalent bonds, and a large amount of energy may be released when they are broken [33].




**Figure 3.** Effect of CO<sub>2</sub>/CH<sub>4</sub> Ratio on the Performance Microwave Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>2</sub> and CO<sub>2</sub>; (b) Selectivity of H<sub>2</sub> and CO; (c) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio (input microwave power at 700 W).

Additionally, the rate of dissociation of methane molecule depends on the initial supplied energy. On the other hand, the rate of thermal dissociation of CO<sub>2</sub> was lower due to its dependence on both temperature and the initial concentrations of CO<sub>2</sub> [34] which adversely affect the conversion of CO<sub>2</sub>. N<sub>2</sub> gas is dissociated due to applied microwave energy, so that it is expected the side reaction, which consumes N<sub>2</sub> may occurs. However the results and discussions on N<sub>2</sub> consumption are excluded from this work as they are not the aim of this study. At these parameters, the plasma reaction was stable for more than four hours with the homogeneous plasma flame in the reactor.

### 3.1.2 Effect of total feed flow rate


The effect of the total feed flow rate on the conversions of CH<sub>4</sub> and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub> and CO and the H<sub>2</sub>/CO ratio are shown in Figure 4(a)-(d), respectively. Experiments were conducted with a wide range of the flow rates of carbon dioxide (0.1-0.4 L min<sup>-1</sup>) methane (0.05-0.2 L min<sup>-1</sup>) and nitrogen (0.3-1.5 L min<sup>-1</sup>). The molar ratio of CO<sub>2</sub>/CH<sub>4</sub> of 2/1 and the input power of 700 W were kept constant for all experiments. As seen from the Figure 4(a)-(c), the conversions of CH<sub>4</sub> and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub>, CO and the H<sub>2</sub>/CO ratio slightly decreased with increasing total flow rates. This is because of the reduction in conversion of CH<sub>4</sub> and CO<sub>2</sub> could be related to the residence time of the gases in the microwave discharge zone, and it is reduced with the increasing of gas feed flow rate and led to the shorter treatment time [3].



**Figure 4.** Effect of Total Gas Feed Flow Rate on the Performance Microwave Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>4</sub> and CO<sub>2</sub>; (b) Selectivity of H<sub>2</sub> and CO; (c) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio; (CO<sub>2</sub>/CH<sub>4</sub> ratio at 2/1; input microwave power: 700 W).

### 3.1.3 Effect of input microwave power

It is well known, the input power is an important factor, which affects the dry plasma reforming of methane as it supply the requested energy for plasma formation. In other words, the input power will influence the density of the active species for the reaction. The conversions of CH<sub>4</sub> and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub> and CO, and CO and the H<sub>2</sub>/CO ratio as a function of input microwave power under CO<sub>2</sub>/CH<sub>4</sub> molar ratio of 2/1, and the CH<sub>4</sub>, CO<sub>2</sub>, and N<sub>2</sub> flow rates of 0.2, 0.4 and 1.5 L min<sup>-1</sup> respectively, as shown in Figure 5(a)-(d), respectively. Experiments were performed in wide range of input power from 700 to 1200 W to get better understanding of the effect of input power on the conversions of CH<sub>4</sub>, and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub>, CO and the molar ratio of H<sub>2</sub>/CO. Figure 5(a)-(c) exhibit the CH<sub>4</sub>, and CO<sub>2</sub> conversions, the CO selectivity and yield increased, while the selectivity and yield of H<sub>2</sub> and the ratio of H<sub>2</sub>/CO decreased with increasing the input power (Figure 5(b)-(d)). The increase of input microwave power could provide more energy to dissociate the CH<sub>4</sub> and CO<sub>2</sub> molecules and then leads to cracking of molecules deeply of CH<sub>4</sub> and CO<sub>2</sub> [35]. On the other hand, at high microwave power a side reaction, which consumes H<sub>2</sub> (see Equation 6), occurs and provides enough energy to activate CO<sub>2</sub> to form CO. As a consequence, the product ratio H<sub>2</sub>/CO decreases with the increasing microwave power [36].





**Figure 5.** Effect of Input MW Power on the Performance Microwave Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>4</sub> and CO<sub>2</sub>; (b) Selectivity of H<sub>2</sub> and CO; (C) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio (CO<sub>2</sub>/CH<sub>4</sub> ratio at 2/1; the feed gas rate at 2.1 L min<sup>-1</sup>).

### 3.2 Microwave Plasma Steam Combined with Dry Reforming of Methane

#### 3.2.1 Steam Concentration

To understand the reaction pathway of CSDRM, the steam concentration was varied at a fixed feed flow rate of CH<sub>4</sub>, CO<sub>2</sub> of 0.008, 0.016 mole min<sup>-1</sup>, CO<sub>2</sub>/CH<sub>4</sub> ratio of 2/1 and input microwave power of 700 W. Figure 6(a)-(d) show the effects of steam concentration on the CH<sub>4</sub> and CO<sub>2</sub> conversions, H<sub>2</sub> and CO the selectivity's and yields and the H<sub>2</sub>/CO ratio. As shown in Figure 6(a)-(d), CH<sub>4</sub> conversions, selectivity and yield of H<sub>2</sub> and H<sub>2</sub>/CO mole ratio increased from 79.35%, 50.12%, 39.77% and 0.86 to 82.74%, 98.79%, 81.73% and 5.23 respectively, whereas CO<sub>2</sub> conversion and CO selectivity and yield slightly decreased from 44.82%, 58.42% and 32.89% to 19.23%, 18.87% and 9.04% respectively with increasing the steam concentration. This is because the steam has more reductive and oxidative radicals (H, OH, and O) in the CSDRM process, and these radicals lead to increasing CH<sub>4</sub> conversion, H<sub>2</sub> and CO selectivity, H<sub>2</sub> and CO yield and H<sub>2</sub>/CO ratio [37].







**Figure 6.** Effect of Steam Concentration on the Performance Microwave Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>4</sub> and CO<sub>2</sub>; (b) Selectivity of H<sub>2</sub> and CO; (c) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio; (feed flow rate of CH<sub>4</sub>, CO<sub>2</sub> at 0.008, 0.016, 0.062 mole min<sup>-1</sup>, CO<sub>2</sub>/CH<sub>4</sub> ratio at 2/1 and input microwave power at 700 W).

### 3.2.2 Effect total feed flow rate

The steam additions have a noteworthy effect on the conversions of CH<sub>4</sub>, and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub> and CO and the H<sub>2</sub>/CO ratio are shown in Figure 7(a)-(d), respectively. The total feed gas flow rate of H<sub>2</sub>O, CO<sub>2</sub>, CH<sub>4</sub> and N<sub>2</sub> ranged from 0.02 to 0.15 mole min<sup>-1</sup>, as keeping constant the input power of 700 W. As is expected, CH<sub>4</sub> conversion, the product selectivity and the yields of H<sub>2</sub> and the H<sub>2</sub>/CO ratio are enhanced with increasing the total feed flow rate, pointing to the fact that combined reforming by H<sub>2</sub>O and CO<sub>2</sub> is stronger than dry reforming (see Figure 7(a)-(d)). This is because the steam molecules could dissociated into OH and H radicals, reacting with CH<sub>4</sub> and resulting in the lower probability of CH<sub>4</sub> recombination due to the production of CH<sub>3</sub> and other by products [38, 39]. The CH<sub>4</sub> reacted with H<sub>2</sub>O instead of CO<sub>2</sub> with increasing amount of steam in the feed stream due to the more stable nature of CO<sub>2</sub>. On the contrary, the increase of steam content caused a considerable decrease of the conversion of CO<sub>2</sub>, CO selectivity, as shown in Figure 7(a)-(c). Although higher steam amounts resulted in the more CH<sub>4</sub> conversion, H<sub>2</sub> selectivity, H<sub>2</sub> yield and the H<sub>2</sub>/CO ratio, increasing steam content did not favour CO<sub>2</sub>, selectivity and yield of CO due to the fixed CO<sub>2</sub>/CH<sub>4</sub> molar ratio in the feed. The conversions of CO<sub>2</sub> and H<sub>2</sub>O were dampened as a result of the RWGS reaction (see Equation (6)).






**Figure 7.** Effect of Total Gas Feed Flow Rate with Water on the Performance Microwave Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>4</sub> and CO<sub>2</sub>; (b) Selectivity of H<sub>2</sub> and CO; (c) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio; (input microwave Power at 700W).


### 3.2.3 Effect of input microwave power

The effect of microwave power on the conversions of CH<sub>4</sub> and CO<sub>2</sub>, the selectivity's and yields of H<sub>2</sub> and CO, and CO and the H<sub>2</sub>/CO ratio, as shown in Figure 8(a)-(d), respectively. The input microwave power changed from 700 to 1200 W. The CO<sub>2</sub>/CH<sub>4</sub> molar ratio was 2/1, and the CH<sub>4</sub>, CO<sub>2</sub> and steam flow rate were 0.008, 0.016, and 0.065 mole min<sup>-1</sup>, respectively. Figure 8(a)-(c) depict the conversions of CH<sub>4</sub> and CO<sub>2</sub>, the selectivity of CO and yields of H<sub>2</sub> and CO increased, while the ratio of H<sub>2</sub>/CO decreased with increasing the input power (Figure 8(d)). The reason for this has been explained previously. The selectivity of H<sub>2</sub> did not change with increase the microwave power (Figure 8(b) and (c)). In this study, we observed the amount of water, and the amount of solid carbon powder out the quartz tube low compared with the CO<sub>2</sub> reforming.



**Figure 8.** Effect of Input MW Power with Water on the Performance MW Plasma Dry Reforming Reaction; (a) Conversion of CH<sub>4</sub> and CO<sub>2</sub>; (b) Selectivities of H<sub>2</sub> and CO; (c) Yield of H<sub>2</sub> and CO; (d) H<sub>2</sub>/CO Ratio (total feed gas rate at 0.15 mole min<sup>-1</sup>).

The combined effects of microwave plasma methane dry reforming and methane steam with dry reforming were compared and displayed in Figure 9(a)-(d). The conversions of CH<sub>4</sub> and CO<sub>2</sub> over dry reforming of methane were about 79.35%, and 44.82% respectively, the selectivity's and yields of H<sub>2</sub> and CO, and the H<sub>2</sub>/CO ratio were 50.12%, 58.42%, 39.77%, 32.89% and 0.86, respectively. When the steam adding with dry reforming of methane, the conversion of CH<sub>4</sub>, selectivity and yield of H<sub>2</sub> and synthesis ratio were improved apparently, as shown in Figure 9(a)-(c), respectively. The conversions of CH<sub>4</sub> and CO<sub>2</sub> were 82.74% and 19.23% respectively. The selectivity's, yields to H<sub>2</sub> and CO and the H<sub>2</sub>/CO ratio were 98.79%, 18.87%, 81.73%, 9.04% and 5.23, respectively. The conversions of CH<sub>4</sub> was 82.74% under combined steam and dry reforming of methane, which was higher than using the dry reforming of methane. Similar tendency the selectivity and yield of H<sub>2</sub> and H<sub>2</sub>/CO ratio were also improved under combined of steam and dry reforming of methane. However, it was observed for conversion of CO<sub>2</sub> decreased with adding the steam. The selectivity of H<sub>2</sub> was 98.79% and that of H<sub>2</sub>/CO ratio was 5.23, which was even higher than those obtained in dry reforming of methane.



**Figure 9.** Effect of H<sub>2</sub>O on equilibrium (a) CH<sub>4</sub> and CO<sub>2</sub> Conversions; (b) H<sub>2</sub> and CO Selectivities; (c) H<sub>2</sub> and CO Yields and (d) H<sub>2</sub>/CO Ratio for combined DR-SR as a function of Microwave Power at 700 W (CO<sub>2</sub>/CH<sub>4</sub>: 2/1; the total gas feed rate at 2.1 L min<sup>-1</sup> and the total feed steam rate at 24.5 L min<sup>-1</sup>).

#### 4. Conclusions

In this paper, the effect of steam adding on the syngas formation has been studied in a microwave plasma reactor at atmospheric pressure for syngas production. Based on the measured results the following conclusions can be made:

1. With H<sub>2</sub>O addition, the high conversions of CH<sub>4</sub> and CO<sub>2</sub> were 82.74% and 19.23% of the steam reforming of methane can achieved. At these conversion levels, the selectivity's of H<sub>2</sub> and CO, the yields of H<sub>2</sub> and CO and H<sub>2</sub>/CO ratio were 98.79%, 18.87%, 81.73%, 9.04% and 5.23, respectively.
2. The CH<sub>4</sub> conversion, H<sub>2</sub> and CO selectivity, H<sub>2</sub> and CO yield, and H<sub>2</sub>/CO ratio were affected by the H<sub>2</sub>O concentration in the feed significantly.
3. The combined SRM and DRM process is very sensitive with the operating conditions such as the input

microwave power and total feed flow rate.

4. The desired syngas ratio  $H_2/CO$  for F-T process can be reached by optimising the  $H_2O$  concentration in the feed and input microwaves power.

### Acknowledgements

The first author would like to gratefully acknowledge the Ministry of Higher Education & Scientific Research in Iraq for their sponsorship for his PhD study at Curtin University.

### References

- [1] X. Tu, J.C. Whitehead, Plasma dry reforming of methane in an atmospheric pressure AC gliding arc discharge: co-generation of syngas and carbon nanomaterials, *international journal of hydrogen energy* 39(18) (2014) 9658-9669.
- [2] J. Ross, A. Van Keulen, M. Hegarty, K. Seshan, The catalytic conversion of natural gas to useful products, *Catalysis Today* 30(1-3) (1996) 193-199.
- [3] D. Pakhare, J. Spivey, A review of dry ( $CO_2$ ) reforming of methane over noble metal catalysts, *Chemical Society Reviews* 43(22) (2014) 7813-7837.
- [4] M.M. Ghouri, S. Afzal, R. Hussain, J. Blank, D.B. Bukur, N.O. Elbashir, Multi-scale modeling of fixed-bed Fischer Tropsch reactor, *Computers & Chemical Engineering* 91 (2016) 38-48.
- [5] A. Kasht, R. Hussain, M. Ghouri, J. Blank, N.O. Elbashir, Product analysis of supercritical Fischer-Tropsch synthesis: utilizing a unique on-line and off-line gas chromatographs setup in a bench-scale reactor unit, *American Journal of Analytical Chemistry* 6(08) (2015) 659.
- [6] J.R. Rostrup-Nielsen, New aspects of syngas production and use, *Catalysis today* 63(2) (2000) 159-164.
- [7] M. Usman, W.W. Daud, H.F. Abbas, Dry reforming of methane: influence of process parameters—a review, *Renewable and Sustainable Energy Reviews* 45 (2015) 710-744.
- [8] B. Abdullah, N.A.A. Ghani, D.-V.N. Vo, Recent advances in dry reforming of methane over Ni-based catalysts, *Journal of Cleaner Production* 162 (2017) 170-185.
- [9] W. Wang, S. Wang, X. Ma, J. Gong, Recent advances in catalytic hydrogenation of carbon dioxide, *Chemical Society Reviews* 40(7) (2011) 3703-3727.
- [10] P.L. Spath, D.C. Dayton, Preliminary screening-technical and economic assessment of synthesis gas to fuels and chemicals with emphasis on the potential for biomass-derived syngas, *National Renewable Energy Lab Golden Co*, 2003.
- [11] J. Pacheco, G. Soria, M. Pacheco, R. Valdivia, F. Ramos, H. Frías, M. Durán, M. Hidalgo, Greenhouse gas treatment and  $H_2$  production, by warm plasma reforming, *international journal of hydrogen energy* 40(48) (2015) 17165-17171.
- [12] S. Rowshanzamir, M. Eikani, Autothermal reforming of methane to synthesis gas: Modeling and simulation, *international journal of hydrogen energy* 34(3) (2009) 1292-1300.
- [13] G. Centi, E.A. Quadrelli, S. Perathoner, Catalysis for  $CO_2$  conversion: a key technology for rapid introduction of renewable energy in the value chain of chemical industries, *Energy & Environmental Science* 6(6) (2013) 1711-1731.
- [14] J. Hubert, M. Moisan, A. Ricard, A new microwave plasma at atmospheric pressure, *Spectrochimica Acta Part B: Atomic Spectroscopy* 34(1) (1979) 1-10.
- [15] S.T. Oyama, P. Hacırlıoğlu, Y. Gu, D. Lee, Dry reforming of methane has no future for hydrogen production: comparison with steam reforming at high pressure in standard and membrane reactors, *international journal of hydrogen energy* 37(13) (2012) 10444-10450.
- [16] G.A. Olah, A. Goepfert, M. Czaun, T. Mathew, R.B. May, G.S. Prakash, Single step bi-reforming and oxidative bi-reforming of methane (natural gas) with steam and carbon dioxide to metgas ( $CO-2H_2$ ) for methanol synthesis: self-sufficient effective and exclusive oxygenation of methane to methanol with oxygen, *Journal of the American Chemical Society* 137(27) (2015) 8720-8729.
- [17] M.M. Noureldin, N.O. Elbashir, M.M. El-Halwagi, Optimization and selection of reforming approaches for syngas generation from natural/shale gas, *Industrial & Engineering Chemistry Research* 53(5) (2013) 1841-1855.

- [18] A.N. Pour, M. Mousavi, Combined reforming of methane by carbon dioxide and water: Particle size effect of Ni–Mg nanoparticles, *International Journal of Hydrogen Energy* 40(38) (2015) 12985-12992.
- [19] A.R. Kim, H.Y. Lee, D.H. Lee, B.-W. Kim, C.-H. Chung, D.J. Moon, E.J. Jang, C. Pang, J.W. Bae, Combined Steam and CO<sub>2</sub> Reforming of CH<sub>4</sub> on LaSrNiO<sub>x</sub> Mixed Oxides Supported on Al<sub>2</sub>O<sub>3</sub>-Modified SiC Support, *Energy & Fuels* 29(2) (2015) 1055-1065.
- [20] V.R. Choudhary, K.C. Mondal, CO<sub>2</sub> reforming of methane combined with steam reforming or partial oxidation of methane to syngas over NdCoO<sub>3</sub> perovskite-type mixed metal-oxide catalyst, *Applied Energy* 83(9) (2006) 1024-1032.
- [21] D. Czyłkowski, B. Hrycak, M. Jasiński, M. Dors, J. Mizeraczyk, Microwave plasma-based method of hydrogen production via combined steam reforming of methane, *Energy* 113 (2016) 653-661.
- [22] L. Li, H. Wang, X. Jiang, Z. Song, X. Zhao, C. Ma, Microwave-enhanced methane combined reforming by CO<sub>2</sub> and H<sub>2</sub>O into syngas production on biomass-derived char, *Fuel* 185 (2016) 692-700.
- [23] R. Snoeckx, Y. Zeng, X. Tu, A. Bogaerts, Plasma-based dry reforming: improving the conversion and energy efficiency in a dielectric barrier discharge, *RSC Advances* 5(38) (2015) 29799-29808.
- [24] W.-C. Chung, M.-B. Chang, Dry reforming of methane by combined spark discharge with a ferroelectric, *Energy Conversion and Management* 124 (2016) 305-314.
- [25] P. Jamróz, W. Kordylewski, M. Wnukowski, Microwave plasma application in decomposition and steam reforming of model tar compounds, *Fuel Processing Technology* 169 (2018) 1-14.
- [26] M.S. Aw, I.G.O. Crnivec, P. Djinovic, A. Pintar, Strategies to enhance dry reforming of methane: Synthesis of ceria-zirconia/nickelcobalt catalysts by freeze-drying and NO calcination, *International Journal of Hydrogen Energy* 39(12636) (2014) e12647.
- [27] M. Nüchter, B. Ondruschka, W. Bonrath, A. Gum, Microwave assisted synthesis—a critical technology overview, *Green chemistry* 6(3) (2004) 128-141.
- [28] J. Menéndez, A. Arenillas, B. Fidalgo, Y. Fernández, L. Zubizarreta, E.G. Calvo, J.M. Bermúdez, Microwave heating processes involving carbon materials, *Fuel Processing Technology* 91(1) (2010) 1-8.
- [29] S. Heijkers, R. Snoeckx, T.s. Kozák, T. Silva, T. Godfroid, N. Britun, R. Snyders, A. Bogaerts, CO<sub>2</sub> conversion in a microwave plasma reactor in the presence of N<sub>2</sub>: elucidating the role of vibrational levels, *The Journal of Physical Chemistry C* 119(23) (2015) 12815-12828.
- [30] N.M. Alawi, A. Barifcani, H.R. Abid, Optimisation of CH<sub>4</sub> and CO<sub>2</sub> conversion and selectivity of H<sub>2</sub> and CO for the dry reforming of methane by a microwave plasma technique using a Box–Behnken design, *Asia-Pacific Journal of Chemical Engineering* (2018) e2254.
- [31] A. Serrano-Lotina, L. Daza, Influence of the operating parameters over dry reforming of methane to syngas, *International Journal of Hydrogen Energy* 39(8) (2014) 4089-4094.
- [32] C.-H. Liao, R.-F. Horng, Experimental study of syngas production from methane dry reforming with heat recovery strategy, *International Journal of Hydrogen Energy* 42(40) (2017) 25213-25224.
- [33] J.W. Moore, C.L. Stanitski, *Chemistry: The molecular science*, Cengage Learning 2014.
- [34] S. Rayne, *Thermal carbon dioxide splitting: A summary of the peer-reviewed scientific literature*, (2008).
- [35] A. Indarto, J.-W. Choi, H. Lee, H.K. Song, Effect of additive gases on methane conversion using gliding arc discharge, *Energy* 31(14) (2006) 2986-2995.
- [36] A. Aziznia, H.R. Bozorgzadeh, N. Seyed-Matin, M. Baghalha, A. Mohamadalizadeh, Comparison of dry reforming of methane in low temperature hybrid plasma-catalytic corona with thermal catalytic reactor over Ni/Al<sub>2</sub>O<sub>3</sub>, *Journal of Natural Gas Chemistry* 21(4) (2012) 466-475.
- [37] T. Jiang, Y. Li, C.-j. Liu, G.-h. Xu, B. Eliasson, B. Xue, Plasma methane conversion using dielectric-barrier discharges with zeolite A, *Catalysis Today* 72(3) (2002) 229-235.
- [38] J. Sutherland, M.C. Su, J. Michael, Rate constants for H+ CH<sub>4</sub>, CH<sub>3</sub>+ H<sub>2</sub>, and CH<sub>4</sub> dissociation at high temperature, *International Journal of Chemical Kinetics* 33(11) (2001) 669-684.
- [39] A. Bonard, V. Daële, J.-L. Delfau, C. Vovelle, Kinetics of OH Radical Reactions with Methane in the Temperature Range 295–660 K and with Dimethyl Ether and Methyl-tert-butyl Ether in the Temperature Range 295–618 K, *The Journal of Physical Chemistry A* 106(17) (2002) 4384-4389.